INCH-POUND

MIL-DTL-11484/30G
9 May 2002
SUPERSEDING
MIL-DTL-11484/30F
27 May 1997

DETAIL SPECIFICATION SHEET

LAPEL BUTTON, EXCEPTIONAL CIVILIAN SERVICE AWARD, AIR FORCE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-11484 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

DASH NO.
-1, -4: Exceptional Civilian Service
-2, -5: Additional Exceptional Civilian Service
-3, -6: Exceptional/Meritorious Civilian Service (DESIGNATES RECIPIENT RECEIVED BOTH AWARDS)

MATERIAL:

-1, -4: Red Brass
-2, -5: Red Brass with a Minimum 2 Point, Grade A, Single Stone, White Synthetic Cubic Zirconia
-3, -6: Red Brass with a Minimum 2 Point Ruby Stone (which may be genuine or synthetic)

FINISH: Gold Plated, Rose Gold Plated, Matte Finished, Polished Highlights, and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 20.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:14Z
Check the source to verify that this is the current version before use.

DIMENSIONS:

DIAMETER: 17/32 inch (REF)
THICKNESS: 0.050 inch ± 0.005 inch

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The designs for -1 and -4 are identical to the figure shown. The designs for -2, -3, -5, and -6 are identical to the figure shown except for the stone located at the center of the eagle's breast. The stones shall be set in the eagle's breast with a three or four bead setting.

3. All lapel buttons shall be lacquered.

4. Attaching device shall be as follows:

-1, -2, -3: Prong with pick and flat ball clutch. The prong shall be centered on the reverse side and fused or soldered to the lapel button.
-4, -5, -6: Pin and catch type fused or soldered to the reverse of the lapel button. The pin shall be located on the horizontal center line of the lapel button with hinge and catch equidistant from the outer edges.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH
Air Force - 11

Preparing activity:
Army - IH

Review activities:
Air Force - 99
DLA - CT

(Project No. 8455-0093/001)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:14Z
Check the source to verify that this is the current version before use.