NOT MEASUREMENT SENSITIVE

MIL-DTL-11484/30K
2 May 2024
SUPERSEDING
MIL-DTL-11484/30J
1 July 2019

DETAIL SPECIFICATION SHEET

LAPEL BUTTON, EXCEPTIONAL CIVILIAN SERVICE AWARD, U.S. AIR FORCE

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-11484.



DASH NO.
-1, -4: Exceptional Civilian Service
-2, -5: Additional Exceptional Civilian Service
-3, -6: Exceptional/Meritorious Civilian Service
(DESIGNATES RECIPIENT RECEIVED BOTH AWARDS)

MATERIAL:
-1, -4: Red Brass 85/15 (UNS Alloy No. C-230)
-2, -5: Red Brass (UNS Alloy No. C-230) with a Minimum 2 Grade A Single Stone, White Synthetic Cubic Zirconia.
-3, -6: Red Brass (UNS Alloy No. C-230) with a minimum 2 Point Ruby Stone (Which may be genuine or synthetic)

FINISH: 24K Gold Plated, Matte Finish, Polished Highlights and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 8.

DIMENSION:
DIAMETER (Circumscribed): 17/32 inch (REF)
THICKNESS: 0.050 inch $\pm$ 0.010 inch

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:14Z
Check the source to verify that this is the current version before use.

ATTACHING DEVICE:

1. -1, -2, -3: Prong with pick and flat ball clutch. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

2. -4, -5, -6: Pin and catch type fused or soldered to the reverse of the lapel button. The pin shall be located on the horizontal center line of the lapel button with hinge and catch equidistant from the outer edges.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The designs for -1 and -4 are identical to the figure shown. The designs for -2, -3, -5, and -6 are identical to the figure shown except for the stone located at the center of the eagle's breast. The stones shall be set in the eagle's breast with a three or four bead setting.

3. All lapel buttons shall be lacquered.

CHANGES FROM PREVIOUS ISSUE: The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - IH
Air Force - 11

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2024-131)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:14Z
Check the source to verify that this is the current version before use.