MILITARY SPECIFICATION

BAG, FOOD SAMPLE, Polyethylene, Disposable

This limited coordination Military specification has been prepared by the Defense Personnel Support Center based upon currently available technical information, but it has not been approved for promulgation. It is subject to modification. However, pending its promulgation as a coordinated Military specification, it may be used in procurement.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers two sizes of sterile disposable sample bags for biological specimens.

1.2 Classification.

1.2.1 Sizes. The bags shall be the following sizes (see 6.1):

Size 1 - 6 fluid ounces (fl. oz.) nominal capacity

Size 2 - 18 fl. oz. nominal capacity

2. APPLICABLE DOCUMENTS

2.1 Specifications and standards. The following documents, of the issue in effect on date of invitations for bid or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

PPP-B-585	Boxes, Wood, Wirebound.
PPP-B-601	Boxes, Wood, Cleated-Plywood.
PPP-B-621	Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	Box, Fiberboard.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:30Z
Check the source to verify that this is the current version before use.

Military

MIL-L-10547	Liners, Case and Sheet, Overwrap, Water-Vaporproof, or Waterproof, Flexible.
MIL-S-36586	Sterilization Test Strip Set, Bacterial Spore.

STANDARDS

Federal

FED-STD-406	Plastic, Methods of Testing.

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	Marking for Shipment and Storage.

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitations for bid or requests for proposal shall apply.

U. S. DEPARTMENT OF AGRICULTURE, AGRICULTURAL RESEARCH SERVICE

Code of Federal Regulations, Title 21, Chapter 1, Part 121, Subpart F, Section 2501, Olefin Polymers.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, D. C. 20402.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:30Z
Check the source to verify that this is the current version before use.

U. S. PHARMACOPEIAL CONVENTION, INC.

Pharmacopeia of the United States

(Application for copies should be addressed to the Mack Publishing Company, Easton, Pa. 18042.)

3. REQUIREMENTS

3.1 Material. Material shall be suitable for the purpose intended and shall be as herein specified.

3.1.1 Polyethylene Polyethylene film shall be nontoxic and safe for use in contact with food in accordance with Code of Federal Regulations, Title 21, Section 121.2501, Olefin Polymers, and shall be 0.003 ± 0.006 inch thick. Tensile strength shall be a minimum of 2650 pounds per square inch (p.s.i.) machine direction, 2300 p.s.i. transverse direction when tested as specified in 4.4.1.

3.1.2 Tape. Tape shall be a minimum of 1/4 inch wide and one side shall be treated with adhesive. Weight gain shall not exceed 10% and side with adhesive shall stick to the bag when tested as specified in 4.4.2.

3.1.3 Wire. Wire shall be 0.019 inch diameter steel wire. Commercial tolerances shall apply to diameter of wire. Wire shall be tin- or copper-coated or galvanized.

3.1.4 Cellulose acetate tab. Cellulose acetate tab shall be 0.002 ± .0005 inch thick.

3.2 Construction. Bag shall be fabricated of polyethylene. Bag shall be completely enclosed, and closure shall be accomplished by heat sealing. A scored line shall extend completely across the width of the bag 7/16 ± 1/8 inch from one end. Two wires shall be in place below, but not more than 3/8 inch below the scored line on each side of the bag. Two pieces of tape shall completely cover the wires, shall secure the wire to the bag and shall be completely below the scored line. Where they extend beyond the polyethylene portion of the bag, the two pieces of tape shall adhere to each other in such a way that they form a cover for the wires and provide a gripping area for opening, closing and sealing the container. A cellulose acetate tab, a minimum of 1/4 inch wide and extending a minimum of 3/8 inch below the tape, shall be securely attached under the tape midway ± 1/2 inch between the edges of the bag.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:30Z
Check the source to verify that this is the current version before use.

3.3 Dimensions. Length and width of the polyethylene portion of the bag shall be as follows:

	Length ± 1/4 inch	Width ± 1/4 inch
Size 1	7-1/4 inches	2-3/4 inches
Size 2	9 inches	4-1/4 inches

3.4 Performance. The bag shall function as indicated in 3.4.1 and 3.4.2.

3.4.1 Opening. The bag shall open and shall remain open when the following steps are taken:

a. The tape shall be completely torn off at the scored line.

b. The wires shall be separated by pulling the tabs outward.

c. The wires shall be further separated by pushing the ends of the wires toward the center of the bag.

3.4.2 Closing. The bag shall be sealed and shall remain sealed when the following steps are taken:

a. Sample shall be placed in open bag (For category 152, Table III, 50 milliliters [ml.] of water shall be used).

b. The wires shall be straightened as much as possible by pulling the ends of the wires.

c. The bag shall be revolved around the wires for three complete revolutions and ends of the wires turned inward against the opposite face to the fold.

3.5 Heat seal. The heat seal tensile strength shall be a minimum of 60 percent of the tensile strength of the polyethylene, when tested as specified in 4.4.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:30Z
Check the source to verify that this is the current version before use.

3.6 Sterility. The bags shall be sterile when tested with a biological indicator as specified in 4.4.3.

3.6.1 Certificate of sterility. A certificate of sterility, stating that samples from each sterilizer lot have been tested and found to be sterile, shall be submitted to the procuring activity. The certificate of sterility shall include:

a. Item identification.
b. Federal stock number.
c. Contract or purchase order number.
d. Sterility lot or control number.
e. Date of sterilization.
f. Quantity of product in sterilizer lot.
g. Type of sterilization (gas, radiation, heat, steam, etc.).
h. Form of biological indicator (i.e., inoculated paper spore strip or carrier, inoculated product, or inoculated simulated product).
i. Test organism(s) and population density used.
j. Test medium, incubation temperature, incubation time, and dates of tests.
k. Number of test units.
l. Statement that samples comply with sterility tests.
m. Signature of head of laboratory or a designated qualified alternate.

When inspection is made at destination, the certificate of sterility shall be submitted by the contractor to the Directorate of Medical Materiel, ATTN: DPSC-ATQ, Defense Personnel Support Center, 2800 South 20th Street, Philadelphia, Pa. 19101, and a copy forwarded with each shipment to the consignee. When inspection is made at source, certificate of sterility shall be furnished to the cognizant Government Quality Assurance Representative for submission to the procuring activity.

3.6.2 Sterility lot. A sterility lot is that single quantity of product subjected to the same manufacturing operation and simultaneously sterilized in the same sterilizer chamber. Each unit package shall be clearly marked with a sterility lot (control) number and date of sterilization as specified in 5.3.1. Each sterility lot shall be traceable to the pertinent manufacturing lot(s).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:30Z
Check the source to verify that this is the current version before use.

3.7 Identification marking. The name or registered trademark of the manufacturer shall be marked on each bag.

3.8 Instructions. Each package shall contain instructions for use. As a minimum, these instructions shall cover the procedures in 3.4. Instructions shall be marked on unit package or shall be furnished as a separate sheet.

3.9 Workmanship. Workmanship shall be first class throughout. The bags shall be free from defects listed in table III or other defects which detract from their appearance or may impair their serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Records. Records of examinations and tests performed by or for the contractor shall be maintained by the contractor and made available to the Government, upon the Government's request, at any time, or from time to time, during the performance of the contract and for a period of 3 years after delivery of the supplies to which such records relate.

4.1.2 Inspection. Inspection, as used in this specification, is defined as both examination (such as visual, or auditory, investigation without the use of special laboratory appliances or procedures and testing (determination by technical means of physical and chemical properties) of the item.

4.1.3 Certificate of quality. Certificate of quality, supplied by the manufacturer of the tape and polyethylene film, may be furnished in lieu of actual performance of such testing by the contractor, provided lot identity has been maintained and can be demonstrated to the Government. The Certificate shall include the name of the contractor, the contract number, the name of the manufacturer or supplier, the FSN, the Item Identification, the name of the component/material, the lot number, the lot size, the sample size, the date of testing, the test method, individual test results, and the specification requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:30Z
Check the source to verify that this is the current version before use.

4.2 Sampling.

4.2.1 For examination. Sampling for examination shall be conducted in accordance with MIL-STD-105 and table I. Unit of product shall be one bag.

Table I. For examination

	Inspection level	AQL (percent defective)
For visual examination		
Major A defects	II	1.0
Major B defects	S-1	1.0
Minor defects	II	2.5
For dimensional examination	S-1	2.5

4.2.2 For tests. Sampling for tests shall be conducted in accordance with MIL-STD-105 and table II. Unit of product shall be one bag, and acceptance number shall be zero.

Table II. For tests

Characteristic	Requirement	Test procedure	Inspection level
Tensile strength	3.1.1	4.4.1	S-1
Heat seal	3.5	4.4.1	S-1
Water absorption	3.1.2	4.4.2	S-1
Sterility	3.6	4.4.3	S-1

4.3 Examination. The bags shall be examined to determine compliance with all requirements contained in this specification. Examination shall include but shall not be limited to the defects listed in table III.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:30Z
Check the source to verify that this is the current version before use.

Table III. Classification of defects

Categories	Defects
Major A	
101	Component part missing.
102	Bag not free of tears or holes.
103	Tape not secured or does not cover wire.
104	Tab not secured.
105	Score line does not extend completely across the width of the bag.
Major B	
151	Bag cannot be opened when procedures in 3.4.1 are followed.
152	Bag cannot be closed or sealed or is not free of leakage when procedures in 3.4.2 are followed.
Minor	
201	Wire not completely covered (protrudes from the ends of the tape).
202	Identification marking not complete, correct or legible.

4.3.1 Dimensional examination. The bags shall be examined for defects in dimensions. Flat, unopened bags shall be used for measurements.

4.4 Tests. Tests shall be conducted to determine compliance with specification requirements.

4.4.1 Tensile strength. Tensile strength shall be tested in accordance with Federal Test Method Standard No. 406, method 1013, A or B.

4.4.2 Water absorption. Tape shall be weighed. Tape shall be immersed in water at ambient temperature for one hour. Tape shall be reweighed and adhesive side shall be pressed to the polyethylene portion of the bag.

4.4.3 Sterility test. The bags shall be tested for sterility in accordance with the method specified in the U.S.P. for transfusion and infusion assemblies using inoculated product, inoculated simulated product, or paper spore strip (carrier). Product containing a biological indicator shall be marked or labeled so that it clearly differentiates from product intended for distribution. The incubation medium and minimum time in each case shall be soybean casein digest for 7 days for inoculated product, inoculated simulated product, or paper spore strip (carrier). The incubation temperature shall be as indicated in paragraph 4.4.3.1. The minimum number of test units, regardless of lot size, shall be 10, except for inoculated carrier which shall be 20 for Type I Sterilization and 30 for Type II Sterilization including inoculated carrier and product test units. The inspection level shall be as indicated in Table II, Sampling Criteria for Tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:30Z
Check the source to verify that this is the current version before use.

4.4.3.1 Inoculated product or simulated product. For each type of sterilization, the organism used shall be as listed below:

Type of Sterilization	Organism	Incubation Temperature
Steam	B. stearothermophilus	55° - 65° C
Dry Heat	B. stearothermophilus, or	55° - 65° C
	B. subtilis var. niger (or globigii)	30° - 35° C
Gas	B. subtilis var. niger (or globigii)	30° - 35° C
Radiation	B. pumilus	30° - 35° C

The number of viable cells shall be sufficient to provide assurance that the product has been sterilized.

4.4.3.2 Inoculated carrier. Inoculated carriers (paper spore strips) if used, shall be in accordance with MIL-S-36586. Other paper carriers shall be inoculated to be of equivalent resistance. The method of incubation and number of test units shall be as indicated in 4.4.3 Sterility test and 4.4.3.1 inoculated product or simulated product. The method of sterilization will control the organism in the spore strip to be tested for as shown in 4.4.3.1. NOTE: When an inoculated carrier is chosen, product samples must also be tested as required by the U.S.P.

4.4.3.3 Alternate method. Suppliers conducting sterility tests or designating lots in a manner other than that indicated herein shall submit proof that the alternate method provides equal assurance concerning the sterility of the product. However, all sterility tests shall be conducted using biological indicators. Requests for approval of any alternate method of testing for sterility shall be made to the Contracting Officer, and approval obtained before employment of the alternate method on a government contract.

4.4.3.4 Product testing. Testing for sterility of the product after receipt by the government shall be without a biological indicator and in accordance with the U.S.P.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:30Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packaging.

5.1.1 Unit of issue. Five hundred bags of the size specified constitutes one unit of issue.

5.1.2 Packaging quantities. The number of units of issue indicated in table IV shall be packaged in each unit, intermediate, and exterior container, as applicable, for the required level of protection specified in the procurement document.

Table IV. Packaging quantities

Size	Unit package	Intermediate package	Exterior container
1	1 unit	Not required	20 units
2	1 unit	Not required	6 units

5.1.2.1 Packing variation permitted. If the required number of units in the entire shipment is less than the number of units specified to be overpacked in an exterior container, such units may be packed in an exterior container of suitable size and design, acceptable to a common carrier, which shall insure safe delivery to destination.

5.1.3 Level A.

5.1.3.1 Unit package. Unit package shall be a box of appropriate size and design constructed in accordance with PPP-B-636, type CF, class domestic. Closure of box shall be adequate to prevent spilling of contents under normal handling and to maintain sterility of contents under normal handling.

5.1.4 Level C. Units shall be packaged in standard commercial containers of the size and kind commonly used, which will afford the degree of protection required for shipment and use of the product for its intended purpose.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:30Z
Check the source to verify that this is the current version before use.

5.2 Packing.

5.2.1 Level A.

5.2.1.1 Exterior container. Exterior container shall be designed for a type 2 load and constructed in accordance with PPP-B-585, class 3, style 3; PPP-B-601, overseas type; PPP-B-621, class 2; or PPP-B-636, class weather-resistant, grade V3c. Fiberboard boxes shall conform to the special requirements specified in PPP-B-636.

5.2.1.2 Case liner. Each level A wood box shall be lined with a waterproof case liner conforming to MIL-L-10547. Closure and sealing shall conform to applicable paragraphs of appendix thereto. Case liner shall not be required for fiberboard boxes.

5.2.1.3 Closure. Closure of wood boxes shall be in accordance with appendix of applicable box specification. Closure of each fiberboard box shall be as specified in the appendix, and waterproofing shall conform with 30.4 of PPP-B-636.

5.2.1.4 Strapping. Strapping, when required, shall be in accordance with appendix of applicable box specification.

NOTE: Strapping shall not be required for shipments forwarded to a receiving activity within the continental limits of the United States for storage and redistribution.

5.2.2 Level B.

5.2.2.1 Exterior container. Exterior container shall be designed for a type 2 load and constructed in accordance with PPP-B-585, class 1, style 3; PPP-B-601, domestic type; PPP-B-621, class 1; or PPP-B-636, class domestic. Closure of wood boxes shall be as specified in the appendix of the applicable box specification. Closure of fiberboard boxes shall conform to method II of PPP-B-636. In addition, fiberboard boxes shall conform to the special requirements specified in PPP-B-636.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:30Z
Check the source to verify that this is the current version before use.

5.2.3 Level C. The subject commodity shall be packed in substantial commercial containers of the type, size, and kind commonly used for the purpose, so constructed as to insure acceptance and safe delivery by common or other carriers, at the lowest rate, to point of delivery called for in the contract or purchase order.

5.3 Marking.

5.3.1 Interior packages. Each unit package shall be marked in accordance with MIL-STD-129. When labels are utilized, waterproofing shall be required only when applicable carton is fabricated of water-resistant material. Contract or purchase order number and name of contractor shall be shown. Lot (control) number and the legend: "STERILITY GUARANTEED UNLESS PACKAGE IS DAMAGED OR OPENED" shall be shown. In addition, the method of sterilization (G-Gas, R-Radiation, C-Cold, S-Steam, D-Dry Heat Sterilization) shall be shown following the level and date of packaging. Example: "A-7/71-G". Final sterilization shall be on or after indicated packaging date.

5.3.2 Exterior container. Exterior container shall be marked in accordance with MIL-STD-129. Lot (control) number and the method of sterilization as specified in 5.3.1 shall be shown.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

a. Title, number and date of this specification.
b. Federal Stock Number (FSN).
c. Specify size bag required (see 1.2.1).
d. Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

6.2 This specification does not cover all types, classes, grades or sizes of the commodity indicated by the title of this specification, or those which are commercially available, but is intended to cover the types which are normally procured to meet requirements.

Custodians:
Army - MD
Navy - MS
Air Force - 03

Review activities:
Army - MD
Navy - MS
Air Force - 03

Preparing activity:
Defense Supply Agency - DM

Project No. 6695-0028

Review information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current DODISS.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:30Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

MIL-B-36882 (DSA-DM)

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 PREVIOUS EDITION OF THIS FORM MAY BE USED

Source: https://assist.dla.mil - Downloaded: 2026-10-21T09:30Z
Check the source to verify that this is the current version before use.