MILITARY SPECIFICATION

CASE, MEDICAL INSTRUMENT AND SUPPLY SET,

Nylon, Nonrigid, No. 3

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers an empty case fabricated of nylon cloth. The case contains three compartments, each fitted with a slide fastener closure, and intended to hold an assortment of items of medical materiel. Each case is equipped with a detachable carrying strap.

2. APPLICABLE DOCUMENTS

2.1 The following specifications and standards, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

L-P-394	Plastic Molding Material, Polypropylene, Injection and Extrusion.
V-F-106	Fastener, Slide, Interlocking.
V-T-285	Thread, Polyester.
FF-R-556	Rivets, Solid, Small; Rivets, Split, Small; Rivets, Tubular, Small; and Caps, Rivets, General Purpose.
PPP-B-585	Box, Wood, Wirebound.
PPP-B-601	Box, Wood, Cleated Plywood.
PPP-B-621	Box, Wood, Nailed and Lock Corner.
PPP-B-636	Box, Fiberboard.

Military

MIL-F-495	Finish, Chemical, Black, for Copper Alloys.
MIL-W-530	Webbing, Textile, Cotton, General Purpose, Natural or in Colors.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:27Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

Military

MIL-B-543	Buckle, Tongueless and Web Strap.
MIL-R-3390	Ring, Dee.
MIL-L-3851	Loops, Slide (For Equipage).
MIL-W-4088	Webbing, Textile, Woven Nylon.
MIL-T-5038	Tape, Textile and Webbing, Textile, Reinforcing, Nylon.
MIL-H-9890	Hardware, Individual Load Carrying Equipment; and Hardware, Miscellaneous.
MIL-F-10884	Fasteners, Snap.
MIL-L-11075	Loop, Strap Fastener.
MIL-W-27265	Webbing, Textile, Woven Nylon, Impregnated.
MIL-C-43128	Cloth, Plain Weave, Nylon, Water Repellent, OG-106.
MIL-S-43770/1	Snap Hook, Wire Body, Fixed Loop Eye, Flat Spring Closure, with Retainer.

STANDARDS

Federal

FED-STD-151	Metal, Test Methods.
FED-STD-751	Stitch, Seam and Stitching.

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	Marking for Shipment and Storage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:27Z
Check the source to verify that this is the current version before use.

STANDARDS

Military

MS-51936 Washer, Flat (Burr).

DRAWING

DEFENSE PERSONNEL SUPPORT CENTER

20774 Case, Medical Instrument and Supply Set, Nylon, Nonrigid, No. 3.

(Copies of specifications, standards, and drawing required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposals shall apply.

THE COLOR ASSOCIATION OF THE UNITED STATES, INC.

United States Army Color Card of Standard Shades for Slide Fastener Tapes.

Department of Defense Standard Color Card of Official Standardized Shades for Sewing Threads 1968

(Application for copies of each should be addressed to the Color Association of the United States, Inc., 200 Madison Avenue, New York, N. Y. 10016).

3. REQUIREMENTS

3.1 Component parts. The case shall consist of two small compartments, one large compartment, a pocket, a hood, a closing strap complete with buckle and quick release device, and a detachable carrying strap. The carrying strap shall be fitted with snaphooks, a strap loop and a slide loop.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:27Z
Check the source to verify that this is the current version before use.

3.2 Materials. Except where otherwise specified, materials shall conform to the applicable portions of the specifications, standards, and drawing specified herein, and as described in 3.3 and shall be capable of meeting the requirements specified therein. In addition, the metals shall conform to the chemical requirements of their applicable specifications when tested as specified in section 4. When materials to be used are not specifically designated, those used shall be of the highest commercial quality, and entirely suitable for the purpose intended.

3.2.1 Cloth, nylon. The nylon cloth shall be olive green No. 106, water repellent, conforming to MIL-C-43128.

3.2.2 Webbing.

3.2.2.1 Webbing, nylon. The 3/4-inch nylon webbing shall conform to type Ia of MIL-W-4088. The 1-inch nylon webbing shall conform to type II of MIL-W-4088.

3.2.2.1.1 Color and finish. The nylon webbing shall be dyed olive drab number 7 to match the standard shade, and shall be resin impregnated conforming to class R of MIL-W-27265. The resin impregnated webbing shall conform to the applicable requirements of MIL-W-27265.

3.2.2.2 Webbing, cotton. The 2-inch wide cotton webbing for the carrying strap shall conform to the requirements of MIL-W-530, type II, class 4, and shall be vat dyed olive drab No. 7.

3.2.3 Tape, nylon. The nylon binding tape shall be OG-106 conforming to type III, 3/4-inch of MIL-T-5038.

3.2.4 Thread polyester. The thread for all stitching shall conform to type I, class I, sub-class B, Size F, of V-T-285. The thread shall be dyed olive drab shade S-1, C.I. 66022, except the colorfastness requirements and test methods shall be limited to weathering only.

3.2.5 Polypropylene. The stiffener for the quick release strap shall be made from sheet stock virgin polypropylene material of natural color meeting requirements of type I of L-P-394. The sheet stock shall be 0.040 ± 0.005 inch thick. The plastic stiffener pieces fabricated from the sheet stock shall be produced in such a manner that the long edges of the pieces shall have been parallel with the direction of extrusion (the long edges) of the roll of material from which they are fabricated. The finished pieces shall be uniform in color, texture, and finish and the edges shall be smooth and free from cracks and sharp corners.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:27Z
Check the source to verify that this is the current version before use.

3.2.6 Buckle, nonslip. The 3/4-inch buckle shall conform to type V, class 3 of MIL-B-543.

3.2.7 "D" rings. The "D" (DEE) rings shall be symbol A, class 1, 25/32 inch by 3/8 inch, black chemical finish, of MIL-R-3390.

3.2.8 Fastener, loop. The fastener loop used for the quick release device shall be type III of MIL-H-9890.

3.2.9 Fasteners, snap. The snap fastener on the quick release assembly shall be style 2A, finish 2, black, of MIL-F-10884.

3.2.10 Rivets. The rivets on the fastener loop shall be type XII, tubular, class 3, oval head, grade F, brass 9/64-inch nominal size, conforming to FF-R-556. The rivets shall be given a black chemical finish. The length shall be such as to effect a secure clinch.

3.2.11 Burrs. The burrs on the fastener loop shall be brass, size No. 9, of MS-51936.

3.2.12 Fasteners, slide. Except as specified herein, the slide fasteners shall conform to V-F-106, type I, style 18, size M, two slider, with short tab pulls fitted with webbing thongs. The metal parts shall be brass with a black chemical finish conforming to MIL-F-495.

3.2.12.1 Tape. The slide fastener tapes shall be vat dyed olive drab shade S, conforming to U.S. Army Color Card of Standard Shades for Slide Fastener Tapes, and shall be water repellent and mildew resistant, in accordance with V-F-106. Mildew resistance shall be obtained by using copper-8-quinolinolate only.

3.2.12.1.1 Water repellence. The finished tape shall be tested for water resistance as specified in V-F-106.

3.2.12.2 Salt spray resistance. The slide fasteners shall meet the salt spray resistance requirements specified in V-F-106.

3.2.12.3 Webbing for thongs. Webbing for thongs shall conform to the requirements of V-F-106 for thongs (cotton webbing) except that mildew resistance shall be obtained by using copper-8-quinolinolate only, and the finished length of the thong after assembly to the pull shall be 3-1/2 $\pm$ 1/2 inch.

3.2.13 Loops, slide. Slide loops shall conform to MIL-L-3851 and shall be class 1, style 2, 2 inches.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:27Z
Check the source to verify that this is the current version before use.

3.2.14 Loops, strap. Strap loops shall conform to MIL-L-11075 and shall be type I, brass, style E, 2-1/16 by 1/4 inch, wire.

3.2.15 Snaphooks. Lines 1 and 2, delete: MIL-S-2578 for type I, class 1" and substitute: "MIL-S-43770/1, Material 1.

3.3 Construction. The construction of the case (including detachable carrying strap) shall conform to the requirements specified herein and to those shown on Defense Personnel Support Center Drawing 20774.

3.3.1 Stitching, machine. All stitching shall conform to FED-STD-751 as follows:

For all stitching except overedge stitching; type 301, 8 to 10 stitches per inch.

For overedge stitching (single operation optional); type 503 or 504, 8 to 10 stitches per inch.

For closing seams and overedge stitching (simultaneous operation optional); type 301 in combination with 503, 504 or 502, 8 to 10 stitches per inch.

All edges of closing seams shall be overstitched. There shall be no lubrication of the thread by any means, prior to or during sewing. Any of the operations requiring box, box with cross stitch, W stitching, straight line tacking or any other design of stitching cited in this specification may be performed with an automatic stitching machine provided the requirements for stitch pattern, stitches per inch, size, and types, of thread are met; and at least three or more tying, overlapping, or back stitches are used to secure the ends of stitching.

3.3.1.1 Type 301 stitching. Thread breaks in stitching shall be overstitched not less than 1 inch at each break. Stitching shall be backstitched not less than 1 inch at the ends, except where ends are turned under in a hem or held down by other stitching. Thread tension shall be maintained so that there will be no loose stitching, and the lock will be imbedded in the materials sewed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:27Z
Check the source to verify that this is the current version before use.

3.3.1.2 Overedge stitching. Thread breaks in overedge stitching shall be overstitched not less than 3/4 inch at each break. Thread tension shall be maintained so that there will be no loose stitching.

3.3.2 Setting of snap fasteners. The hole punched before insertion of the male or female part of the fastener shall be smaller than the outside diameter of the fastener tube so that the tube shall be forced through the hole. The fasteners shall be securely clinched.

3.3.3 Setting of rivets. All holes in fabric shall be pre-punched before insertion of the rivets. When installed, the clinched end of the rivet shall be reasonably free of cracks or burrs, and shall have a uniform roll that will effect a secure hold.

3.3.4 Fusing of nylon webbing. All ends of nylon webbing shall be fused after cutting, including bias cuts.

3.4 Marking for identification. Each case (including carrying strap) shall be legibly and permanently marked with black waterproof ink or paint in accordance with the drawing.

3.5 Workmanship. Workmanship shall be first class throughout. Complete cases (including carrying straps) shall be well made and free from defects which detract from their appearance or may impair their serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Records. Records of examinations and tests performed by or for the contractor shall be maintained by the contractor and made available to the Government, upon the Government's request, at any time, or from time to time, during the performance of the contract and for a period of three years after delivery of the supplies to which such records relate.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:27Z
Check the source to verify that this is the current version before use.

4.1.2 Inspection. Inspection, as used in this specification, is defined as both examination (such as visual or auditory investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item.

4.1.3 Certificates of quality. Certificates of quality, supplied by the manufacturer of the cloth, fasteners, hardware, tape, and webbing, may be furnished in lieu of actual performance of such testing by the contractor, provided lot identity has been maintained and can be demonstrated to the Government. The certificate shall include the name of the contractor, the contract number; the name of the manufacturer or supplier, the FSN, the item identification, the name of the component/material, the lot number, the lot size, the sample size, the date of testing, the test method, individual test results, and the specification requirements.

4.2 Quality conformance inspection. The examinations and tests required to assure conformance of those items or lots of items to be offered for acceptance are classified as specified in tables I and II (see 4.2.1 and 4.2.2) and 4.2.3.

4.2.1 Sampling for examination.

4.2.1.1 Sampling for visual defects. Sampling for visual defects shall be conducted in accordance with MIL-STD-105. The inspection levels and acceptable quality levels shall be as indicated in table I. Unit of product for examination purposes shall be one case.

Table I. Sampling for Visual Defects

	Inspection level	AQL (defects per 100 units)
Major	II	2.5
Total (Major and Minor combined)	II	6.5

4.2.1.2 Examination for dimensional defects. During this examination, any measurement deviating from the dimensions and tolerances of the finished case specified in the drawing shall be scored as a size measurement defect. The sample unit for this examination shall be one completely fabricated case. The lot size shall be expressed in units of one case. The sample size shall be selected in accordance with inspection level S-3 of MIL-STD-105. The acceptable quality level shall be 4.0 (one class) defects per 100 units.

4.2.2 Examination. The case shall be examined for defects including, but not limited to, those listed in table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:27Z
Check the source to verify that this is the current version before use.

Table II. Classification of Defects

Defect	Major	Minor
Material Defects and Damages.		
a. Any hole, cut, tear, mend, patch or unauthorized splice.	X	
b. Needle chews which may develop into a hole.	X	
c. Any weakening defect such as smash, multiple float, or loose slub that may develop into a hole.	X	
Cleanness.		
a. One or more spots or stains of an obviously permanent nature.	X	
b. One or more removable spots or stains clearly noticeable.		X
c. Thread end not trimmed.		
Components and Assembly.		
Any component part omitted or any required operation omitted or improperly performed.	X	
Seams and Stitching.		
a. Any part of case pleated, twisted, or caught in any unrelated row of stitching.		X
b. Any seam twisted, or puckered so severly as to impair appearance or serviceability.	X	
c. Seam type other than specified.	X	
d. Stitch type other than specified.	X	
e. Less than 8 per inch.	X	
f. One or more required rows of stitching omitted.	X	
g. Any open seam - 1/4 inch or more.	X	
h. Broken or skipped stitches, not amounting to an open seam, occurring twice or more in the same row of stitching. Open seam less than 1/4 inch.		X
i. Raw edges.	X	
j. All ends of stitching backstitched less than 3/4 inch.		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:27Z
Check the source to verify that this is the current version before use.

Table II. Classification of Defects (Cont'd)

Defect	Major	Minor
Webbing		
a. Not size specified.	X	
b. Frayed or scalloped edges.	X	
c. Not tightly and firmly woven.	X	
d. Not cut on bias when specified.		X
Hardware		
a. Broken or malformed.	X	
b. Burrs or sharp edges.	X	
c. Finish omitted.	X	
d. Finish not uniform.		X
Slide fastener		
a. Not slide fastener specified.	X	
b. Does not operate smoothly.	X	
c. Thongs omitted.	X	
Markings		
a. Omitted, incorrect, or illegible.	X	
b. Not size specified.	X	
c. Not located as specified.	X	
d. Color not uniform.		X

4.2.3 Sampling for tests.

4.2.3.1 Sampling for tests. Sampling for tests shall be conducted in accordance with MIL-STD-105. Sufficient samples of the component materials shall be selected from each lot of material used in the manufacture of the case to perform tests as required by the applicable referenced specifications, or by tests specified herein. When sample size is not specified, it shall be as indicated for inspection level S-1 of MIL-STD-105, except that the acceptance number shall be zero for all sample sizes, and the minimum of three samples shall be taken regardless of lot size. The unit of product for testing shall be the quantity of material necessary to perform all required tests one time each. The same material may be used to perform two or more tests. Lot sizes are expressed in multiples of the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:27Z
Check the source to verify that this is the current version before use.

Para. 4.2.3.1 Continued.

Cloth, nylon	Yard or fraction of a yard
Tape	Yard or fraction of a yard
Thread, polyester	Cone or spool
Webbing	Yard or fraction of a yard
Hardware items	Each

4.2.3.2 Sampling for chemical testing of metals. Four ounces of each lot of each metal used in the construction of the cases shall be selected for the chemical analysis as specified in 4.3.1.

4.3 Tests. Tests shall be conducted to determine compliance with specification requirements.

4.3.1 Chemical analysis of metals. The samples selected in accordance with 4.2.3.2 shall be analyzed in conformance with methods 111 or 112 of FED-STD-151. In case of dispute, method 111 shall be used for referee analysis.

5. PREPARATION FOR DELIVERY

5.1 Packaging.

5.1.1 Unit of issue. One case, as specified, constitutes one unit of issue.

5.1.2 Packaging quantities. The number of units of issue indicated in table III shall be packaged in each unit, intermediate, and exterior container, as applicable, for the required level of protection specified in the procurement document.

Table III. Packaging Quantities

Unit package	Intermediate package	Exterior container
Not required	Not required	48 units

5.1.2.1 Packing variation permitted. If the required number of units in the entire shipment is less than the number of units specified to be overpacked in an exterior container, such units shall be packed in an exterior container of suitable size and design, acceptable to a common carrier, which shall insure safe delivery to destination.

5.2 Packing. Packing shall be Levels A, B or C as specified (see 6.2).

5.2.1 Level A.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:27Z
Check the source to verify that this is the current version before use.

5.2.1.1 Exterior container. Exterior container shall be designed for a type 2 load and constructed in accordance with PPP-B-585, class 3, style 3; PPP-B-601, overseas type; PPP-B-621, class 2; or PPP-B-636, class weather-resistant. Closure and strapping shall be as specified in the appendix of the applicable box specification. Special requirements of applicable table shall apply for PPP-B-636 box.

5.2.2 Level B.

5.2.2.1 Exterior container. Exterior container shall be designed for a type 2 load and constructed in accordance with PPP-B-585, class 1, style 3; PPP-B-601, domestic type; PPP-B-621, class 1; or PPP-B-636, class domestic. Closure shall be as specified in the appendix of the applicable box specification. Fiberboard box shall be closed by method II of PPP-B-636. Special requirements of applicable table shall apply for PPP-B-636 box.

5.2.3 Level C. The subject commodity shall be packed in substantial commercial containers of the type, size, and kind commonly used for the purpose, so constructed as to insure acceptance and safe delivery by common or other carriers, at the lowest rate, to point of delivery called for in the contract or purchase order.

5.3 Marking. Marking shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The case covered by this specification is intended to hold an assortment of items of medical materiel.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:27Z
Check the source to verify that this is the current version before use.

6.3 Certain provisions (3.2 and 3.3) of this specification are the subjects of Quadripartite Standardization Agreement QSTAG 231. When amendment, revision, or cancellation of this specification is proposed which will effect or violate the international agreement concerned, the preparing activity will take appropriate reconciliation action through international standardization channels including departmental standardization offices, if required.

6.4 This specification does not include all types, classes, grades, sizes, etc., of the commodity indicated by the title of this specification, or which are commercially available, but is intended to cover the types, etc., which are normally procured to meet military requirements.

6.5 This specification is intended to cover the following item appearing in the Federal Supply Catalog:

FSN	Item Identification
6545-912-9870	CASE, MEDICAL INSTRUMENT AND SUPPLY SET, Nylon, Nonrigid, No. 3, 10 inches Long by 4-1/4 inches Wide by 8 inches High

6.6 Supersession Data. This specification includes the requirements of Defense Medical Purchase Description No. 8, dated 14 April 1971 and Modification No. 1, dated 3 March 1972.

Custodians:
Army - MD
Navy - MS
Air Force - 03

Review activities:
Army - MD
Navy - MS
Air Force - 03

Preparing activity:
Defense Supply Agency - DM

Project No. 6545-0008

Review information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current DODISS.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:27Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

MIL-C-36856

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1 HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A GIVE PARAGRAPH NUMBER AND WORDING

B RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2 COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3 IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4 REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:27Z
Check the source to verify that this is the current version before use.

FOLD

DEFENSE PERSONNEL SUPPORT CENTER
2800 South 20th Street
Philadelphia, Pa. 19101

Defense Supply Agency

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID
DEFENSE SUPPLY AGENCY
DoD - 304

U.S. MAIL

HEADQUARTERS, DEFENSE PERSONNEL SUPPORT CENTER
ATTN: DIRECTORATE OF MEDICAL MATERIEL, CODE ATT
2800 SOUTH 20TH STREET
PHILADELPHIA, PA. 19101

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:27Z
Check the source to verify that this is the current version before use.