MILITARY SPECIFICATION

HANDPIECE, DENTAL, CONTRA-ANGLE, WITH FRICTION GRIP CHUCK, ROUND SLEEVE

This amendment forms a part of Military Specification MIL-H-36887, dated 2 August 1972, and is approved for use by all Departments and Agencies of the Department of Defense.

Page 3

TABLE I, substitute the following for the applicable component as specified:

"Part	Component	Material	Rockwell Hardness	Plating
Spindle assembly	Spindle		C26 min.	
	Gear	AISI 01 drill rod	Delete	Delete
	Slinger	AISI 416 or 303	C26 min.	
Head and neck assembly	Collet	AISI 17-4PH or 416	C26 min.	
	Drive screw	AISI 17-4PH or 416	C26 min.	
	Head cap		Delete	
	Pinion gear	AISI 01 drill rod	Delete	Delete
	Elbow gear	AISI 01 drill rod	Delete	Delete
Elbow and rear end assembly	Elbow gear	AISI 01 drill rod	Delete	Delete
	Rear end shaft	Stainless	Delete	
Chuck tool assembly	Wrench square	AISI 303 or 302"		

Source: https://assist.dla.mil -- Downloaded: 202610-21T09:31Z
Check the source to verify that this is the current version before use.

3.3 In the last sentence of the paragraph, delete period and add the following: ", except for the following revisions:

Component	Delete	Substitute
Head		
Overall length	.516 ± .005	17/32 ± 1/32
Rear end assembly		
Knurl	80 ± 10TPI	64 ± 10TPI
Diameter, step	.345 / .335	Delete, not required
Depth to step	.403 / .397	Delete, not required
Depth to end of taper	.740 / .730	Delete, not required
Depth to beginning of taper	.567 / .563	.530 / .526
Diameter of shaft	.0922 / .0919	.0922 / .0918
Width of vertical slot	.093 / .098	.092 / .094
Depth of vertical slot to horizontal	None	.160 ± .010
Depth of vertical slot through horizontal	.175 ± .005	Delete, not required
Width of horizontal slot	.016 ± .005	.015 ± .010""

Delete sheet 2 of Drawing 24298 in its entirety and substitute: "A chuck tool assembly, a wrench spanner, a wrench handle and a square wrench shall be furnished of such design as to be dimensionally interchangeable with the applicable components of the handpiece to provide for bur insertion, bur removal, assembly and disassembly."

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:31Z
Check the source to verify that this is the current version before use.

Page 5

3.6, line 2: Delete "0.0010 inch" and substitute "0.0015 inch."

Page 10

Insert the following paragraph:

"4.5 Packaging inspection. The inspection of the unit, intermediate package, packing and marking for shipment and storage shall be in accordance with quality assurance provisions of the applicable container specification and the marking requirements of MIL-STD-129."

Page 11

5.1.3.2, line 1: Delete "Not required." and substitute: "A preservative shall not be applied to the exterior surfaces of the handpiece."

Page 12

5.2.2.1, line 5: following "method," insert "I or".

Military Custodians:
Army - MD
Navy - MS
Air Force - 03

Preparing activity:
DSA-DM

Project No. 6520-1428

Source: https://assist.dla.mil -- Downloaded: 202610-21T09:31Z
Check the source to verify that this is the currentversion before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:31Z
Check the source to verify that this is the current version before use.