MILITARY SPECIFICATION

INSERT, FIRST AID KIT CASE, Plastic, Olive Drab, 4-3/4 inches Long by 2-3/8 inches Wide by 4-1/2 inches High

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a semi-rigid plastic insert with attached cover for use as a liner for NSN 6545-00-180-6239 CASE, MEDICAL INSTRUMENT and SUPPLY SET, Nylon, Non-Rigid, No. 8 and is to contain and protect first aid supplies.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

L-P-394	- Plastic Molding Material, Polypropylene, Injection and Extrusion.
PPP-B-636	- Boxes, Fiberboard.

STANDARDS

FEDERAL

FED STD No. 595 - Color Requirements.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Defense Personnel Support Center, Directorate of Medical Materiel, DPSC-ATT, 2800 So. 20th Street, Philadelphia, PA 19101, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 6545

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:27Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

DRAWING

Defense Personnel Support Center (DPSC)

24153 - INSERT, FIRST AID KIT CASE

(Copies of specifications, standards and drawing, required by contractors in connection with specific procurement functions, should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 Material. The insert shall be fabricated from an impact and low temperature resistant propylene copolymer conforming to type IV, grade B of L-P-394.

3.2 Color. The plastic material shall be an olive drab color approximating 34087 of Federal Standard No. 595.

* 3.3 Design and construction. The insert shall be molded in accordance with Defense Personnel Support Center Drawing No. 24153. The finished insert shall show no evidence of cracking when tested as specified (see 4.4.1).

3.4 Finish. The insert shall have a lusterless satin finish on all surfaces. Vapor honing of the mold to attain the specified finish is permissible.

3.5 Flexing of hinge and latch. The hinge and latch shall not crack nor break when tested as specified (see 4.4.2).

3.6 Identification marking. The front exterior surface of the bottom section and the interior of the insert cover shall be permanently and legibly marked by hot stamping or other intaglio process at the locations indicated on the drawing. The letters and numerals shall be colored black by means of ink or paint. The ink or paint shall not mar adjacent surfaces.

3.7 Workmanship. Workmanship shall be first class throughout. Inserts shall be well made and free from defects which detract from their appearance or impair their serviceability.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:27Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification to assure supplies and services conform to prescribed requirements.

4.1.1 Records. Records of examinations and tests performed by or for the contractor shall be maintained by the contractor and made available to the Government, upon the Government's request, at any time, or from time to time, during the performance of the contract and for a period of three years after delivery of the supplies to which such records relate.

4.1.2 Inspection. Inspection, as used in this specification, is defined as both examination (such as visual or auditory investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item.

4.1.3 Certificates of quality. Certificates of quality, supplied by the manufacturer of the plastic molding material, may be furnished in lieu of actual performance of such testing by the contractor, provided lot identity has been maintained and can be demonstrated to the Government. The certificate shall include the name of the contractor, the contract number, the name of the manufacturer or supplier, the NSN, the item identification, the name of the component/material, the lot number, the lot size, the sample size, the date of testing, the test method, individual test results, and the specification requirements.

* 4.2 Sampling.

* 4.2.1 For examination. Sampling for examination shall be conducted in accordance with MIL-STD-105 and table I. Unit of product for examination purposes shall be one insert.

TABLE I. For examination.

	Inspection level	AQL (percent defective)
Visual examination		
Major	S-4	1.0
Minor	S-4	4.0
For dimensional examination	S-2	2.5

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:27Z
Check the source to verify that this is the current version before use.

* 4.2.2 For tests. Sampling for tests shall be conducted in accordance with MIL-STD-105 and table II. Inspection level shall be S-2 and the acceptance number shall be zero. Unit of product for test purposes shall be one insert.

TABLE II. For tests.

Characteristic	Requirement	Test procedure
Drop test at 155°F	3.3	4.4.1.1
Drop test at -20°F	3.3	4.4.1.2
Flexing of hinge and latch	3.5	4.4.2

4.3 Examination. The inserts shall be examined to determine compliance with all requirements of this specification.

* 4.3.1 Classification of defects. Examination shall be conducted in accordance with the classification of defects listed in table III. Examination shall not be restricted to the classified defects listed below.

TABLE III. Classification of defects.

Categories	Defects
Major	
101	Cover does not fit bottom.
102	Latch or hinge missing.
103	Latch does not engage bottom.
104	Insert not completely molded or malformed.
105	Color not as specified.
106	Incorrect markings.
107	Insert cracked, pitted, or scratched.
Minor	
201	Insert interior and exterior not free of flash.
202	Corners not well rounded.
203	Sharp edges not removed from cover and bottom.
204	Finish not as specified.
205	Marking incomplete.

* 4.3.2 Dimensional examination. The insert shall be examined for defects in dimensions. Any dimension not within the tolerance specified shall be classified as a defect.

* 4.4 Tests. Tests shall be conducted as necessary, to determine compliance with specification requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:27Z
Check the source to verify that this is the current version before use.

* 4.4.1 Drop tests. A one (1) pound weight shall be cushioned in the insert bottom and the insert cover secured by a single layer of two inch tape over the entire top-bottom joint. The insert shall be conditioned as specified below, and immediately dropped once, on a bottom corner, from a height of 60 inches onto a concrete floor.

* 4.4.1.1 Drop test at 155°F. The insert shall be conditioned for 3 hours at 155° ± 2°F.

* 4.4.1.2 Drop test at minus 20°F. The insert shall be conditioned for 3 hours at minus 20° ± 2°F.

* 4.4.2 Flexing of hinge and latch. The insert shall be conditioned for 3 hours at minus 20° ± 2°F. At the end of the conditioning period, first the latch and then the hinge shall be flexed, continuously by hand, for 25 flexes. The angle of flex shall be approximately 135°. The rate of flexing shall not exceed 1 flex per second. The above procedure shall be repeated using a conditioning temperature of 155° ± 2°F. in lieu of minus 20°F.

4.5 Packaging inspection. The inspection of the packaging, packing and marking for shipment and storage shall be in accordance with quality assurance provisions of the applicable container specification and the marking requirements of MIL-STD-129.

5. PACKAGING

5.1 Packaging. Packaging shall be level A or C, as specified (see 6.3).

5.1.1 Unit of issue. Each insert constitutes a unit of issue.

5.1.2 Level A.

5.1.2.1 Unit packaging. Each unit shall be clean and wrapped in kraft paper or inserted into a clear, snug fitting 2 mil plastic bag. Closure of the bag or wrap shall be secured with tape or by other suitable means.

5.1.2.2 Intermediate package. Twelve unit packages shall be packaged in a box conforming to PPP-B-636, class domestic. Closure shall be as specified in the box specification.

5.1.3 Level C. Each insert shall be clean and packaged in a manner that will afford adequate protection against physical damage during shipment from the supply source to the first receiving activity.

5.2 Packing. Packing shall be level A, B or C, as specified (see 6.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:27Z
Check the source to verify that this is the current version before use.

5.2.1 Level A. Four intermediate packages shall be packaged in a shipping container designed for a type 2 load and conforming to PPP-B-636, class weather-resistant. Closure, strapping and waterproofing shall be as specified in the appendix of the box specification.

5.2.2 Level B. Four intermediate packages shall be packed in a shipping container designed for a type 2 load and conforming to PPP-B-636, class domestic. Closure shall be as specified in the appendix of the box specification.

5.2.3 Level C. The packaged inserts shall be packed in shipping containers in a manner that will afford adequate protection against damage during direct shipment from the supply source to the first receiving activity. These packs shall conform to the carrier's rules and regulations.

5.3 Marking. Each unit package, intermediate package and shipping container shall be marked as specified in MIL-STD-129. Plastic bagged inserts may have the required marking printed on the bag or on a label inserted within the bag in such a manner to permit ready identification.

6. NOTES

6.1 The following plastic materials are reported to meet the requirements of L-P-394b in whole or in part:

Amoco Polypropylene Grade 6011	Amoco Chemicals Corporation
Eastman Tenite Polyallomar 5321	Eastman Chemical Products, Inc.
Enjay Grades CD-347 and E-803HC	Enjay Chemical Company
Shell Polypropylene WM110.2	Shell Chemical Company

6.2 Intended use. The insert is a protective container for the components of NSN 6545-00-823-8165, Individual First Aid Kit.

6.3 Ordering data. Procurement documents should specify the following:

(a) Number and date of this specification.
(b) National Stock Number (NSN).
(c) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:27Z
Check the source to verify that this is the current version before use.

6.4 This specification does not include all types, classes, grades, sizes, etc., of the commodity indicated by the title of this specification, or which are commercially available, but is intended to cover the types, etc., which are normally procured to meet military requirements.

6.5 This specification is intended to cover the following item appearing in the Federal Supply Catalog:

National Stock Number	Item Identification
6545-00-125-5527	INSERT, FIRST AID KIT CASE, Plastic, Olive Drab, 4-3/4 inches Long by 2-3/8 inches Wide by 4-1/2 inches High

6.6 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - MD
Navy - MS
Air Force - 03

Review activity:
DoD - MB

Preparing activity:
Defense Logistics Agency - DM

Project Number: 6545-0039

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:27Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEFENSE LOGISTICS AGENCY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 4968 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEFENSE LOGISTICS AGENCY

Commander
Defense Personnel Support Center
ATTN: DPSC-ATTS
2800 South 20th Street
Philadelphia, Pennsylvania 19101-8419

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:27Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-I-36854A	Insert, First Aid Kit Case

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:27Z
Check the source to verify that this is the current version before use.