NOT MEASUREMENT SENSITIVE

MIL-B-3628/20B
14 September 1990
SUPERSEDING
MIL-B-3628/20A
30 June 1967

MILITARY SPECIFICATION SHEET

BADGE CLASPS, BADGE, QUALIFICATION, BASIC, MARINE CORPS

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-3628.

-3

DASH NO:
-1: EX-S.M.G.
-2: SS-S.M.G.
-3: EX-RIFLE-B
-4: SS-RIFLE-B
-5: M.M.-RIFLE-B

MATERIAL: Red brass

DIMENSIONS:
HEIGHT (Including lugs): .410 inch (1.041 cm) (REF)
HEIGHT (Excluding lugs): .200 inch (0.508 cm) (REF)
WIDTH (Overall): 1 inch (2.54 cm) (REF)
THICKNESS (At rim): .060 inch ± .005 inch (0.152 cm ± 0.012 cm)

FINISH: Nickel plated, mirror-like polished

NOTES:
1. All lugs are integral.
2. All badge clasps are of identical design except for the lettering.
3. Badge clasps covered by this specification sheet shall be used in conjunction with the basic qualification badge in specification sheet 3628/19.
4. Two jump rings shall be positioned on the top lugs.
5. Badge may be rhodium plated, mirror-like polished at the option of manufacturer.

Custodians:
Army - IH
Navy - NU

Review activities:
Navy - NU
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0536)

AMSC N/A

FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:53Z
Check the source to verify that this is the current version before use.