NOT MEASUREMENT SENSITIVE


MIL-B-3628/16G
13 September 1991
SUPERSEDING
MIL-B-3628/16F
14 September 1990

MILITARY SPECIFICATION SHEET

Badge, Qualification, Rifle, Marine Corps; Pendant and Suspension Bar

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-3628.



MATERIAL: Red Brass, nickel silver, or zinc aluminum

DASH NO:
-1: Expert
-2: Sharpshooter
-3: Marksman

DIMENSIONS:
PENDANT:
HEIGHT (Overall):
-1: 1-5/16 inch (3.33 cm) (REF)
-2: 1-7/16 inch (3.65 cm) (REF)
-3: 1-5/32 inch (2.94 cm) (REF)
THICKNESS:
-1: .100 inch ± .005 inch (0.254 cm ± 0.012 cm) (At thickest point)
-2: .070 inch ± .005 inch (0.177 cm ± 0.012 cm) (At rim)
.190 inch ± .005 inch (0.482 cm ± 0.012 cm) (Total at center)
-3: .070 inch ± .005 inch (0.177 cm ± 0.012 cm) (At center)
SUSPENSION BAR:
HEIGHT:
EXCLUDING LUG: 9/32 inch (0.71 cm) (REF)
OVERALL: 13/32 inch (1.03 cm) (REF)
WIDTH: 1-29/32 inch (2.30 cm) (REF)
THICKNESS (At rim): .060 inch ± .005 inch (0.152 cm ± 0.012 cm)

FINISH:
RED BRASS OR NICKEL SILVER: Nickel plated, mirror-like polished except textured background areas which shall be lightly polished.
ZINC ALUMINUM: Copper plated, nickel plated, mirror-like polished except textured background areas which shall be lightly polished.

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:52Z
Check the source to verify that this is the current version before use.

NOTES:

1. All lugs are integral.
2. Requalification clasps used with Dash No. 1 shall conform to MIL-B-3628/18.
3. The attaching device shall be prong and clutch type. Prongs shall be located on the horizontal centerline of the suspension bar, equidistant from each end and 1-1/2 inches ± 1/16 inch (3.81 cm ± 0.16 cm) apart.
4. The Marine Corps emblem shall be circumscribed in a 1/2 inch (1.27 cm) diameter circle and shall be soft soldered to the target area of the cross for Dash No 2 after trimming and piercing.
5. Lugs for bar and pendant shall be located equidistant from each end of the bar and pendant. The distance, center to center of the lugs, shall be as follows:

   -1: 7/8 inch ± 1/64 inch (2.22 cm ± 0.04 cm)
   -2: 1/2 inch ± 1/64 inch (1.27 cm ± 0.04 cm)
   -3: 5/8 inch ± 1/64 inch (1.59 cm ± 0.04 cm)

6. Badge may be rhodium plated mirror-like polished at option of manufacturer.

Custodians:
Army - IH
Navy - NU

Preparing activity:
Army - IH

Review activities:
Navy - MC
DLA - CT

(Project No. 8455-N621)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:52Z
Check the source to verify that this is the current version before use.