NOT MEASUREMENT SENSITIVE

MIL-B-3628/17E
6 June 1990
SUPERSEDING
MIL-B-3628/17D
10 February 1988

MILITARY SPECIFICATION SHEET

BADGE, QUALIFICATION, PISTOL, MARINE CORPS; PENDANT AND SUSPENSION BAR

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-3628.



EXPERT SHARPSHOOTER MARKSMAN

MATERIAL: Red brass, nickel silver or zinc aluminum

DASH NO:
-1: Expert
-2: Sharpshooter
-3: Marksman

DIMENSIONS:
PENDANT:
HEIGHT (Including lug):
-1: 15/16 inch (2.38 cm) (REF)
-2: 1-5/32 inch (2.90 cm) (REF)
-3: 1-1/32 inch (2.62 cm) (REF)
THICKNESS:
-1: .115 inch ± .005 inch (0.292 cm ± 0.012 cm) (At thickest point)
-2: .075 inch ± .005 inch (0.190 cm ± 0.012 cm) (At edge)
.160 inch ± .005 inch (0.406 cm ± 0.012 cm) (Total)
-3: .070 inch ± .005 inch (0.177 cm ± 0.012 cm) (At center)
WIDTH (Overall):
-1: 1-1/32 inch (2.62 cm) (REF)
-2: 1 inch (2.54 cm) (REF)
-3: 7/8 inch (3.73 cm) (REF)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:52Z
Check the source to verify that this is the current version before use.

SUSPENSION BAR:
HEIGHT: 7/32 inch (0.56 cm) (REF)
WIDTH; 1-15/32 inch (3.73 cm) (REF
THICKNESS (At edge): .060 inch ± .005 inch (0.152 cm ± 0.012 cm)

FINISH (Obverse and Reverse):
RED BRASS: Nickel plated, rhodium plated, mirror-like polished except textured background areas which shall be lightly polished.
NICKEL SILVER: Rhodium plated, mirror-like polished except textured background areas which shall be lightly polished.
ZINC ALUMINUM: Copper plated, nickel plated, rhodium plated, mirror-like polished except textured background areas which shall be lightly polished.

NOTES:
1. All lugs are integral.
2. Requalification clasps used with dash no. 1 shall conform to MIL-B-3628/18.
3. Attaching device shall be prong and clutch type. The prongs shall be located on the horizontal centerline of the suspension bar, equidistant from each end and 1-3/6 inch ± 1/32 inch (3.02 cm ± 0.08 cm) apart.
4. The Marine Corps emblem shall be circumscribed in a 3/8 inch (0.95 cm) diameter circle and shall be soft soldered to the target area of the cross for dash no. 2 after trimming and piercing.
5. Lugs for bar and pendant shall be located equidistant from each end of the bar and pendant. The distance, center to center of the lugs, shall be as follows:

-1: 5/8 inch ± 1/64 inch (1.59 cm ± 0.04 cm)
-2: 3/8 inch ± 1/64 inch (0.95 cm ± 0.04 cm)
-3: 1/2 inch ± 1/64 inch (1.27 cm ± 0.04 cm)

Custodian:
Army - IH
Navy - NU

Preparing activity:
Army - IH

Review activity:
Navy - MC
DLA - CT

(Project No. 8455-0523)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:52Z
Check the source to verify that this is the current version before use.