NOT MEASUREMENT SENSITIVE


MIL-B-3628/17G
30 July 1993
SUPERSEDING
MIL-B-3628/17F
14 September 1990

MILITARY SPECIFICATION SHEET


BADGE, QUALIFICATION, PISTOL, MARINE CORPS; PENDANT AND SUSPENSION BAR

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-3628.



-1



-2



-3

DASH NO:
-1: Expert
-2: Sharpshooter
-3: Marksman

MATERIAL: Red Brass, Nickel Silver or Zinc Aluminum

FINISH:
RED BRASS OR NICKEL SILVER: Nickel Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 16 except Textured Background Areas which shall be lightly Polished.
ZINC ALUMINUM: Copper Plated, Nickel Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 16 except Textured Background Areas which shall be lightly Polished.

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil - Downloaded: 2026-10-16T18:52Z
Check the source to verify that this is the current version before use.

DIMENSIONS:

PENDANT:

HEIGHT (Overall):

-1: 15/16 inch (2.38 cm) (REF)
-2: 1-5/32 inches (2.90 cm) (REF)
-3: 1-1/32 inches (2.62 cm) (REF)

WIDTH (Overall):

-1: 1-1/32 inches (2.62 cm) (REF)
-2: 1 inch (2.54 cm) (REF)
-3: 7/8 inch (3.73 cm) (REF)

THICKNESS:

-1: 0.115 inch ± 0.005 inch (0.292 cm ± 0.012 cm) (At Thickest Point)
-2: 0.075 inch ± 0.005 inch (0.190 cm ± 0.012 cm) (At Edge)
-2: 0.160 inch ± 0.005 inch (0.406 cm ± 0.012 cm) (Total)
-3: 0.070 inch ± 0.005 inch (0.177 cm ± 0.012 cm) (At Center)

SUSPENSION BAR:

HEIGHT (Overall): 7/32 inch (0.56 cm) (REF)
WIDTH (Overall): 1-15/32 inches (3.73 cm) (REF)
THICKNESS (At Edge): 0.070 inch ± .005 inch (0.177 cm ± 0.012 cm)

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Piercing shall be as indicated for Dash No. -1 only.

3. Qualification clasps used with Dash No. -1 shall conform to MIL-B-3628/18.

4. The attaching device shall be prong and clutch type. Prongs shall be located on the horizontal center line of the back of the suspension bar, equidistant from each end and 1-3/16 inches ± 1/32 inch (3.02 cm ± 0.08 cm) apart.

5. The Marine Corps emblem shall be circumscribed in a 3/8 inch (0.95 cm) diameter circle and shall be soft soldered to the target area of the cross for Dash No. -2 after trimming and piercing.

6. Lugs for bar and pendant are intergral.

7. Links shall be 13/64 ± 1/64 inch (0.52 cm ± 0.04 cm) in width and 1/4 inch ± 1/64 inch (0.64 cm ± 0.04 cm) in length and shall be fabricated from 0.044 inch ± 0.005 inch (0.114 cm ± 0.012 cm) diameter wire.

7. Badge may be rhodium plated with a mirror-like polished finish which shall match TIOH Metal Finish Chip Number 16 at the option of the manufacturer.

Custodian:
Army - IH
Navy - NU

Preparing activities:
Army - IH

Review activities:
Navy - MC
DLA - CT

(Project No. 8455-0693)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:52Z
Check the source to verify that this is the current version before use.