NOT MEASUREMENT SENSITIVE

MIL-B-3628/22E
26 April 1991
SUPERSEDING
MIL-B-3628/22D
10 February 1988

MILITARY SPECIFICATION SHEET

Badge, Qualification, Clasps, Basic, Driver and Mechanic, Army

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-3628.



-6

DASH NO:	Badge Clasp Title
-1:	Driver-W
-2:	Driver-A
-3:	Driver-T
-4:	Driver-M
-5:	Mechanic
-6:	Operator-S

MATERIAL: Red brass or nickel silver

DIMENSIONS:
HEIGHT (Overall): .410 inch (1.04 cm) (REF)
WIDTH (Overall): 1 inch (2.54 cm) (REF)
THICKNESS (At rim): .060 inch ± .005 inch (0.152 ± 0.012 cm)

FINISH: Nickel plated (red brass only), silver plated, relieved, matte finish.

NOTES:
1. All lugs are integral.
2. Two jump rings shall be positioned on top lugs.
3. The clasps are of identical design except for lettering; therefore, only one sample is shown.
4. Lugs shall be located equidistant from each end and .675 inch ± .015 inch - .000 inch (1.71 cm ± 0.038 cm - 0 cm) on centers.
5. Badge clasps covered by this sheet shall be used in conjunction with the basic badge on sheet MIL-3628/21.
6. Badge may be nickel or rhoduim plated with a mirror-like polished finish for commercial sale except the silver plating requirement shall not apply.

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:54Z
Check the source to verify that this is the current version before use.

Custodian:
Army - IH

Review Activity:
DLA - CT

Preparing Activity:
Army - IH

(Projected No. 8455-0586)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:54Z
Check the source to verify that this is the current version before use.