NOT MEASUREMENT SENSITIVE

MIL-B-3628/22F
30 July 1993
SUPERSEDING
MIL-B-3628/22E
26 April 1991

MILITARY SPECIFICATION SHEET

BADGE, QUALIFICATION, CLASPS, BASIC, DRIVER AND MECHANIC, ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-3628.



PEBBLED BACKGROUND

DASH NO:	BADGE CLASP TITLES
-1:	Driver-W
-2:	Driver-A
-3:	Driver-T
-4:	Driver-M
-5:	Mechanic
-6:	Operator-S

MATERIAL: Red Brass or Nickel Silver

FINISH: Nickel Plated (Red Brass only), Silver Plated, Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 14.

DIMENSIONS:
HEIGHT (Overall): 0.410 inch (1.04 cm) (REF)
WIDTH (Overall): 1 inch (2.54 cm) (REF)
THICKNESS (At Rim): 0.060 inch ± .005 inch (0.152 cm ± 0.012 cm)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil - Downloaded: 2026-10-16T18:54Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Lugs shall be located equidistant from each end and 0.675 inch + 0.015 inch - 0 inch (1.71 cm + 0.038 cm - 0 cm) on centers.

3. Two links shall be positioned on top lugs and shall use the same material and finish as the badge clasp. Links shall be 13/64 inch ± 1/64 inch (0.52 cm ± 0.04 cm) in width and 1/4 inch ± 1/64 inch (0.64 cm ± 0.04 cm) in length and shall be fabricated from 0.044 inch ± 0.005 inch (0.114 cm ± 0.012 cm) diameter wire.

4. The clasps are of identical design except for lettering; therefore, only one sample is shown.

5. Badge clasps covered by this specification sheet shall be used in conjunction with the basic badge covered on specification sheet MIL-B-3628/21.

6. Badge may be nickel or rhodium plated with a mirror-like polished finish which shall match TIOH Metal Finish Chip Number 16 for commercial sale only. For nickel or rhodium plated items, the silver plating requirement need not apply.

Custodian:
Army - IH

Review activities:
DLA - CT

Preparing activities:
Army - IH

(Project No. 8455-0693)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:54Z
Check the source to verify that this is the current version before use.