A-A-1817A
March 15, 1984
Superseding
A-A-1817
July 27, 1982

COMMERCIAL ITEM DESCRIPTION

BOOKCASES (STEEL, CONTEMPORARY STYLE)

The General Services Administration has authorized the use of the Commercial Item Description in preference to Interim Federal Specification AA-B-001922.

Salient Characteristics

These characteristics concisely describe the essential physical and functional/performance characteristics of the commercially available item.

Design. The bookcases shall be comtemporary style designed for heavy duty office use.

Types and sizes.

Type I - with laminate tops
Type II - without laminate tops
Size 1 - 30"W x 13"D x 47 1/2"H (Type I) 46 1/2"H (Type II), minimum, two adjustable shelves, allowing three 12"H minimum clear openings.
Size 2 - 30"W x 13"D x 29 1/4"H (Type I) 28 1/4"H (Type II), minimum, one adjustable shelf, allowing one 12"H minimum clear opening.

Adjustable shelves. Formed on all sides. Shelf adjusting devices shall not be visible on the exterior of the case. Shelf supports shall be provided.

Tops. Type I tops shall be self-edged HP laminated plastic with a backing sheet on the bottom. The color shall be walnut grain per GSA Std. Sample No. FSS-L-01002. Alternatively, the manufacturer may provide his equivalent commercial walnut grain HP laminated plastic subject to contracting officer approval. Overall thickness of the top shall be 3/4 inch minimum. Type II tops shall be steel.

Legs. The legs shall be a minimum 7/8" square polished finish stainless or chromium plated steel. They shall have adjustable glides and the exposed length shall be a minimum of 6 inches from the base frame to the bottom of the fully retracted glides.

Finish. The finish shall be semi-gloss baked enamel. Unless otherwise specified, colors shall match Fed. Std. No. 595 black (27040), parchment within the range delimited by (26586) and (26405) and gray (26134). Alternatively, the manufacture may provide his commercial black or gray baked enamel finish subject to the approval of the contracting officer.

FSC 7110

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:17Z
Check the source to verify that this is the current version before use.

Identification label. The label shall have the contractor's name or trademark, contract number, NSN (if specified) and year and month of manufacture legibly marked with permanent dark ink. The label shall be affixed to the back of the bookcase and shall not be removable by hand without defacement after being affixed for 4 hours.

Workmanship. Edges and corners shall be eased. Metal shall be free of sharp edges and burrs to prevent injury to personnel or damage to their clothing. Baked enamel finish shall be smooth without runs, grit, wrinkles, tackiness or separation of color. Chromium plating shall be free of pits, blisters, stains and brush or grind marks.

Performance. Bookcases shall comply with the following requirements. Failure to comply with these requirements shall be cause for rejection.

Chromium plating test. Test samples shall be plated and shall be tested for corrosion in accordance with the 5 percent neutral salt spray at 95 degrees F in accordance with ASTM Test Method B-117. Test period shall be not less than 48 hours. After the specified exposure is completed, the specimen shall be visually examined to assure that the plating shows no evidence of peel, chip, uneven color, powder film, pits, or stain. Widely scattered spots of corrosion are permitted; however, none of these spots of corrosion shall exceed 1/16 inch along the greatest dimension.

Shelf test (static). This test shall be performed on both the size 1 and size 2 bookcases. The complete bookcase shall be placed on a level surface. Only one shelf shall be used and it shall be adjusted to the approximate mid-point (top-to-bottom). A load of 20 pounds shall be placed on the shelf at both of the extreme sides for 5 minutes to assure that the shelf supports are fully engaging the shelf. This load shall then be removed. A dial indicator or equivalent measuring device shall be placed at the front edge. An evenly distributed non-rigid load totaling 150 pounds shall be applied on the shelf and shall remain undisturbed for 15 minutes. Deflection shall then be recorded. The shelf shall not be deflected more than 0.1875 inch. The load shall then be removed and the permanent distortion recorded. The shelf shall not have taken on more than 0.0312 inch permanent set.

Leg attachment test. Each leg of the bookcase shall be tested as follows: The bookcase shall be inverted and restrained from movement. Two inches from the bottom of the leg under test, a force of 200 pounds shall be applied against the outside of the leg toward the center of the bookcase. This force shall be held against the leg for not less than ten minutes. At the end of ten minutes time, the force shall be removed from the leg. Permanent distortion of the leg shall not exceed 0.187 inch and there shall be no weakening of the leg's attachment to the bookcase.

Drop test. The glides shall be fully retracted. One end of the bookcase shall then be raised 6 inches and dropped onto the floor. The bookcase shall be thoroughly examined. There shall be no broken welds, loose mechanical attachments, or visual permanent distortion.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:17Z
Check the source to verify that this is the current version before use.

Regulatory requirements. The offeror/contractor is encouraged to use recovered material in accordance with Public Law 94-580 to the maximum extent practicable.

Packaging, packing and marking. Packaging, packing and marking shall be as specified in the contract or order.

Plastic laminate sample. A sample panel of the decorative plastic laminate is obtainable from the Engineering Division, Furniture Commodity Center, Federal Supply and Services, General Services Administration, Washington, DC 20406, or from the Business Service Center in the nearest General Services Administration Regional Office.

Finish sample. A sample panel of the baked enamel finish is obtainable from the Business Service Center, Federal Supply and Services, General Services Administration, Washington, DC 20407, or from the Business Service Center in the nearest General Services Administration Regional Office.

ASTM Test Method. Copies of the ASTM Test Method B-117 are obtainable from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

Note. The Commercial Certification Clause is not required when this Commercial Item Description is used for procurement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:17Z
Check the source to verify that this is the current version before use.