[INCH-POUND]
A-A-248B
April 14, 1998
SUPERSEDING
A-A-248A
February 19, 1991

COMMERCIAL ITEM DESCRIPTION

VALVE, INLET, ANTISIPHON (WATER CLOSET)

The General Services Administration has authorized the use of this commercial item description by all federal agencies.

1. SCOPE

1.1 Scope. This commercial item description (CID) covers water inlet valves of antisiphon design for use with a standard size water closet tank.

2. SALIENT CHARACTERISTICS

2.1 Construction. Inlet valves shall be of the antisiphon type made of corrosion-resistant materials throughout and designed for mounting in a standard 14-inch (355.6 mm) water closet tank. The valve shall provide for connection to a 3/8-inch (9.5 mm) supply tube. Flow and shut-off of the water shall be controlled by the valve in response to the water level in the tank. Each valve shall be provided with the following items:

a) Inlet valve tank gasket.
b) Shank coupling nut.
c) Bevel slip joint washer.
d) Friction ring.
e) Supply coupling.
f) Refill tube.

2.2 Float-rod receptors. Inlet valves designed for use with float rods shall be furnished with an 8-inch (203.2 mm) float rod in accordance with CID A-A-249. Float-rod receptors in such valves shall have 0.250-20 UNC-2B internal threads in accordance with ANSI Y14.6.

2.3 Performance. Inlet valves shall meet the performance requirements of ASSE 1002.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: General Services Administration, Engineering Branch (7FXEE), 819 Taylor St., Fort Worth, TX 76102

FSC 4510

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:06Z
Check the source to verify that this is the current version before use.

2.4 Workmanship. The inlet valves shall be free of defects which affect function, serviceability, or operation.

2.5 Measurement system. The values stated in inch-pound units are to be regarded as the standard. The metric values stated in parentheses are for information purposes only.

2.6 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, providing they fall within the tolerances specified and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

3. REGULATORY REQUIREMENTS

3.1 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4. QUALITY ASSURANCE PROVISIONS

4.1 Product Conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

5. PACKAGING

5.1 Packaging. Preservation, packing, and marking shall be as specified in the contract or order.

6. NOTES

6.1 Referenced Documents. The documents referenced in this commercial item description shall be the issues in effect on the date of issuance of the invitation for bids or request for proposals unless otherwise specified. These documents form a part of this commercial item description to the extent specified. In the event of a conflict between this commercial item description and a document referenced herein, this commercial item description shall take precedence.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:06Z
Check the source to verify that this is the current version before use.

Commercial Item Description:

A-A-249 - Rod, Tank Float (Water Closet)

Copies of commercial item descriptions are available from the Federal Supply Service Bureau, Specification Section (3FBP-W), Suite 8100, 470 East L'Enfant Plaza, SW, Washington, DC 20407.

ANSI Standard:

Y14.6 - Screw Thread Representation

Application for copies of ANSI standards should be addressed to the American National Standards Institute, 11 West 42nd Street, 13th Floor, New York, NY 10036.

ASSE Standard:

1002 - Performance Requirements for Water Closet Flush Tank Ball Cocks.

Application for copies of ASSE standards should be addressed to the American Society of Sanitary Engineering, PO Box 40362, Bay Village, OH 44140.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents (if applicable).

a. Title, number and date of this commercial item description.
b. Preservation, packing, and marking desired.

6.3 Referencing NSN: 4510-00-541-7539

MILITARY INTERESTS:

Reviewer:
DLA - CC

CIVIL AGENCY COORDINATING ACTIVITY:
GSA-FSS

PREPARING ACTIVITY:
GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:06Z
Check the source to verify that this is the current version before use.