COMMERCIAL ITEM DESCRIPTION


CHISEL, DIAMOND POINT, HAND
(NONSPARKING AND NONMAGNETIC)

The General Services Administration has authorized the use of this commercial item description.

This commercial item description covers one size diamond point hand chisel assigned National Stock Number (NSN) 5110-00-238-8296. and made of a nonferrous alloy having a low sparking hazard and a low magnetic permeability.

Salient characteristics.

Design and dimensions: Design and dimensions shall be as illustrated below:




Material. Material shall be a beryllium copper or aluminum bronze alloy having an iron content not over five percent, and when present, it shall be well diffused throughout the alloy. When tested with a magnetic permeability indicator conforming to Military Specification MIL-I-17214, the magnetic permeability shall not be above 1.2 on the indicator scale.

Hardness. The chisels shall have a minimum hardness of Rocxkwell B95, or equivalent.

Surface finish. The striking end and the cutting edge shall be smoothly machined or ground. Other surfaces shall be finished in accordance with good commercial practice and shall be free from fins, scale, cracks, seams, burrs, or any other defects which may affect the serviceability or durability of the chisel. Forging flash lines shall be removed sufficiently to blend smoothly with adjacent surfaces.

Marking. Each chisel shall be marked in a plain and permanent manner with the manufacturer's name, or with a trademark of such known character that the source of manufacture may be readily determined, the country of origin, and the name, abbreviation, or chemical symbol of each alloy used.

Quality assurance provisions. Sampling for inspection shall be in accordance with MIL-STD-105, Sampling Procedures and Tables for Inspection by Attributes, except where otherwise indicated herein. The lot size shall consist of all chisels offered for acceptance at one time. A sample unit shall be one chisel.

A. Examination for design, dimensions and workmanship. The inspection level shall be S-2 with an acceptable quality level (AQL) of 4.0 percent defective.

FSC 5110

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026Ø10-26T08:23Z
Check the source to verify that this is the current version before use.

B. Material. Material shall be ascertained by manufacturer's certification.

C. Hardness testing shall be in conformance with commercially accepted procedures. The inspection level shall be S-2 with an AQL of 4.0 percent defective.

Regulatory requirement. In accordance with the section 23.403 of the Federal Acquisitition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing suppliers' employees to undue hazards from the recovered materials.

Packaging, packing, labeling and marking. Packaging, packing, labeling and marking shall be as specified in the contract or order.

Notes:

The issue of referenced documents in effect on the date of invitation for bid or request for proposals shall be used to determine compliance with the stated requirements. Sources for referenced documents may be determined by contacting the Contracting Officer.

MILITARY INTERESTS:

NONE: DoD has determined that no military activity has an official interest in this commercial item description.

PREPARING ACTIVITY:

GSA-FSS



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:23Z
Check the source to verify that this is the current version before use.