A-A-2568
March 25, 1988

COMMERCIAL ITEM DESCRIPTION

BAR, DIGGING

The General Services Administration has authorized the use of this commercial item description in preference to Federal Specification GGG-B-101, Type VII, Sizes 1 and 2.

This commercial item description covers digging bars.

SALIENT CHARACTERISTICS

Material. The material used in the manufacture of the bars shall be either tool steel or an alloy steel. The chemical composition of the material and the heat treatment employed shall be such as to produce bars to withstand the specified tests. All forgings shall be of uniform quality, free from defects and imperfections that may affect their serviceability or durability. Special quality, fine grain, hot rolled or cold finished carbon steel may also be used.

Design. The bars, otherwise meeting the requirements of this specification, may be the manufacturer's standard design.

Finish. The bars shall be free from burrs, roughness and excessive oxide scale. The body of the bars shall be either lacquered, enameled, painted, or have an oil-coated natural finish. The work ends of Type VII bars shall have a satin finish, and shall be oil or phosphate coated, lacquered or painted.

Type VII, digging. Digging bars at one end shall be provided with a formed bit, finished, and uniformly tapered having a cutting edge ground to a double-beveled edge. The opposite end of the bar shall terminate in a round uniform tapered point. The bar shall conform to table I and be similar to figure 1.

Table I. Type VII, digging bar.

	Dimensions											Test load minimum
	A		B		C		D		E		F	G	
Size Number	Min Inches	Max Inches	Min Inches	Max Inches	Min Inches	Max Inches	Min Inches	Max Inches	Min Inches	Max Inches	Min Inches	Max Inches	Pounds
1	83	85	3-7/8	4-1/8	1-3/32	1-5/32	2	2-1/2	1/4	3-7/8	1/4		300
2	95	97	3-7/8	4-1/8	1-3/32	1-5/32	2	2-1/2	1/4	3-7/8	1/4		250

Size Number	National Stock Number
1	5120-00-516-3802
2	5120-00-224-1367

DISTRIBUTION STATEMENT A. Approved for Public Release; Distribution is Unlimited.
Source: https://assist.dla.mil - Downloaded: 2026-10-26T08:24Z
Check the source to verify that this is the current version before use.




FIGURE 1. Type VII, digging bar.

Hardness. The work ends of the bar shall show a hardness reading of not less than 42 nor more than 52 on the Rockwell C scale, or a hardness reading of not less than 390 nor more than 512 on the Brinell scale.

Identification marking. Each digging bar shall be etched or stamped in a permanent and legible manner with the manufacturer's name or identifying symbol of such known character that the source may be readily identifiable, part number, and country of origin.

Workmanship. All bars shall be free from imperfections which may affect their safety, appearance, serviceability, or durability.

QUALITY ASSURANCE PROVISIONS

Sampling for inspection. Sampling shall be in accordance with MIL-STD-105, Sampling Procedures and Tables for Inspection by Attributes, except where otherwise specified herein. The lot size shall consist of all bars offered for acceptance at one time. The sample unit is one digging bar.

Visual inspection. Each bar from the sample lot shall be examined for workmanship and marking requirements. The inspection level shall be 1 with an acceptable quality level (AQL) of 2.5 defects per hundred units.

Dimensional inspection. Each bar from the sample lot shall be examined for dimensional requirements. The inspection level shall be S-4 with an acceptable quality level (AQL) of 2.5 defects per hundred units.

Testing of end item. The inspection level shall be S-3 with an acceptable quality level (AQL) of 4.0 percent defective.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:24Z
Check the source to verify that this is the currentversion before use.

Hardness test. Hardness test shall be in accordance with ASTM E18 or ASTM E10. The impressions shall be taken 1/2 inch from the end tested. The manufacturer shall certify that both the cutting edge end and the taper end have been similarly hardened.

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580, as amended, to the maximum extent practicable.

Preservation, packaging, packing, labeling, and marking. Preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

Notes.

The issue of referenced documents in effect on date of invitation for bid or request for proposal shall be used to determine compliance with the stated requirements.

ASTM standards are available from American Society For Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

Military standards are available from Naval Publications and Forms Center, 5801 Tabor Avenue, Philadelphia, PA 19120.

MILITARY INTERESTS:

Military Coordinating Activity
Army - GL

Custodians
Army - GL
Air Force - 99

Review Activities
Air Force - 84

PREPARING ACTIVITY:

GSA/FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:24Z
Check the source to verify that this is the current version before use.