A-A-865B
December 17, 1991
SUPERSEDING
A-A-865A
December 9,1982

COMMERCIAL ITEM DESCRIPTION

MAILING AND FILING TUBES

The General Services Administration has authorized the use of this commercial item description.

This commercial item description covers spiral wound or convolutely wound, commercially available tubes used in mailing, filing, and map storage.

Classification

Class 1: Spiral wound tubes.
Class 2: Convolutely wound tubes.

1. Salient Characteristics

A. Tubes shall either be class 1, spiral wound, or class 2, convolutely wound. Plies of class 1 tubes shall be wound with butt joints, with a maximum gap of 1/16 inch.

B. Seams of class 2 tubes shall be tapered or bevelled to form a smooth seam.

C. Crushing strength of both class 1 and class 2 tubes shall not be less than 8 pounds per inch of the tube length, as indicated by T-108 Test of the Composite Can and Tube Institute.

D. Inside diameter and inside length shall be as specified. (See Section 6). The tolerance on the inside diameter shall be +/- 1/32 inch and on the inside length shall be plus 3/8 inch, minus 0 inch.

E. Closure shall be by the use of metal ends, either by crimping or metal screw cap.

F. Workmanship - The tube shall be free from any defect that may affect its appearance, performance or use.

DISTRIBUTION STATEMENT A : Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:10Z
Check the source to verify that this is the current version before use.

2. Recovered Materials

The contractor must certify that the product offered shall include a minimum of 80 % post consumer recovered material as defined in 40 CFR, part 250. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise required.

3. Quality Assurance

Responsibility for Inspection - Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth herein, where such inspections are deemed necessary to assure that supplies and services conform to the prescribed requirements.

Each lot of Mailing and filing tubes shall be inspected for conformance to the requirements herein. Inspection shall be in accordance with MIL-STD-105 using the sampling plans specified below.

A. Visual characteristics - Inspection level S-4 with an Acceptable Quality level (AQL) of 4.0 percent defective. The sample unit shall be a single tube.

B. Dimensional characteristics - Inspection level S-2 with an Acceptable Quality level (AQL) of 4.0 percent defective. The sample unit shall be one tube.

C. Sampling for Crush Test - Inspection level S-2 with an AQL of 4.0 percent defective. The sample unit shall be one tube.

D. Preservation, Packaging, Packing, Labeling and Marking - Inspection level S-2 with an AQL of 4.0 percent defective. Thesample unit shall be one fully prepared shipping container.

4. Application for copies of technical documents referenced herein

The issue date in effect on date of invitation for bids or request for proposal shall apply.

A. MIL-STD-105 is available from Standardization Documents Order Desk; Building 40; 700 Robbins Avenue; Philadelphia, PA 19111-5094.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:10Z
Check the source to verify that this is the current version before use.

B. T-108 Test is available from the Composite Can and Tube Institute, 1800 M Street, N.W., Washington, DC 20036.

C. Code of Federal Regulations, Title 40, Part 250 is available through the Superintendent of documents, U.S. Government Printing Office, Washington DC 20402.

5. Preparation for Delivery

Preservation, Packaging, Packing, Labeling, and Marking shall be as specified in the contract or purchase order.

6. Ordering Data

Purchasers should select the prefered options permitted herein, and include the following information in procurement documents:

A. Class.
B. Inside diameter and inside length.

7. Item Identifiers/Reference Part Number System (For Cataloging use only)

Part Reference Numbers:

AA865 - 1 :This example describes a
MAILING AND FILING TUBE, CLASS 1, SPIRAL WOUND

1 - CLASS 1, SPIRAL WOUND

2 - CLASS 2, CONVOLUTELY WOUND

NO OFFICIAL DOD INTEREST HAS BEEN REGISTERED

PREPARING ACTIVITY:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:10Z
Check the source to verify that this is the current version before use.