MILITARY SPECIFICATION

GREASE, PLUG VALVE, GASOLINE AND OIL RESISTANT,
NATO CODE NUMBER G-363, METRIC

This amendment forms a part of military specification MIL-G-6032D, dated 29 June 1984, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 8

Table I, sixth entry: Delete in its entirety and substitute the following:

Characteristics	Limits	Test Paragraph
"Unworked penetration (1/4 scale)		
Type I	20-72	4.6.2
Type II	16-24	4.6.2"

Table I, column 1, opposite "Storage stability: Unworked penetration": Delete ", maximum".

Table I, column 2, opposite "Storage stability. Unworked penetration": Delete "23" and substitute "16-24".

Custodians:
Army - ME
Navy - AS
Air Force - 68

Review activities:
Army - AT
DLA - GS

User activities:
Army - AT
Navy - SH

International Interests:
NATO

Preparing Activity:
Navy -AS
(Project No. 9150-1012)

AMSC N/A FSC 9150

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:03Z
Check the source to verify that this is the current version before use.