MIL-P-5954A (ASG)
AMENDMENT-1
8 SEPTEMBER 1955

MILITARY SPECIFICATION

PUMP UNIT, HYDRAULIC, ELECTRIC MOTOR DRIVEN
FIXED DISPLACEMENT

This amendment forms a part of Military Specification MIL-P-5954A(ASG), dated 6 April 1953, and has been approved by the Department of the Air Force and by the Navy Bureau of Aeronautics.

Page 9, paragraph 4.3.2.2 High temperature: In the third line delete "30 hours" and substitute "12 hours."

Page 10, paragraph 4.3.2.3 Low-temperature capacity: In the third line delete "72 hours" and substitute "12 hours."

Page 11, paragraph 4.4.2.1 Low-temperature starting: In the third line delete "72 hours" and substitute "12 hours."

Page 11, paragraph 4.4.2.4.1 Delivery pressure: Add the following at the end of the first sentence:

"(Continuous duty is defined as continuous operation at 100 percent load.)"

Page 12, TABLE II Endurance test conditions: Add the following at the end of footnote "2/": ", provided the time of operation does not exceed 1,000 hours."

Custodians:
Navy - Bureau of Aeronautics
Air Force

-oOo-

Source: https://assist.dla.mil -- Downloaded: 202610-17T05:59Z
Check the source to verify that this is the current version before use.