MIL-R-5757J
SUPPLEMENT 1
11 October 2011

MILITARY SPECIFICATION

RELAYS, ELECTROMAGNETIC, GENERAL SPECIFICATION FOR

Inactive for new design after 15 October 1998. No superseding specification

This supplement forms part of MIL-R-5757J, dated 11 October 2011.

SPECIFICATION SHEETS

MIL-R-5757/1	-	Relays, Electrical, Hermetically Sealed, 6PDT, Low Level to 2 Amperes. (Inactive for new design)
MIL-R-5757/7	-	Relays, Electromagnetic, Hermetically Sealed, 4PDT, Low Level to 2 Amperes (Inactive for new design).
MIL-R-5757/8	-	Relays, Electrical, Hermetically Sealed, DPDT, 2 Amperes (Inactive for new design).
MIL-R-5757/10	-	Relays, Electromagnetic, Hermetically Sealed, DPDT, Low Level and 2 Amperes. (Inactive for new design)
MIL-R-5757/13	-	Relays, Electrical, Hermetically Sealed, DPDT, Low Level to 2 Amperes, (Sensitive, 40 Milliwatt) (Inactive for new design).
MIL-R-5757/23	-	Relays, Electrical, Hermetically Sealed, DPDT, 10 Amperes (Inactive for new design).
MIL-R-5757/29	-	Relays, Electrical, 1PST to 4PDT Contacts, Low Level to 1/2 Ampere (Dry Reed) (Inactive for new design).

Custodians:
Army - CR
Navy - EC
Air Force - 85

Preparing activity:
DLA - CC

(Project 5945-2011-025)

Review activities:
Army - AT, AV, CR4, MI,
Navy - AS, MC, OS
Air Force – 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.daps.dla.mil/ .

AMSC N/A

FSC 5945

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T05:37Z
Check the source to verify that this is the current version before use.