INCH-POUND

MIL-R-5757/1H
AMENDMENT 3
17 March 1995
SUPERSEDING
AMENDMENT 2
9 July 1990

MILITARY SPECIFICATION SHEET

RELAYS, ELECTRICAL, HERMETICALLY SEALED,
6PDT, LOW LEVEL TO 2 AMPERES

This amendment forms a part of MIL-R-5757/1H, dated 3 January 1986, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

FIGURE 2, top view: Delete dimension "1.69" and substitute "1.70 MAX".

PAGE 3

FIGURE 2, dimension table: Delete "1.69" and "42.9" and substitute "1.70" and "43.2", respectively.

PAGE 4

Contact data, load ratings (relay case grounded): Delete "Minimum current" and substitute "Intermediate current".

*Requirements, contact bounce, high level characteristics: Delete "2 ms max (-027 and -028)" and substitute "2 ms max (-027 and -028, test at rated load)"

*Requirements, contact bounce, low level characteristics: Delete in its entirety and substitute "5 ms max (-021, -026, -027, -028)".

PAGE 5

Life test requirements, add the following after "Low level": "Intermediate current (level II)---------- 50,000 cycles".

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Preparing activity:
DLA - ES

(Project 5945-0970)

Review activities:
Army - AR, AT, AV, MI
Navy - MC, SH
Air Force - 17, 19, 99

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T05:38Z
Check the source to verify that this is the current version before use.