INCH-POUND

MIL-DTL-5757/7H
13 July 2022
SUPERSEDING
MIL-R-5757/7G
12 May 2011

DETAIL SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, HERMETICALLY SEALED, 4PDT, LOW LEVEL TO 2 AMPERES

INACTIVE FOR NEW DESIGN AFTER 18 FEBRUARY 1986. FOR NEW DESIGNS USE MIL-PRF-39016/14.

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-5757.




FIGURE 1. Relay - solder lug configuration (M5757/7-001).

AMSC N/A
FSC 5945

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T05:38Z
Check the source to verify that this is the current version before use.


Inches	mm
.152	3.86
.287	7.29
.44	11.18
1.06	26.94
1.128	28.65
1.13	28.70
1.40	35.56
1.406	35.71
1.66	42.16

NOTES:

1. Dimensions are in inches.
2. Unless otherwise specified, tolerance is ±.010 (0.25 mm).
3. Metric equivalents are given for general information only.
4. A colored line or dot shall be placed in the position shown, or optionally, the adjacent terminal in a clockwise direction around the outermost terminal circle, terminal number A3, shall have a contrasting bead.
5. Mounting screw head clearance shall be provided so that the relay may be mounted using a round head machine screw having .250 (6.35 mm) nominal head diameter. The mounting surface shall be flat with a minimum .276 (7.01 mm) diameter, and concentric with the mounting hole.

FIGURE 1. Relay - solder lug configuration (M5757/7-001) - Continued.


Source: https://assist.dla.mil -- Downloaded: 2026-10-17T05:38Z
Check the source to verify that this is the current version before use.



Inches	mm	Inches	mm
.152	3.86	1.14	28.96
.287	7.29	1.40	35.56
.44	11.18	1.406	35.71
1.06	26.92	1.66	42.16
1.128	28.65	1.70	43.18

FIGURE 2. Relay - socket pin configuration (M5757/7-003).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T05:38Z
Check the source to verify that this is the current version before use.



DETAIL A

Inches	mm	Inches	mm	Inches	mm	Inches	mm
.040	1.02	.164	4.17	.281	7.14	1.06	26.92
.060	1.52	.203	5.16	.339	8.61	1.14	28.96
.085	2.16	.210	5.33	.357	9.07	1.34	34.04
.119	3.02	.238	6.05	.36	9.14	1.406	35.71
.138	3.51	.265	6.73	.388	9.86	1.69	42.93
.140	3.56	.278	7.06	.394	10.01		

NOTES:

1. Dimensions are in inches
2. Unless otherwise specified, tolerance is ±.010 (0.25 mm).
3. Metric equivalents are given for general information only.
4. All active electrical terminals shall be gold plated 0.00005 (50 microinches) minimum. One system for gold plating that may be used is ASTM-B488, type 3, class 1.25 with a nickel underplate of 50 to 150 microinches thick. Gold plating of index pins is optional. The gold plating system shall enable the product to meet the performance requirements of this specification and shall be approved by the qualifying activity.

FIGURE 2. Relay - socket pin configuration (M5757/7-003) - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T05:38Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Contact data:

	High level characteristics (M5757/7-001)	Low level characteristics (M5757/7-003)
Configuration:	4PDT	4PDT
Arrangement:	4 form C	4 form C
Load ratings (relay case	grounded):	
Resistive:	2 amperes at 28 V dc	30 microamperes at 30 millivolts, 1000 Hz
Minimum current (resistive	loads only):	
	2 amperes at 28 V dc	Not applicable
	0.100 ampere at 28 V dc	
	0.500 ampere at 28 V dc	
Contact resistance or voltage	drop:	
Rated life:		
Before:	.05 ohm maximum	.05 ohm maximum
During:	10 percent of open circuit voltage maximum	100 ohms maximum
After:	.10 ohm maximum	.15 ohm maximum
Minimum current:		
Before:	.05 ohm maximum	Not applicable
During:	3 ohms maximum	
After:	3 ohms maximum	
Contact bounce:	1 millisecond (ms) maximum	5 ms maximum
Overload:		
Resistive:	Two times rated current	Not applicable

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T05:38Z
Check the source to verify that this is the current version before use.

Coil data:

Duty rating: continuous.

Maximum voltage: 32 V dc.

Nominal voltage: 26.5 V dc.

Pickup voltage: 18 V dc maximum over temperature range.

Dropout voltage: 14 V dc maximum over temperature range, 1.5 V dc minimum.

Coil resistance:

-001: 225 ohms minimum, 385 ohms maximum at +25°C.
-003: 225 ohms minimum, 385 ohms maximum at +25°C.

Operate time: 15 ms maximum.

Release time: 10 ms maximum.

Electrical data:

Insulation resistance: 1,000 megohms minimum, except the resistance between coil and case at high temperature shall be 500 megohms or greater.

Dielectric withstanding voltage:

	Sea level V rms (60 Hz)	Altitude V rms (60 Hz)
Between case, frame or enclosure, and all contacts in the energized and deenergized positions:	1,000	
Between case, frame or enclosure, and coil:	1,000	350
Between all contacts and coil:	1,000	All terminals to case
Between open contacts in the energized and deenergized positions:	500	
Between contact poles:	1,000	

Environmental data:

Temperature range: (-65°C to +125°C).

Vibration: (15 g's, 10 to 2,000 Hz).

Acceleration: Applicable.

Shock: (100 g's).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T05:38Z
Check the source to verify that this is the current version before use.

Physical:

Terminal strength: 5 ±0.5 pounds pull.

Sealed by welding: Optional.

Dimensions and configuration: See figure 1 and figure 2.

Terminations: See figure 1 and figure 2.

Weight: 0.2 pound maximum.

Life test requirements:

High level (applicable to M5757/7-001): 100,000 cycles at rated load.

Low level: (applicable to M5757/7-003): 100,000 cycles at rated load.

Minimum current: Level II, 50,000 cycles.

Verification:

Periodic inspection: Groups B and C inspections are not applicable.

Group A.

a. Group A1: Run-in (applicable to -003 low level relays only). This subgroup may be waived at the discretion of the qualifying activity if fully tested MIL-PRF-39016/6 relays are used internally.

b. Group A2: 100 percent.

c. Dielectric withstanding voltage:

(1) Tests to be conducted at sea level rating only.

(2) Duration of application: 5-10 seconds at a 10 percent increase in the dielectric strength voltage.

Qualification: See table I or table II as applicable.

TABLE I. Qualification inspection and sample size.

Part or Identifying Number (PIN) M5757/7	Number of sample units
-001	16 units plus 1 open unit. Qualification inspection as applicable.
-003	12 units plus 1 open unit. Qualification inspection as as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T05:38Z
Check the source to verify that this is the current version before use.


TABLE II. Extension of qualification and sample size.

PIN M5757/7		Test	Number of sample units
Qualified	Extension to		
-001	-003	Low level life	4
-003	-001	High level life	4
		Minimum current	4
		Visual and mechanical	1

Qualification by similarity: If the relay case, frame, or enclosure contains integral electromagnetic relays (mounting means excepted) currently listed on the qualified products list of MIL-PRF-39016, reduced testing shall consist of subjecting four sample units to the shock and vibration requirements of this specification sheet. Post tests shall include insulation resistance, dielectric withstanding voltage and electrical characteristics, and seal. One unsealed unit shall be submitted to the qualifying activity.

PIN: Consists of the basic number of this specification sheet and a dash number.

Example:



Supersession data: See table III.

TABLE III. Supersession data.

PIN 1/ M5757/7	Super sedes	
	FSCM	PIN
-001	81349	RY4LB1A3L01
	81349	RY4LB1B3L01
	81349	RY4LB2A3L01
	81349	RY4LB2B3L01
	81349	RY4LB3A3L01
	81349	RY4LB3B3L01
-003	80063	SM-C-415281

1/ PIN M5757/7-002, type designations RY4LB1C3L01, RY4LB2C3L01, and RY4LB3C3L01 are canceled without replacement.

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T05:38Z
Check the source to verify that this is the current version before use.

Referenced documents. In addition to MIL-DTL-5757, this document references the following:

MIL-PRF-39016 MIL-PRF-39016/6 MIL-PRF-39016/14
ASTM-B488

Custodians:
Army - CR
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

Review activities:
Army - AV, MI

(Project 5945-2022-032)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T05:38Z
Check the source to verify that this is the current version before use.