NOTICE OF
CHANGE

MIL-STD-35-l03(MI)
NOTICE 3
18 SEPTEMBER 1992

MILITARY STANDARD

AUTOMATED ENGINEERING
DOCUMENT PREPARATION SYSTEM

AMPLIFIERS

TO ALL HOLDERS OF MIL-STD-35-103(MI):

1. THE FOLLOWING PAGES OF MIL-STD-35-103(MI) HAVE BEEN REVISED AND SUPERSEDE THE PAGES LISTED.

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
3	18 SEPTEMBER 1992	3	30 JUNE 1976
4	18 SEPTEMBER 1992	4	30 JUNE 1976
5	18 SEPTEMBER 1992	5	30 JUNE 1976
6	18 SEPTEMBER 1992	6	30 JUNE 1976
7	18 SEPTEMBER 1992	7	30 JUNE 1976
8	30 JUNE 1976	(Reprinted without change)	
15	30 JUNE 1976	(Reprinted without change)	
16	18 SEPTEMBER 1992	16	18 NOVEMBER 1976
17	18 SEPTEMBER 1992	17	18 NOVEMBER 1976
18	18 SEPTEMBER 1992	18	18 NOVEMBER 1976
19	18 SEPTEMBER 1992	19	30 JUNE 1976
20	18 SEPTEMBER 1992	20	30 JUNE 1976
81	18 SEPTEMBER 1992	81	30 JUNE 1976
82	30 JUNE 1976	(Reprinted without change)	
95	18 SEPTEMBER 1992	95	30 JUNE 1976
96	18 SEPTEMBER 1992	96	30 JUNE 1976

2. RETAIN THIS NOTICE PAGE AND INSERT BEFORE THE TABLE OF CONTENTS.

3. Holders of MIL-STD-35-103(MI) will verify that page changes and additions indicated above have been entered. The notice page will be retained as a check sheet. This issuance, together with appended pages is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or canceled.

Custodians:
Army-MI

Review activities:
Army-AT, AV, CR, ER
ME, MR, SC

User activity
Army - AR

Preparing activity:
Army-MI

(project EGDS-A445)

AMSC N/A

AREA EGDS

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026l0-23T21:01Z
Check the source to verify that this is the currentversion before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

If the item selected from the AEDPS document becomes an item of supply, then the Cataloging Handbood H6 must ge used.

The MSE title may or may not be the same as the title used in DODISS, FIIG or the document to which the MSE document was written. Documents referenced in the MSE that will be listed in the Applicable Documents. paragraph (2.1) of the MSE will be identified by the exact title that appears on the referenced document. The title written on the MSE or in DODISS or FIIG will not be entered in paragraph 2.1.

1.4.2 Index

The Military Specification Exception Title index is as follows;

RELATED DOCUMENT	RELATED DOCUMENT COVERAGE	MSE TITLE	MSE TITLE CODE
		Amplifier, Audio Frequency	454001
MIL-A-14819	DOPPLER-FREQUENCY Signal		
MIL-A-23088	AM-3198( )/URC		
MIL-A-23595	AM-3597C/A & AM-4326B/A		
MIL-A-25546	AM-944/AIC-13		
MIL-A-28716	AM-3729( )/SR		
MIL-A-55129	AM-1780( )/VRC		
		Amplifier Electonic Control	454003
MIL-A-60146	Sigh System XM58		
MIL-A-83162	Synchro Signal AM-6015/A		

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

RELATED DOCUMENT	RELATED DOCUMENT COVERAGE	MSE TITLE	MSE TITLE CODE
MIL-A-55218 MIL-A-60100	AM-761( )/TPX AM-1063/MS AM-1064/MS	Amplifier, Intermediate Frequency	454004
MIL-A-28988	AM-6545\GRC-193	Amplifier, Radio Frequency	454005
MIL-A-48316	M4E1	Amplifier, Trigger Pulse	454006
MIL-A-14878	10559445 Laser Receiver-Transmitter	Amplifier, Video	454007
MIL-A-46330	AM-1075A/M		

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

SECTION 2

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-A-14819	Amplifier, Audio Frequency, Doppler
MIL-A-14878	Amplifier, Video, 10559445, Laser Reciver-Transmitter
MIL-A-23088	Amplifier, Audio Frequency, AM-3198/URC
MIL-A-23595	Amplifier, Audio Frequency, AM-3597C/A and AM-4326B/M
MIL–A-25546	Amplifier, Audio Frequency, AM-944/AIC-13
MIL–A-28716	Amplifier, Audio Frequency, AM-3729/SR

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS (CONT)

MILITARY

MIL-A-28988	Amplifier, Radio Frequency, AM-6545/GRC-193
MIL-A-46330	Amplifier, Video, AM-1075A/M
MIL-A-48316	Amplifier, Trigger Pulse, M4E1

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS (CONT)

MILITARY

MIL-A-49277	Amplifier, Audio Frequency, AM-1780A/VCR
MIL-A-55218	Amplifier, Intermediate Frequency, AM-761/TPX
MIL-A-6O100	Amplifier, Intermediate Frequency, AM-1063/MS, AM-1064/MS
MIL-A-60146	Amplifier, Electronic Control, Sight System XM58
MIL-A-83l62	Amplifier, Electronic Control, AM-6015/A

STANDARDS

MILLITARY

MIL-STD-202	Test Methods for Electronic and Electrical Component Parts
MIL–STD-461	Electromagnetic Interference Charac-teristics Requirements for Equipment
MIL-STD-462	Electromagnetic Interference Charac-teristics, Measurement of
MIL-STD-810	Environmental Test Methods
MIL–STD-2036	Electronic Equipment Specifications, General Requirements for

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents order Desk , Bldg 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

Source: https://assist.dla.mil -- Downloaded: 2026l0-23T21:01Z
Check the source to verify that this is the currentversion before use.

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation.

ASTM E 380 Metric Practice Guide

(Application for copies should be addressed to The American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:01Z
Check the source to verify that this is the current version before use.

"GROUP A INSPECTION GROUP A INSPECTION SHALL BE PERFORMED AS SPECIFIED IN THE SPECIFICATION REFERENCED IN 3.1 EXCEPT THERMAL SHOCK SHALL BE 175 DEG C HIGH TEMP."

The test method per 1006 code and requirements per 1006 code from the same test shall not be used together. This conditions would indicate no exception is being specified. If a test method code(s) has been selected, it is mandatory that a requirement code be selected; and if a requirement code has been selected, it is mandatory that a test method code(s) be selected.

5.5 Approved Item Name Code

The approved item name code to be entered on the SRS with code 1007 for an Amplifier is selected from the following list:

APPROVED ITEM MAME	ITEM NAME CODE
Audio Frequency Amplifier	00511
Direct Current Amplifier	19692
Electronic Control Amplifier	00096
Intermediate Frequency Amplifer	00885
Radio Frequency Amplifer	00094
Trigger Pulse Amplilfier	00094
Video Amplifier	00095
Unapproved Name	77777

Only the item Name Code number is entered on the SR5 with Code 1007.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

5.6 Dimensions and Figures

All specification requirements for dimensions and figures described in MIL-STD-35 are applicable.

The figures applicable to Amplifiers are contained in Section 7. It is mandatory to enter, on the SRS, Code 1009 and a figure number.

5.7 Applicable Documents

The documents listed in the Applicable Document List of Section 5 of MIL-STD-35 and appropriate codes from Table B of MIL-STD-35 shall be entered in the SRS.

Source: https://assist.dla.mil -- Downloaded: 2026l0-23T21:01Z
Check the source to verify that this is the current version before use.

THIS PAGE DELETED

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

THIS PAGE DELETED

Supersedes page 18 of 18 NOVEMBER 1976

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:01Z
Check the source to verify that this is the current version before use.

The documents listed in the Applicable Document List of Section 5 of MIL-STD-35 and appropriate codes from Table B of MIL-STD-35 shall be entered on the SRS. In addition, the appropriate documents shown in the DOCUMENTS column bellow and the applicable codes from Table B of MIL-STD-35 shall be entered on the SRS when the codes listed in the CODES column are used to be specify test. Shown parenthetically in the CODES column is a reference to the applicable test. A document designation, with a code from Table B, is entered on the SRS only once.

DOCUMENTS	CODES
MIL-STD-202	6251 (Acceleration) 6300 (DWV, Reduced Pressure) 4862 (DWV, Sea Level) 4853 (Humidity) 4810 (Inmersion) 1511 (Insulation Resistance) 1397 (Moisture Resistance) 4771 (Salt Spray) 4960 (Salt and Dust). 1482 (Shock, High Impact) 4714 (Thermal shock) 1447 (Vibration, High Frequency) 1467 (Vibration, Low Frequeny) 1427 (Vibration, Random)
MIL-STD-81O	1607 (Altitude) 4755 (Fungus) 6218 (High Temperature) 6232 (Low Temperature) 7312 (shock) 1958 (Temperature Altitude)
MIL-STD-462	1865, 1866, 1867, 1868, 1869 (Electromagnetic Interference)
MIL-STD-462	1864 (Electromagnetic Interference)
Document to which exception is taken	1006

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

In addition, when the codes listed below are used to specify mounting or special preparations in accordance with a document, the document designation with an appropriate code from Table B of MIL-STD-35 must be entered on the SRS.

6265	Acceleration, mounting
4859	DWV at reduced pressure, special preparation
6280	DWV at reduced pressure, mounting
4850	DWV at sea level, special preparation
5000	DWV at sea level, mounting
1520	Insulatiion resistance, special preparation
1449	Moisture resistance, mounting
4773	Salt spray, mounting
1468	Shock, high impact, mounting
4684	Shock, specified pulse, mounting
4719	Thermal shock, mounting
4707	Vibration, high frequency, mounting
4729	Vibration, low frequency, mounting
4975	Vibration, random, mounting

For these codes any document from the Index, 1.4.2, may be used to specify which test in the document contains applicable mounting or preparation requirement, enter on the SRS the test name and the document designation.

Code 6265 specifies that the mounting in the Acceleration, test which is not in MIL-A-6589, shall be in accordance with the mounting in the Acceleration test in MIL-A 8026.

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:01Z
Check the source to verify that this is the current version before use.

Code 1965 and an "X", entered on the SRS, will specify that the device shall remain within specified tolerance.

Code 1966 and an "X", entered on the SRS, will specify that there shall be no discontinuity during the test.

5.38 Thermal Shock

Code 4712 is the 1006 test code (see 5.4).

code 4713 is the 1006 except test code (see 5.4).

To detail a thermal shock test in accordance with MIL-STD-2O2, it is mandatory to use Codes 4714 and 4715.

Code 4714 and an "X", entered on the SRS, will specify to test in accordance with Method 107 of MIL-STD-202.

Code 4713 and a letter, entered on the SRS, will specify the applicable test condition letter.

Code 4719 and a document designation, entered on the SRS, will specify mounting shall be in accordance with the document (see 5.7).

To detail a thermal shock test, in accordance with MIL–STD-2036, Codes 1968 and 1969 are mandatory.

Code 1968 and an "X", entered on the SRS, will specify to test in accordance with MIL-STD-2036.

Code 1969 and a number, entered on the SRS, will specify the equipment class number in MIL–STD-2036.

Code 4720 is the 1006 requirements code (see 5.4).

Code 4722 is the 1006 except requirements code (see 5.4).

Code 4723 and an "X", entered on the SRS, will specify no evidence of physical damage. This code is mandatory when requirements are to be detailed after the thermal shock test.

Code 4726 and an "X", entered on the SRS, will specify the device shall remain within specified tolerance.

Source: https://assist.dla.mil -- Downloaded: 2026l0-23T21:01Z
Check the source to verify that this is the currentversion before use.

The design test conducted to determine if the parameters remain within specified tolerance after the amplifier is exposed to an environmental test are listed in the SRL under this paragraph number and title. The test to be conducted are specified by entering on the SRS the appropriate codes with an "X".

5.39 Vibration, High Frequency

Code 1445 is the 1006 test code (5.4).

Code 1446 is the 1006 except test code (5.4).

To detail the high frequency vibration test, Code 1447 and Code 1448 are mandatory. Other codes are optional.

Code 1447 and an "X", entered on the SRS, will specify to test in accordance with method 204 of MIL-STD-202.

Code 1448 and a letter, entered on the SRS, will specify the applicable test condition letter as selected from Method 204 of MIL-STD-202.

There are three codes available to specify the method of mounting. Only one may be used. Information concerning them is as follows:

Code 4709 and an "X", entered on the SRS,will specify any suitable mounting method may be used.

Code 4708 and an "X", entered on the SRS, will specify normal usage mounting means shall be used.

Code 4707 and a document designation, entered on the SRS, will specify to mount in accordance with the document (5.7).

There are two codes available to specify the method of determining mechanical resonance. Only one of the codes may be entered. Information concerning them is as follows:

Codes 1533 and an "X", entered on the SRS, will specify mechanical resonance shall be monitored visually by means of strobotac.

Code 1534 and an "X", entered on the SRS, will specify mechanical resonance shall be monitored by electrical output indicators.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

CHARACTERISTIC

REF. PARA.	NAME	CODE
5.12 (CONT)	ACCELERATION (CONT)	
	TEST CONDTION LETTER (SELECT ONE) (CONT)	
	TEST CONDITION LETTER C	
	LEVEL (G)	4893
	TEST PER (DOC DES)	1600
	(G)	1601
	*DURATION (MIN.)	1602
	*REQUIREMENTS (SELECT ONE)	
	PER 1006 DOCUMENT (SEE 5.4) ____	6271
	PER 1006 DOCUMENT EXCEPT (SEE 5.4) ____	6272
	AS FOLLOWS:	
	*NO EVIDENCE OF PHYSICAL DAMAGE.	6273
	REMAIN WITHIN SPECIFIED TOLERANCE.	6277
	NO DISCONTINUITY.	7345
	DESIGN PERFORMANCE REQUIREMENTS	
	GAIN.	2000
	POWER.	2001
	BANDWITH AND CENTER FREQUENCY.	2002

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

CHARACTERISTIC

REF. PARA.	NAME	CODE
5.12 (CONT)	ACCELERATION (CONT)	
	DESIGN PERFORMANCE REQUIREMENTS (CONT)	
	FIDELITY.	2003
	FREQUENCY RESPONCE.	2004
	IMPEDANCE.	2005
	LINEARITY.	2006
	PULSE RESPONSE.	2007
	SPURIOUS OUTPUTS.	2008
	STABILITY.	2009
5.13	ALTITIDE (LOW PRESSURE)	
	*TEST METHODS (SELECT ONE)	
	PER 1006 DOCUMENT (SEE 5.4).	1605
	PER 1006 DOCUMENT EXCEPT (SEE 5.4)____	1606
	PER MIL-STD-810, METHOD 500.	1607
	DURATION OF OPERATION AND MEASUREMENTS (HR)	1608

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.