MILITARY STANDARD

AUTOMATED ENGINEERING

DOCUMENT PREPARATION SYSTEM

INDICATORS, POINTER

TO ALL HOLDERS OF MIL-STD-35-109(MI):

1. THE FOLLOWING PAGES OF MIL-STD-35-109(MI) HAVE BEEN REVISED AND SUPERSEDE THE PAGES LISTED:

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
143	9 July 1976	(REPRINTED WITHOUT CHANGE)	
144	3 September 1976	144	9 July 1976

2. RETAIN THIS NOTICE PAGE AND INSERT BEFORE THE TABLE OF CONTENTS.

3. Holders of MIL-STD-35-109(MI) will verify that page changes and additions indicated above have been entered. The notice page will be retained as a check sheet. This issuance, together with appended pages is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or canceled.

Custodians:
Army - MI

Review activities:

Army - AT
Army - AV
Army - EL
Army - ME
Army - MR
Army - SG
Army - WC

User activity:
Army - MU

Preparing activity:
Army - MI

(Project EDS-A201)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:02Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC	
	NAME	CODE
5.22	Error, Friction	
	*Test Methods (Select one)	
	Per 1006 document (see 5.4).	2330
	Per 1006 document except (see 5.4).	2332
	Per document from 5.7 (doc des)	2334
	Test point values, column 1, Table II	Table II
	*Test points units of measure (select one)	
	Scale divisions.	2336
	Percent of full scale.	2338
	Pounds per square inch.	2340
	Kilopascals.	2342
	Pounds per hour.	2344
	Kilograms per hour.	2346
	Degrees Celsius.	2348
	Feet per minute.	2350
	Metres per second.	2352
	Knots.	2354
	Mach number.	2356

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:02Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.22	*Test points units of measure (Cont)	
	Litres.	2358
	Cubic metres.	2360
	Revolutions per minute.	2362
	Percent of rated engine speed.	2364
	Low temperature test temperature (deg C)	2412
	Plus temperature tolerance (deg C)	2413
	Minus temperature tolerance (deg C)	2418
	High temperature test temperature (deg C)	2419
	Plus temperature tolerance (deg C)	2424
	Minus temperature tolerance (deg C)	2425
	*Requirements (Select one)	
	Per 1006 document (see 5.4).	2426
	Per 1006 document except (see 5.4) ____	2427

Supersedes page 144 of 9 July 1976.

☆U.S. GOVERNMENT PRINTING OFFICE: 1976-603-766/6582

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:02Z
Check the source to verify that this is the current version before use.