
FED. SUP CLASS
5305



Nominal size			#10 (.190)	1/4 (.250)	5/16 (.3125)	3/8 (.375)
Threads per inch (UNF-3A)			32	28	24	24
D	Body diameter	Max	0.1900	0.2500	0.3125	0.3750
		Min	0.1840	0.2435	0.3053	0.3678
A	Head diameter	Max	0.312	0.375	0.469	0.562
		Min	0.303	0.365	0.457	0.550
H	Head height	Max	0.190	0.250	0.312	0.375
		Min	0.185	0.244	0.306	0.368
S	Head side height	Min	0.171	0.225	0.281	0.337
J	Socket width across flats	Max	0.1587	0.1900	0.2530	0.3160
		Min	0.1562	0.1875	0.2500	0.3125
T	Key engagement	Min	0.090	0.120	0.151	0.182
G	Wall thickness	Min	0.065	0.095	0.119	0.143
C	Chamfer or radius	Max	0.005	0.008	0.008	0.008
R	Fillet extension	Max	0.014	0.014	0.017	0.020
		Min	0.009	0.009	0.012	0.015
K	Hole location	Max	0.065	0.085	0.104	0.123
		Min	0.045	0.065	0.084	0.103
E	Hole diameter	Max	0.050	0.050	0.050	0.067
		Min	0.044	0.044	0.044	0.061
	Recommended wire diameter	Max	0.040	0.040	0.040	0.057
		Min	0.032	0.032	0.032	0.045
*	Alignment plug diameter		0.030	0.030	0.030	0.051
**	Tensile strength, lbs	Min	1,600	2,920	4,640	7,020

L Length	Tolerance	Dash no.	L_G Max	L_B Min	Dash no.	L_G Max	L_B Min	Dash no.	L_G Max	L_B Min	Dash no.	L_G Max	L_B Min
0.375		-1											
0.500		-2			-9								
0.625	+0.00	-3			-10								
0.750	-0.03	-4			-11						-19		
0.875		-5											
1.000		-6			-12			-16			-20		
1.250	+0.00	-7	0.38	0.17	-13			-17			-21		
1.500	-0.04	-8	0.38	0.17	-14	0.50	0.25	-18			-22		

For NOTES see SHEET 2.

Ⓓ denotes changes

USER ACTIVITIES:
Army – AT, ME
Navy – AS, SH

REVIEWER ACTIVITIES:
Army – MI
Navy – MC
Air Force – 11
DLA – IS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

APPROVED 7 April 1960 REVISED Ⓐ 27 January 1961 Ⓑ 7 July 1975 Ⓒ 15 March 1978 Ⓓ 9 November 1984

P.A.	OS	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD
Other Cust	AR 99		SCREW, CAP, SOCKET HEAD, HEXAGON, DRILLED CORROSION-RESISTING STEEL (UNF-3A)	MS 24673
Procurement Specification FF-S-86		SUPERSEDES:		SHEET 1 OF 2

DD FORM 1 MAY 73 672 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE 5305-1431

Source: https://assist.dla.mil - Downloaded: 2026-10-23T14:59Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS
5305

NOTES:

1. MATERIAL: Austenitic corrosion-resisting steel in accordance with FF-S-86.

2. PROTECTIVE COATING: Passivate in accordance with QQ-P-35.

3. MECHANICAL PROPERTIES: Screws shall meet the mechanical property requirements of FF-S-86 as well as the magnetic permeability requirements specified in Note 4.

4. MAGNETIC PERMEABILITY: Screws shall have a magnetic permeability of 2.0 MAX (Air = 1.0) for a field strength of H = 200 oersteds, using a magnetic indicator conforming to MIL-I-17214, or equivalent.

5. THREADS: Threads shall be in accordance with MIL-S-7742.

6. THREAD LENGTH: Screws above heavy line shall have complete (full form) threads extending within two threads of the head as measured with a thread ring gage.

7. HEAD: Head may or may not be knurled at manufacturer's option. Type of knurling optional. Diameter of knurled head shall not exceed the maximum head diameter specified.

8. DRILLED HOLE DATA:
   (a) Edges of the holes on the outside of the head shall be chamfered 45° by 0.010 to 0.020 deep.
   (b) Drilled holes shall be within the flats of the hexagon socket and shall not break the corners of the hexagon socket.

*9. ALIGNMENT PLUG: Plug shall pass completely through the head without deflection.

**10. TENSILE STRENGTH: Based on 80,000 PSI minimum ultimate tensile strength. Load pounds calculated by the stress areas indicated in Fed-STD-H28.

11. DIMENSIONS: Dimensions are in inches, unless otherwise specified.

12. PART NUMBER: The MS part number consists of the MS number, plus the dash number.
Example: MS 24673-1 is the part number for a screw .190-32UNF-3A by 0.375 long of corrosion-resisting steel.

13. OTHER NOTES:
   (a) Referenced documents shall be of the issue in effect on date of invitation for bids.
   (b) For design feature purposes, this standard takes precedence over procurement documents referenced herein.

APPROVED 7 April 1960 REVISED ① For changes see sheet 1.

P.A. OS Other Cust AR 99	INTERNATIONAL INTEREST	TITLE SCREW, CAP, SOCKET HEAD, HEXAGON, DRILLED CORROSION-RESISTING STEEL (UNF-3A)	MILITARY STANDARD MS 24673	
Procurement Specification FF-S-86	SUPERSEDES:		SHEET 2	OF 2

DD FORM 1 MAY 73 672 (COORDINATED) SUPERSEDES PREVIOUS EDITION OF 1 JUN 65 IS OBSOLETE

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T14:59Z
Check the source to verify that this is the current version before use.