MILITARY SPECIFICATION

BATTERY ASSEMBLY, TRAINING: 14XPM-15

1. SCOPE

1.1 This specification covers requirements, quality assurance provisons, and the preparation for delivery criteria for one type of battery assembly, Training: 14XPM-15 used with the Atomic Demolition Charge.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

TT-V-109-Varnish, Spar, Alkyd-Resin

STANDARDS

MILITARY

AN960C416 - Washer, Plain, Flat
MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MS29561-010 - "O" Ring
MS5275-254 - Screw, Machine, Filister Head
MS51971-1 - Nut, Plain, Hexagon

DRAWINGS

ORDNANCE CORPS

8808362 - Packing and Marking for Storage and Shipments
8887528 - Block
8887539 - Block
8887540 - Block

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:45Z
Check the source to verify that this is the current version before use.

8887541 - Block
8887542 - Vent Plate
8887543 - 14XPM-15 Battery Assembly Training
8887544 - Orifice Block
8887545 - Vent Plate Assembly
8887547 - Vent
8887551 - Reservoir Assembly
8887552 - Bottom Reservoir
8887553 - End Reservoir
8887582 - Decal, Battery, Training
8887599 - Screw, Nylon, Drain
9206900 - Box, Fiber, for 14 XPM-15, Battery Assembly, Training
9242431 - Cement, Acrylic
9242432 - Sponge, Rubber Plug
9242433 - Vent Cap
ET-8887543 - Equipment Tabulation

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The battery assembly shall comply with all requirements specified on the drawing (dwg) 8887543, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 Workmanship.

3.3.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.3.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.3.3 Burrs. Parts shall be free from burrs.

3.3.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.3.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:45Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection. Not Applicable.

4.3 Quality Conformance Inspection.

4.3.1 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

4.3.2 Product inspection examination. Critical characteristics shall require 100 percent inspection of all items in the inspection lot. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Table I
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:45Z
Check the source to verify that this is the current version before use.

Table II
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Washer (see AN960C416); "O" ring (see MS29561-010); screw, machine, filister head (see MS35275-280); screw, machine (see MS35275-254); nut, plain, hexagon (see MS51971-1); screw, nylon, drain (see dwg 8887599); cement, acrylic (see dwg 9242431); sponge rubber plug (see dwg 9242432); vent, cap (see dwg 9242433); decal, battery, training (see dwg 8887582); covering details of dwgs 8887545 and 8887543 as applicable.

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Objective evidence (see 6.2) for part in accordance with applicable standard or drawing	Visual
Minor:		
201.	None defined.	

4.3.2.1.2 Block (see dwg 8887539-1 & 2) covering a detail of dwg 8887545.

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Thickness, max	Gage
102.	Paint present no bare spot	Visual
103.	Marking (8887539-2) only)	Visual
104.	Laquer coating present	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:45Z
Check the source to verify that this is the current version before use.

105. Materials (see 3.1).....Visual

Minor:
201. Workmanship (see 3.3).....Visual/Manual

4.3.2.1.3 Block (see dwg 8887540) covering a detail of dwg 8887545.

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Total length, max.	Gage
102.	Thickness, max.	Gage
103.	Paint present no bare spot.	Visual
104.	Marking.	Visual
105.	Laquer coating present.	Visual
106.	Materials (see 3.1).	Visual/Manual
Minor:		
201.	Workmanship (see 3.3).	Visual/Manual

4.3.2.1.4 Block (see dwg 8887541) covering a detail of dwg 8887545.

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Paint present no bare spot.	Visual
102.	Total length, max.	Gage
103.	Thickness, max.	Gage
104.	Lacquer present.	Visual
105.	Marking.	Visual
106.	Materials (see 3.1).	Visual
Minor:		
201.	Workmanship (see 3.1).	Visual/Manual

4.3.2.1.5 Vent plate (see dwg 8887542) covering a detail of dwg 8887545.

Categories	Characteristics	Method of Inspection
Critical: None defined.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:45Z
Check the source to verify that this is the current version before use.

Major:
101. Location of counterbored holes.....Gage
102. Location of threaded holes.....Gage
103. Location of 3 holes.....Gage
104. Length, max.....Gage
105. Width, max.....Gage
106. Thickness, max.....Gage
107. Material (see 3.1).....Visual

Minor:
201. Workmanship (see 3.3).....Visual/Manual

4.3.2.1.6 Vent (see dwg 8887547) covering a detail of dwg 8887545.

Categories	Characteristics	Method of Inspection

Critical: None defined.

Major:
101. Diameter of inside hole.....Gage
102. Diameter of top cavity.....Gage
103. Diameter of bottom cavity.....Gage
104. Depth of top cavity.....Gage
105. Length from bottom of bottom cavity to top face.....Gage
106. Material (see 3.1).....Visual

Minor:
201. Workmanship (see 3.3).....Visual/Manual

4.3.2.1.7 Block (see dwg 8887528) covering a detail of dwg 8887545.

Categories	Characteristics	Method of Inspection

Critical: None defined.

Major:
101. Length, max.....Gage
102. Thickness, max.....Gage
103. Material (see 3.1).....Visual

Minor:
201. Workmanship (see 3.3).....Visual/Manual

4.3.2.1.8 Vent plate assembly (see dwg 8887545) covering a detail of dwg 8887543.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:45Z
Check the source to verify that this is the current version before use.

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Joints flush	Visual/Manual
102.	No excess cement	Visual
103.	Two screws with sealing compound	Visual
104.	Nuts free of sealing compound	Visual
105.	No part loose or improperly assembled	Visual/Manual
Minor:		
201.	Workmanship (see 3.3)	Visual/Manual

4.3.2.1.9 End, reservoir (see dwg 8887553-1) covering a detail of dwg 8887551.

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Length, max	Gage
102.	Width, max	Gage
103.	Material (see 3.1)	Visual
Minor:		
201.	Workmanship (see 3.3)	Visual/Manual

4.3.2.1.10 Bottom, reservoir (see dwg 8857552) covering a detail of dwg 8887551.

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Length, max	Gage
102.	Width, max	Gage
103.	Thickness, max	Gage
104.	Materials (see 3.1)	Visual
Minor:		
201.	Workmanship (see 3.3)	Visual/Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:45Z
Check the source to verify that this is the current version before use.

4.3.2.1.11 Reservoir assembly (see dwg 8887551) covering a detail of dwg 8887543.

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Joints flush	Visual/Manual
102.	No excess cement	Visual
103.	Pitch diameter of thread side hole, max	Gage
104.	Minor diameter of thread side hole, max	Gage
105.	Location of hole in side	Gage
Minor:		
201.	Workmanship (see 3.3)	Visual/Manual

4.3.2.1.12 Orifice block (see dwg 8887544) covering a detail of dwg 8887543.

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Pitch diameter of 4 threaded holes, max	Gage
102.	Minor diameter of 4 threaded holes, max	Gage
103.	Diameter of orifice hole	Gage
104.	Diameter of countersink on orifice hole	Gage
105.	Diameter of counterbore on orifice hole	Gage
106.	Depth of counterbore on orifice hole	Gage
107.	Length, max	Gage
108.	Height, max	Gage
109.	Width, max	Gage
110.	Material (see 3.1)	Visual
Minor:		
201.	Workmanship (see 3.3)	Visual/Manual

4.3.2.1.13 14XPM-15 battery assembly, training (see dwg 8887543).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	No part missing or improperly assembled	Visual
102.	Joints flush	Visual/Manual
103.	Decal coated with varnish	Visual
104.	Objective evidence available for varnish in accordance with TT-U-109	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:45Z
Check the source to verify that this is the current version before use.

Minor:
201. Workmanship (see 3.3).....Visual/Manual

4.3.2.1.14 Box, fiber, for 14XPM-15 battery assembly, training (see dwg 9206900).

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Contents tight in container	Manual
102.	Carton properly sealed	Visual
103.	Label properly applied	Visual
Minor: None defined.		

4.3.2.1.15 Packing and marking for storage and shipments (see dwg 8808362).

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Gross load weight, max	*Measure
102.	Contents tight in package	Manual
103.	Correctly packed	Visual/Manual
104.	Material (see 3.1)	Visual

*Determine weight with suitable scale.

Minor:
201. Marking.....Visual
202. Workmanship (see 3.3).....Visual/Manual

4.3.3 Testing. This test shall be performed.

Test	Test Classification
a. Leakage	Major

This test is not considered destructive and samples so tested may be returned to the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:45Z
Check the source to verify that this is the current version before use.

4.3.3.1 Leakage (see dwg 8887543). Each battery assembly shall be tested in accordance with 4.4.1. If any item fails to comply with drawing requirements, the item shall be rejected and removed from the lot.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Critical and major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL). ELs for assemblies are listed on the Equipment Tabulation, ET-8887543. When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment and obtain approval prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired (see 6.3).
b. The code "CD" is listed in the "Part or Identifying Number" column on the EL (see 6.1.2).

4.3.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on ELs. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

4.4.1 Leakage (see 4.3.3.1). Fill each cell of the battery with 35 cubic centimeters of water with the battery on a level surface. If leakage occurs at the joint between the reservoir and orifice block, dry the battery without disturbing position. Allow the battery to stand 15 minutes, minimum. Observe the battery for any evidence of leakage.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A. The battery assembly shall be packaged in accordance with dwg 9206900 and 8808362 using the specified moisture barrier.

5.1.2 Level C. The battery assembly shall be packaged in accordance with dwg 9206900 and 8808362 except that the moisture barrier may be omitted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:45Z
Check the source to verify that this is the current version before use.

5.2 Packing.

5.2.1 Level A and C. The battery assembly shall be packed in accordance with dwg 9206900 and 8808362.

5.3 Marking. Marking shall be as specified in accordance with dwg 9206900 and 8808362.

6. NOTES

6.1 Ordering data. Procurement documents should specify:

6.1.1 Procurement requirements

a. Title, number and date of this specification.
b. Selection of applicable level of packaging and packing (see 5.1 and 5.2).

6.1.2 Contract data requirements (see 4.3.4.1). Data specified in 4.3.4.1 will be delivered as identified on a numbered DD Form 1667 or specification when required on a DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commanding Officer, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SMUPA-NR4.

Custodian:
Army - MU

Preparing activity:
Army - MU

Project No. 6910-A292

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:45Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

MIL-B-50961(MU) Battery Assembly, Training 14 XPM-15

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:45Z
Check the source to verify that this is the current version before use.