MILITARY SPECIFICATION

CARTRIDGE, 20MM, DUMMY, M51A3

This Specification is approved for use within the US Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers requirements, quality assurance provisions and preparation for delivery for one type of cartridge designated as Cartridge, 20mm, Dummy, M51A3 for use in 20mm, Automatic guns.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards and handbooks. The following specifications, standards and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issue of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification, for

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-651 - Visual Inspection Standard for 20mm Ammunition and Components
MIL-STD-1168- Lot Numbering of Ammunition

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament,Munitions and Chemical Command, Attn. AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A
FSC 1305
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, and drawings and publications. The following other Government documents, drawings and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect of the date of solicitation.

DRAWINGS (see 6.4)

US ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

12551820 - Cartridge, 20mm, Dummy, M51A3
12551821 - Projectile for Cartridge, 20mm, Dummy, M51A3
12551822 - Case for Cartridge, 20mm, Dummy, M51A3

INSPECTION EQUIPMENT DRAWINGS

7259434 - Scale
7259472 - Acceptance Check Gage
7298435 - Staging Fixture
7298436 - Over Screen Chart
7285209 - Contour Projector Lens
7298155 - Contour Projector (Shadow only)
7556901 - Indicator Comparator Gage
7559527 - Instructions
7560498 - Riser Block

(Copies of specifications, standards, and drawings required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the Contracting Officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DoDISS specified in the solicitation. Unless otherwise specified, the issues of the documents not listed in the DoDISS shall be the issue of the nongovernment documents which is current on the date of solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM B117- Standard Method of Salt Spray (FOG) Testing

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General.

a. Material. Materials shall be in accordance with the applicable drawings and specifications.

b. Manufacturing process. All parts and assemblies shall be manufactured by a process approved by the contracting officer, and no deviation from that process shall be made without prior approval (6.6).

3.2 Cartridge. The cartridge shall comply with all requirements specified on Drawing (dwg.) 12551820, all associated drawings, and with all requirements specified in applicable specifications.

3.3 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3 and 6.5).

3.4 Projectile torque. The projectile shall withstand a minimum of 50 foot-pounds torque applied counterclockwise without movement.

3.5 Protective coating.

3.5.1 Plating. The plating on the projectile and case shall be in accordance with the requirements of the applicable drawings.

3.5.2 Corrosion resistance. The exterior plated surface of the cartridge shall show neither white corrosion products of cadmium nor basis metal corrosion products at the end of 96 hours when tested by continuous exposure to the salt spray in accordance with 4.5.2.

3.6 Workmanship. The requirements for workmanship are as specified by applicable drawings, referenced specifications and the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

3.6.1 Processing defects. The metal parts shall be free of defects such as; deep scratches, cuts, excessive surface roughness, cracks, dents, metal flaws, burrs, deformities, sharp edges, plating flaws, tarnish, scale, peeling, blisters and other forms of substandard workmanship.

3.6.2 Cleanliness. All components and assemblies shall be free of foreign matter, such as, oil, grease, corrosion, dirt, chips and adhesive on external surfaces.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may utilize his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspections set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of any defective material.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item.

a. First Article Inspection. (4.3)

b. Quality Conformance Inspection. (4.4)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article as designated by the contracting officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated:

Part descriptions	Drawing	Quantity
Cartridge	12551820	132
Projectile	12551821	132
Case	12551822	132

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I herein.

4.3.3 Rejection. See MIL-A-48078. Failure of the original first article sample to be in accordance with the applicable drawings and requirements of Table I, as specified herein will result in sample disapproval.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS MIL-C-48672(AR)

PARAGRAPH	TITLE: Cartridge and Components		SHEET 1 OF 1		DRAWING NUMBER: See below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Projectile (Dwg. 12551821) Examination for defects	132	Acc-0 Rej-1	3.2	4.4.2.1
	Case (Dwg. 12551822) Examination for defects	132	Acc-0 Rej-1	3.2	4.4.2.2
	Cartridge (Dwg. 12551820) Examination for defects	132	Acc-0 Rej-1	3.2	4.4.2.3
	Torque test	100	Acc-0 Rej-1	3.4	4.4.2.4/4.5.1
	Corrosion resistance	32	Acc-0 Rej-1	3.5.2	4.4.2.4/4.5.2

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, each inspection lot shall contain:

a. Cartridges produced by one manufacturer in one unchanged process, in accordance with the same drawing and drawing revisions, and same specification and specification revisions.

4.4.2 Examination. See MIL-A-48078.

a. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

b. Major and minor defects. To determine product acceptability, major and minor defects as listed herein may be considered collectively on a class basis or defects may be considered individually. When a class basis is utilized the Acceptable Quality Level (AQL) for major defects shall be 1.50 percent and the AQL for minor defects shall be 2.50 percent. However, when major defects are considered collectively on a class basis, the AQL for any individual defect shall be limited to .40 percent. In addition, where three or less defects appear in a classification sampling plans applicable to a class shall not be used for major defects.

c. Critical defects. Unless otherwise specified, one hundred percent examination shall be performed for all critical defects. If a visual critical defect is found in a sample the lot shall be rejected. The lot shall then be screened and resubmitted for visual inspection of critical defects. If a critical defect is found during packing, the portion of the lot that has been packed or is in the process of being packed shall be rejected. In addition, the portion of the lot remaining to be packed shall be rejected. The lot shall then be screened and resubmitted for visual inspection of critical defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48672(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 12551821
4.4.2.1	Projectile for Cartridge, 20mm Dummy 1/				NEXT HIGHER ASSEMBLY 12551820
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	.7500-28UN-2A Thread, pitch diameter		0.25	3.2	Gage
102.	.7500-28UN-2A Thread, major diameter		0.25	3.2	Gage
103.	.826 Diameter, rotating band		0.25	3.2	Gage
104.	3.449, Total length		0.25	3.2	Gage
105.	2.949, Length to rear of crimp groove		0.25	3.2	Gage
106.	.005 Runout of .826 diameter with datums -A- and -B-		0.25	3.2	Gage
107.	.002 Runout of .784 diameter with datums -A- and -B-		0.25	3.2	Gage
108.	.784 Diameter, bourrelet		0.25	3.2	Gage
109.	Profile and location of "detail A"		0.25	3.2	Gage
110.	Presence of corrosion		0.25	3.5.2	Visual
MINOR					
201.	AA63 Surface roughness		0.40	3.2	Visual
202.	Protective plating missing or non-uniform		0.40	3.2	Visual
203.	Marking incorrect, missing or improperly placed		0.40	3.2	Visual
204.	Poor workmanship		0.65	3.6	Visual

NOTES: 1/ MIL-STD-651 shall apply in defining and evaluating visual defects as applicable.

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48672(AR)

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.2	Case for Cartridge, 20mm Dummy 1/		12551822
			NEXT HIGHER ASSEMBLY 12551820

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	.7500-28UN-2B or .7500-28UN-2B (Spiralock) Thread, pitch diameter		0.25	3.2	Gage
102.	.7500-28UN-2B or .7500-28UN-2B (Spiralock) Thread, minor diameter		0.25	3.2	Gage
103.	1.005 Diameter extractor groove, max		0.25	3.2	2/
104.	.120 Width extractor groove		0.25	3.2	2/
105.	.099 Thickness head rim, min		0.25	3.2	2/
106.	1.165 Diameter head, min		0.25	3.2	2/
107.	Head chamfer missing		0.25	3.2	Visual
108.	.070, Length of flat on mouth rim, min		0.25	3.2	2/
109.	3.651, Total Length, max		0.25	3.2	Gage
110.	1.105 Diameter, body taper at 1.750 location, min		0.25	3.2	Gage
111.	.005 Runout of 1.165 diameter with datums -A- and -B-		0.25	3.2	Gage
112.	.375 Min, effective threads		0.25	3.2	Gage
113.	Head configuration		0.25	3.2	Visual
114.	Presence of corrosion		0.25	3.5.2	Visual
115.	3.458 Length to .942 datum diameter		0.15	3.2	Gage
MINOR					
201.	AA63 Surface roughness		0.40	3.2	Visual
202.	Protective plating missing or non-uniform		0.40	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48672(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 12551822
4.4.2.2	Case for Cartridge, 20mm Dummy 1/				NEXT HIGHER ASSEMBLY 12551820
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
203.	3.651, Total length, min		0.40	3.2	Gage
204.	1.005, Diameter extractor groove, min		0.40	3.2	2/
205.	1.165 Diameter, head, max		0.40	3.2	2/
206.	Poor workmanship		0.65	3.6	Visual

NOTES: 1/ MIL-STD-651 shall apply in defining and evaluating visual defects as applicable.
2/ 7298155, 7285209, 7298436,7560498, 7298435, 7559527, 7259472.

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48672(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.3	Cartridge, 20mm Dummy 1/				12551820
					NEXT HIGHER ASSEMBLY N/A
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL					
1	Presence of live loaded cartridge		100%		Visual
MAJOR					
101.	4000 Grains, cartridge weight		0.25	3.2	7259434
102.	6.515 Overall length, max		0.25	3.2	7556901
103.	Protective Plating missing or nonuniform		0.25	3.2	Visual
104.	Presence of corrosion		0.25	3.5.2	Visual
105.	Profile and alignment, max.		0.25	3.2	Gage
MINOR					
201.	Incorrect, missing or improperly placed ammunition lot number (see MIL-STD-1168)		0.40	3.2	Visual
202.	Poor workmanship		0.65	3.6	Visual

NOTES: 1/ MIL-STD-651 shall apply in defining and evaluating visual defects as applicable.

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.4	Cartridge, 20mm, Dummy Test Requirements		12551820
			NEXT HIGHER ASSEMBLY: N/A

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Projectile Torque Test	50	4.4.3.1	3.4	4.5.1
	Corrosion Resistance	32	4.4.3.2	3.5	4.5.2

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

4.4.3 Tests. The tests listed in 4.4.2.4 shall be performed on each cartridge lot in accordance with the test methods prescribed in 4.5. Sample size and acceptance criteria for each test shall be as specified. Only cartridges which have met the visual and dimensional requirements and which have been selected in such a manner that the sample is representative of the entire lot shall be used in the tests. The selected cartridges shall be mixed thoroughly before being divided into samples for the various tests.

4.4.3.1 Projectile torque. If two or more sample cartridges fail to comply with the minimum torque requirement, the lot shall be rejected. If one cartridge of the sample fails to comply with the minimum torque requirement, a second sample consisting of the same number of cartridges as specified in the first sample shall be tested. The lot shall be rejected if two or more cartridges of the accumulated samples fails to comply with the minimum torque requirement.

4.4.3.2 Corrosion resistance. If two or more sample cartridges fail to comply with the corrosion resistance requirement, the lot shall be rejected. If one cartridge of the sample fails to comply with the corrosion resistance requirement, a second sample consisting of the same number of cartridges as specified in the first sample shall be tested. The lot shall be rejected if two or more cartridges of the accumulated samples fails to comply with the corrosion resistance requirement.

4.4.4 Packaging, packing and marking. Inspection for packaging, packing and marking shall be in accordance with MIL-STD-644.

4.4.5 Inspection equipment. The inspection equipment required to perform the examination and test prescribed herein is described in the Paragraph Reference/Inspection Method Column in tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See section 6 of MIL-A-48078 and 6.3 herein.

4.5 Test methods and procedures.

4.5.1 Projectile torque test. The sample cartridge shall be marked with a light scratch extending axially across the rotating band onto the case neck. The marked cartridges shall be placed in a fixture and the torque requirement shall be applied slowly counterclockwise to the projectile. Observation shall be made for movement of the projectile with respect to the misalignment in the scratch mark. This test is a non-destructive test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

4.5.2 Corrosion resistance. The method of test shall be as prescribed in American Society for Testing and Materials (ASTM), ASTM B117.

5. PACKAGING

5.1 Preservation and packaging. The M51A3 cartridge shall be preserved and packaged in accordance with instructions and the applicable combination of adopted items drawing from the procuring agency.

5.2 Packing. The cartridge shall be packed in accordance with the combination of adopted items drawing from the procuring agency.

5.2 Marking. Marking of the packed container shall be in accordance with the applicable combination of adopted items.

5.3 Shipping. When shipments from more than one lot are shipped as a carload, each lot shall be kept separate and the division between lots clearly indicated to prevent mixing of lots in transit.

6. NOTES

6.1 Intended use. This specification covers the production, assembly and packing for Cartridge, 20mm, Dummy, M51A3 for use in automatic cannon systems.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. (See MIL-A-48078). Submit inspection equipment designs as required to: Commander, ARDEC, ATTN: AMSMC-QAF-I(D), Picatinny Arsenal, NJ 07806-5000.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, US Army Research and Development Command (ARRADCOM) Picatinny Arsenal or US Army Armament Research Development Center (ARDC) drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.5 First article. When a first article inspection is required, the items should be a first article sample. The first article should consist of the items specified in paragraph 4.3.1. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations,

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

approval of first article test results and disposition of first articles. Invitation for bids should provide that the government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior government approval is presently appropriate for the pending contract.

6.6 Process deviation. A process deviation is defined as a change in the approved basic method of manufacture, or an operational change which may alter the metallurgical or physical properties of the item.

6.7 Subject term (key words) listing.

Dummy Cartridge
Small Arms Ammunition

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1305-AC78)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
US ARMY ARDEC
ATTN: AMSMC-QA
PICATINNY ARSENAL, NJ 07806-5000

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-48672	CARTRIDGE, 20MM, DUMMY. M51A3

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.