23 SEP 82
SUPERSEDING
MIL-C-83864(USAF)
6 June 1973

MILITARY SPECIFICATION

CONTAINER, INNER, SURVIVAL KIT

This specification is approved for use by the Departments of the Air Force, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE.

1.1 Scope. This specification covers the requirements for the survival kit inner container, more commonly known as a Rucksack. This container is used to protect life support equipment.

2. APPLICABLE DOCUMENTS.

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-B-636	Box, Shipping, Fiberboard

Military

MIL-P-116	Preservation, Methods of
MIL-W-4088	Webbing, Textile, Woven Nylon
MIL-C-5040	Cord, Nylon
MIL-C-20696	Cloth, Coated, Nylon, Waterproof
MIL-S-83427	Survival Kit Containers, CNU-129(V)/P and CNU-130/P

STANDARDS

Federal

FED-STD-191	Textile Test Methods
FED-STD-595	Colors

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: the Engineering Division, San Antonio Air Logistics Center, Kelly AFB, TX 78241 by using the self-addressed Standardization Document Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:51Z
Check the source to verify that this is the current version before use.

Military

DOD-STD-100	Engineering Drawing Practices
MIL-STD-129	Marking for Shipping and Storage
MIL-STD-130	Identification Marking of U.S. Military Property
MIL-STD-143	Standards and Specifications, Order of Precedence for the Selection of
MIL-STD-794	Part and Equipment, Procedures for Packaging and Packing of
MIL-STD-831	Test Reports, Preparation of

DRAWINGS

Air Force

59D3607	Container-Survival Kit Container Inner, Assembly of

*(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

*2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

HQ DPSC HANDBOOK 4120.1	List of Armed Services Colors for Clothing, Equipages and Textiles.

(Application for copies should be addressed to the Defense Personnel Support Center, 2800 South 20th Street, Philadelphia PA 19101).

*2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS.

*3.1 First Article testing. This specification makes provision for First Article testing.

3.2 Selection of specifications and standards. Specifications and standards for necessary commodities and services not specified herein shall be selected in accordance with MIL-STD-143.

3.3 Materials. Materials shall conform to applicable specifications and shall be as specified herein and on applicable drawings. Materials which are not covered by specifications, or which are not specifically described herein, shall be of the best quality, of the lightest practicable weight, and suitable for the purpose intended.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:51Z
Check the source to verify that this is the current version before use.

3.3.1 Nonmetallic materials. The material used shall be of the type which resists moisture, fungi, and is not susceptible to melting, hardening, cracking, chipping, or peeling.

3.3.2 Metals. Metals shall be of the corrosion-resistant type or suitably treated to resist corrosion due to fuels, salt spray, or atmospheric conditions likely to occur in storage or normal service. Metals shall be protected against such corrosion in a manner that will in no way prevent compliance with the performance requirements of this specification. The use of any protective treatment that will crack, chip, or scale with age or extremes of atmospheric conditions shall be avoided.

*3.4 Design and construction. The inner container assembly shall be designed to provide a moisture proof environment for life support equipment within the forward main compartment of the survival kit in accordance with MIL-S-83427. The inner container assembly shall be constructed of a chloroprene coated nylon cloth, semicured, conforming to MIL-C-20696, Type II, Class I, sage green color No. 34058 or black color No. 37038 per FED-STD-595. The inner container shall have a vent valve and vent flap, a slide fastener and fastener guard, a swivel eye clip and attaching cord, and two shoulder straps, including necessary reinforcements. The inner container shall be constructed in accordance with 59D3607 or as specified by the procuring activity. The assembly shall be complete when all attachments are made. The inner container shall be designed so as to maintain moisture proof integrity and shall have vulcanized lap joints, one inch minimum in width.

3.4.1 Vent valve. The vent valve shall have the performance characteristics specified in 3.5.1.

3.4.2 Slide fastener. The slide fastener shall be equal to and interchangeable with P/N 1430-19X manufactured by B. F. Goodrich Corporation, Akron Ohio. The slide fastener shall be medium heavy, leakproof, pressure sealing, and closed at both ends with a tab on the lip sealing side.

3.4.3 Swivel eye clip. The swivel eye clip shall be equal to and interchangeable with P/N 334 manufactured by North and Judd Manufacturing Co., New Britain, Conn. The clip shall have a black oxide finish and have a one-fourth inch eye. The clip shall be attached to the shoulder strap with nylon cord and tied with a figure eight knot. The nylon cord shall be in accordance with MIL-C-5040, Type I. The color shall be sage green No. 1521 in accordance with HQ DPSC Handbook 4120.1.

3.4.4 Shoulder strap. The shoulder strap shall be made of nylon webbing in accordance with MIL-W-4088, Type XII and attached according to 59D3607. The color shall be sage green, No. 1531 in accordance with HQ DPSC Handbook 4120.1.

3.5 Performance.

3.5.1 Vent valve. The valve shall open and reseat within the limits of 0.3 and 0.8 pounds per square inch. The flow rate shall be 5 cubic feet per minute, plus or minus 0.5 cubic feet per minute at a pressure of 1.5 pounds per square inch.

3.5.2 Lap joint strength. The vulcanized lap joints shall have a minimum break strength of 100 pounds per inch when tested per paragraph 4.5.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:51Z
Check the source to verify that this is the current version before use.

3.5.3 Moisture proof integrity. The inner container shall be able to withstand submergence in water without leakage, when tested per paragraph 4.5.4.

*3.6. Interchangeability. All parts having the same manufacturer's part number shall be functionally and dimensionally interchangeable. The drawing number requirements of DOD-STD-100 shall govern changes in the manufacturer's part numbers.

3.7 Identification of product. The inner container assembly shall be marked with the following information in accordance with MIL-STD-130. The marking shall be permanently affixed or impregnated on that area between and on the same side as the shoulder straps, centered, and having a minimum letter height of 3/16 of an inch and shall be of a suitable contrasting color.

Manufacturer's Name and Code
Manufacturer's Part Number
Rucksack
MIL-C-83864A(USAF)
Federal Stock Number
US Air Force
Contract Number

The manufacturer shall include the applicable information.

3.8 Workmanship. The inner container of the survival kit shall be uniform in quality and shall be free from irregularities, defects, or foreign matter which could adversely affect safety, performance, reliability or durability.

4. QUALITY ASSURANCE PROVISIONS.

*4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless otherwise disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The examination and testing of the inner container of the survival kit shall be classified as follows:

* (a) First Article. First Article consists of examinations and tests performed on samples submitted for approval as qualified products.

(b) Quality conformance inspection. Quality conformance inspection consists of examinations and tests performed on individual products or lots with the requirements set forth in this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:51Z
Check the source to verify that this is the current version before use.

*4.3 First Article inspection. First Article inspection shall consist of all examinations and tests of this specification.

*4.3.1 First Article samples. The First Article samples shall consist of three inner container assemblies prepared in accordance with this specification and representative of production. The test samples that were tested shall be furnished to the qualifying activity at the same time as the test reports. The samples shall be identified with such information as required in this specification and the procuring activity.

4.3.2 Test report. Three copies of a test report prepared in accordance with MIL-STD-831 shall be furnished to the qualifying activity. The test report shall include the results of all tests and detailed statement of compliance or noncompliance with each requirement of this specification, identified by the applicable paragraph number.

4.4 Quality conformance inspection. Quality conformance inspection shall consist of the individual and sampling tests as specified in the following.

4.4.1 Individual tests. The tests specified in paragraph 4.5.1 and paragraph 4.5.4 shall constitute individual tests.

4.4.2 Sampling tests. One inner container assembly out of a lot of 100 or fraction thereof, shall be tested according to paragraphs 4.5.2 and 4.5.3.

4.4.3 Rejection and retest. When an item selected from a production run fails to meet the specification, no items still on hand or later produced shall be accepted until the extent and cause of failure have been determined and appropriately corrected. The contractor shall explain to the Government representative the cause of failure and the action taken to preclude recurrence. After correction, all of the tests shall be repeated.

4.5 Test Methods.

4.5.1 Visual examination. The container shall be examined according to Table I. Any major defect shall constitute rejection. Three minor defects out of a lot of 50 container assemblies, or fraction thereof, shall constitute rejection.

4.5.2 Vent valve test. The vent valve on the container shall be tested to determine the performance characteristics of the valve required in paragraph 3.5.1.

4.5.3 Lap joint strength. The container assembly shall be placed in an environment with 150°F plus or minus 10°F temperature and have a relative humidity of 95% plus or minus 5% for 30 days. For sampling test, environmental aging shall be 120 hours. The lap joints shall then be tested per Method 5102 of FED-STD-191 to provide and accurate evaluation of bond strength. Five one-inch by six-inch specimens cut with the long dimension at right angles to the run of the joint shall be tested. The bond shall meet the requirements as specified in paragraph 3.5.2.

4.5.4 Water tight integrity. The inner container assembly shall be fully packed with material to simulate survival equipment and submerged in water for five minutes to a depth of twelve inches, minimum. The container shall meet the requirements of paragraph 3.5.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:51Z
Check the source to verify that this is the current version before use.

TABLE I

CLASSIFICATION OF DEFECTS FOR VISUAL EXAMINATION.

CRITICAL	MINOR
1. Deterioration of bonds of lap joints, reinforcement patches, shoulder straps, slide fastener, and vent valve. 2. Material shredding, chipping, or peeling from main container. 3. Rusting, pitting, or difficulty in operation of the slide fastener. 4. Holes or other noticeable impairments to intended use of the inner container assembly. 5. Incorrect assembling or improper positioning of components. 6. Dimensions not in conformance with drawing requirements.	101. Color not acceptable according to specification. 102. The swivel clip and attaching cord not attached to the shoulder straps properly. 103. Cover flaps stitching loose or torn. 104. Marking illegible, missing or not in proper location. 105. Any attachments which are not of proper color, class, type, length or grade. 106. Any foreign matter which is evident and which might hinder operations or effectiveness of the container.

*5. PACKAGING.

5.1 Level A. The survival kit container shall be packaged in accordance with Method 1c3 of MIL-P-116. The slide fastener shall be closed and protected with a fiberboard stiffener and the fastener shall not be folded.

5.1.2 Level C. The level C preservation for container shall conform to MIL-STD-794 requirements for this level.

5.2 Level A. The survival kit container shall be packed in fiberboard containers conforming to PPP-B-636, class weather resistant. The closure and waterproofing shall be in accordance with the appendix of PPP-B-636.

5.2.1 Level B. Same as 5.2 except the PPP-B-636 shall be class domestic.

5.2.2 Level C. The level C packing for Survival Kit Container shall conform to MIL-STD-794 requirement for this level.

5.3 Marking Level A, B & C. In addition to any special or other identification marking required by the contract (6.2) each unit pack, intermediate and exterior container shall be marked in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:51Z
Check the source to verify that this is the current version before use.

6. NOTES.

6.1 Intended use. The inner container assembly or rucksack shall be used as a container for survival equipment which need an environment free from moisture or other debris that might otherwise affect their intended use. The container shall be packed with those survival items needing that moisture proof environment and then shall be placed in the survival kit for use at such time as needed.

*6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

(a) Title, number and date of this specification.

(b) List of interchangeable components and assemblies.

(c) Levels of preservation-packaging and packing (see 5.1).

6.3 Data. For the information of contractors and contracting officers, any of the data specified in the applicable documents listed in Section 2 of this specification or referenced lower-tier documents need not be prepared for the Government and shall not be furnished to the Government unless specified in the contract or order. The data to be furnished shall be listed on DD Form 1423 (Contractor Data Requirements List), which shall be attached to and made a part of the contract or order.

6.4 Changes from previous issue. The margins of this specification are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian
Air Force - 99

Preparing Activity
Air Force - 82

(Project No. 1660-F470)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:51Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-C-83864A	2. DOCUMENT DATE *(YYMMDD)*

3. DOCUMENT TITLE
CONTAINER, INNER, SURVIVAL KIT

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME *(Last, First, Middle Initial)*	b. ORGANIZATION	
c. ADDRESS *(Include Zip Code)*	d. TELEPHONE *(Include Area Code)* (1) Commercial (2) AUTOVON *(If applicable)*	7. DATE SUBMITTED *(YYMMDD)*

8. PREPARING ACTIVITY

a. NAME SA-ALC/TIRDM ATTN: ESTER BADILLO	b. TELEPHONE *(Include Area Code)* (1) Commercial (2) AUTOVON
c. ADDRESS *(Include Zip Code)* Kelly AFB TX 78241-5000	**IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:** Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil - Downloaded: 2023-10-23T00:51Z
Check the source to verify that this is the current version before use.