MILITARY SPECIFICATION

FIN M27

This specification is approved for use by the US Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification contains requirements and provides quality assurance provisions for the fabrication of the M27 Fin.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-H-6088	-	Heat Treatment of Aluminum Alloys
MIL-A-48078	-	Ammunition, Standard Quality Assurance Provisions, General Specification for

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1167	-	Ammunition Data Card

DRAWINGS (See 6.9)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

FSC: 1310

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:32Z
Check the source to verify that this is the current version before use.

F11751196 - Fin, M27
C9287835 - Packing and Marking for Box, Fiberboard, for Fin M27

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitations for bids or request for proposal shall apply.

ANSI-846.1 - Surface Texture

(Applications for copies should be addressed to the American National Standards Institute (ANSI), 1430 Broadway, New York, NY 10018).

ASTM Method E-8 - Tension Testing of Metallic Materials
ASTM Method E-340 - Macroetching Metals and Alloys

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal Agencies.

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings and specifications.

3.2 Components and assemblies. The components and assemblies shall comply with all requirements specified on drawing 11751196 and associated drawings and with all requirements specified in applicable specifications and standards.

3.3 Mechanical properties. Mechanical properties shall be in accordance with the requirements of the applicable drawings and specifications.

3.4 Heat treatment. Heat treatment equipment, procedures and controls shall be in accordance with MIL-H-6088. The extrusion stock shall be solution heat treated in such a manner as to avoid overheating of the material or cracking during quenching.

3.5 Data requirements. The contractor shall generate data in accordance with the requirements of the data item descriptions cited in 4.5.4.2 and 4.5.5. Ammunition data cards are required (see section 6). All data cards shall list drawings and revisions for components and assemblies.

Source: https://assist.dla.mil -- Downloaded: 202640-22T19:32Z
Check the source to verify that this is the currentversion before use.

3.6 First Article Inspection. This specification makes provisions for first article inspection. Requirements for submission of first article samples by the contractor shall be as specified in the contract.

3.7 Workmanship. The requirements for workmanship are as shown on the applicable drawing, referenced specification and the following:

3.7.1 Metal defective. Soundness of the material shall be as required by the applicable material specifications. Fins shall be homogeneous and free from cracks, laminations, porosity, pipe type or other deleterious defects.

3.7.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required by the applicable drawings.

3.7.3 Burr. No part shall have a burr which might adversely affect the assembly or function of the round or which might be injurous to personnel handling the item.

3.7.4 Foreign matter. All parts shall be free of chips, dirt, grease, rust, corrosion or other foreign matter.

4. QUALITY ASSURANCE PROVISONS

4.1 Responsibility for Inspection and Standard Quality Assurance Provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of Inspections. The following types of inspection shall be conducted on this item:

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First Article Inspection

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Following nominal cropping, one full cross-sectional specimen suitable for macroetch shall be selected from the front and rear of each extrusion bar.

10 Fins completely machined including flash holes
10 Fins completely machined less the flash holes

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:32Z
Check the source to verify that this is the currentversion before use.

2 Flat tensile specimens
2 Round tensile specimens
2 Microstructure specimens

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:32Z
Check the source to verify that this is the current version before use.

FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48580B (AR)

PARAGRAPH	TITLE		SHEET		DRAWING NUMBER
	Fins and Extrusion Stock		1 OF 1		See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Extrusion Bar (front and rear blank)				
	Macroetch Test	2		3.7.1	4.5.3
	Extrusion Blanks				
	Tension Test	4		3.1	4.5.4/6.5
	Microstructure examination	2		3.4	4.5.4.1/6.4
	Fin, Prior to Drilling Flash Holes				
	Hydro Test	10		3.2	4.5.5
	Fin (dwg. 11751196)				
	Examination for defects	10		3.2	4.4.2.4

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:32Z
Check the source to verify that this is the current version before use.

4.4 Quality Conformance Inspection

4.4.1 Inspection Lot Formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, the extrusion lot shall consist of not more than 2000 pounds of extruded stock of the same alloy that has been thermally treated by the same method in the same furnace equipment at the same temperature and time in one unchanged process regardless of the solution heat treating method utilized. Each extrusion lot representing material that has been solution heat treated after extrusion, must be solution heat treated at the same time in the same furnace using the same temperature and time in that furnace. The extrusion lot thus constituted shall be the basis for selecting the sample blanks for the microstructure and tension tests herein after prescribed.

4.4.2 Examination. See MIL-A-48078.

a. Sampling Plans. Unless otherwise specified in the Classification of Defects and Test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

b. Control tool manufacture. For dimensions marked control tool manufacture, select and gage one fin from each machine in operation every two hours or fraction thereof, and whenever tooling is changed. Prior to any tooling change the last fin produced from the old tooling shall be gaged for the requirements of the applicable drawing. All material produced prior to all periodic inspection shall be rejected and screened whenever a defective characteristic is found and corrective action shall be taken.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48580B (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Extrusion Bar				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Special					
a.	Macroetch test		100%	3.7.1	4.5.3
Major	None defined				
Minor	None defined				

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48580B (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Extrusion Blanks (following final heat treatment)				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Special					
a.	Tension test	4	(a)	3.1	4.5.4/6.5
b.	Microstructure examination	2		3.4	4.5.4.1/6.4
Major	None defined				
Minor	None defined				

NOTES: (a) See para. 4.4.1.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48580B (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Fin, Prior to Drilling Flash Holes	1 OF 1	11751196
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	Hydro test		100%	3.2	4.5.5
Major	None defined				
Minor	None defined				

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARFA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48580B (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Fin	1 OF 3	11751196
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Flash hole(s) missing		100%	3.2	4.5.2.1
2	Hydrostatic test stamp missing		100%	3.2	4.5.5
Special					
a.	Forward thread minor dia., maximum		100%	3.2	Gage
b.	Presence of burr or foreign matter in ignition cartridge cavity or any flash hole		100%	3.7.3/ 3.7.4	Visual
c.	Metal defective		100%	3.7.1	Visual
Major					
101	Runout of forward outside dia. with pitch dia. of forward thread and front face		0.40%	3.2	Gage
102	Runout of pitch dia. of ignition cartridge thread with pitch diameter of forward thread and front and rear faces		0.40%	3.2	Gage
103	Runout of outside dia. of fin blades with pitch dia. of forward thread and front face		0.40%	3.2	Gage
104	Horizontal T.I.R. of fin blades after canting blades to P.D. of forward thread and front face		0.40%	3.2	Gage
105	Vertical T.I.R. of fin blades after canting blades to P.D. of forward thread and front face		0.40%	3.2	Gage
106	True position of ignition cartridge cavity with pitch dia. of ignition cartridge thread for min. length		0.40%	3.2	Gage
107	Pitch dia. of forward thread, max.		0.40%	3.2	Gage
108	Pitch dia. of forward thread, min.		0.40%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 20260-22T19:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48580B (AR)

PARAGRAPH	TITLE		SHEET 2 OF 3		DRAWING NUMBER
4.4.2.4	Fin				11751196
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
109	Pitch dia. of ignition cartridge thread, max.		0.40%	3.2	Gage
110	Pitch dia. of ignition cartridge thread, min.		0.40%	3.2	Gage
111	Minor dia. of ignition cartridge thread, max.		0.40%	3.2	Gage
112	Diameter of ignition cartridge cavity		0.40%	3.2	Gage
113	Diameter of hub		0.40%	3.2	Gage
114	Dia. of fin blade counterbore at rear of fin		0.40%	3.2	Gage
115	Diameter of fin blades (large)		0.40%	3.2	Gage
116	Diameter of fin blades (small)		0.40%	3.2	Gage
117	Depth of ignition cartridge cavity		0.40%	3.2	Gage
118	Depth to bottom of forward thread cavity		0.40%	3.2	Gage
119	Depth of fin blade counterbore at rear of fin		0.40%	3.2	Gage
120	Length of forward thread, min.		0.40%	3.2	Gage
121	Length of ignition cartridge thread, min.		0.40%	3.2	Gage
122	Length of flat at largest dia. of fin blades		0.40%	3.2	Gage
123	Length of fin blade, total		0.40%	3.2	Gage
124	Length, total		0.40%	3.2	Gage
125	Location of basic dia. on forward edge of fin blade		0.40%	3.2	Gage
126	Height of cant, fin blade		0.40%	3.2	Gage
127	Fin blade(s) distorted or damaged		0.40%	3.2	Visual
128	Fin blade(s) canted in improper direction		0.40%	3.2	Visual
129	Thread(s) damaged or not full		0.40%	3.7.2	Visual
130	Flash holes excessive in number		0.40%	3.2	4.5.2.2
Minor					
201	Dia. of hub between fin blades, max.		0.65%	3.2	Gage
202	Dia. of forward thread counterbore		0.65%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:32Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 3 OF 3		DRAWING NUMBER
4.4.2.4	Fin				11751196
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
203	Depth of forward thread counterbore		0.65%	3.2	Gage
204	Depth of ignition cartridge thread, max.		0.65%	3.2	Gage
205	Angle between fin blades		0.65%	3.2	Gage
206	Thickness of fin blades		0.65%	3.2	Gage
207	Radii or chamfers missing or incorrect		0.65%	3.2	Visual (see 6.6)
208	Surface finish improper		0.65%	3.2	Visual (see 6.7)
209	Presence of burr		0.65%	3.7.3	Visual
210	Foreign matter		0.65%	3.7.4	Visual
211	Marking missing, incorrect or illegible		0.65%	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 20260-22T19:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48580B (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Box, Fiberboard Prior to Sealing				9287835
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Tray missing or damaged		0.65%	3.1	Visual
202	Improperly packed		0.65%	3.1	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48580B (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Box, Fiberboard After Sealing				9287835
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Contents loose		0.65%	3.1	Manual
202	Box damaged (cut or damaged through all layers)		0.65%	3.1	Visual
203	Box not properly sealed		0.65%	3.1	Visual
204	Marking missing, incorrect or illegible		0.65%	3.1	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:32Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed in this specification is identified either directly or by reference, in the "Paragraph Reference/Inspection Method" column of the Quality Conformance Inspection Tables herein. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Methods of Inspection

4.5.1 Materials, Components and Processes. Compliance with all requirements of Section 3 of this specification shall be ascertained by current and continuing examination of inspection and test data to determine that all components (parts, subassemblies, and materials) have been inspected and tested and found to comply with their respective drawing and specification requirements, and that all specified manufacturing processes have been followed.

4.5.1.1 Visual and Mechanical Inspections. The visual, manual and mechanical inspections and tests shall verify compliance with the requirements of Sections 3 and 5 of this specification in accordance with 4.4.2 herein and Table I.

4.5.2 Flash hole inspection

4.5.2.1 Missing flash holes. Each fin shall be inspected by an electronic and/or mechanical system capable of determining the presence of the required number of flash holes (see drawing).

4.5.2.2 Excessive flash holes. The sample fins shall be visually inspected for the presence of flash holes in excess of the drawing requirement.

4.5.3 Macroetch test. Following nominal cropping full cross section macroetch specimens from the front and back of each individual extrusion billet shall be examined. Failure to comply with the requirements of 3.7.1 will require an additional length of discard from the defective extrusion end(s) and testing of additional macroetch specimen(s) from the defective end(s) of the remaining length of extruded material. This procedure must be continued until a sufficient length of the defective extrusion has been discarded and the requirements of 3.7.1 are met. Suitable identification of each length of extrusion and corresponding macroetch must be maintained until the extruded material is accepted. The specimens shall be macroetched using the criteria prescribed in ASTM Method E-340 except that sodium hydroxide shall be used as the macroetching reagent.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:32Z
Check the source to verify that this is the current version before use.

4.5.4 Tension test. Four specimens total shall be taken from each extrusion lot (as defined by 4.4.1). For press-quench production, two specimens (one round and one flat) shall be taken from both the front and rear of each extrusion lot representing the first and last material respectively which has been extruded and is in accordance with the provisions of 4.4.1. For solution heat treatment following extrusion, two specimens (one round and one flat) shall be chosen from both the hottest and coldest zones of the furnace.

The flat tensile specimens shall be the largest flat-type specimens obtainable from the blade area, and the remaining two specimens shall be the largest round-type specimens obtainable from the housing portion.

Specimens shall be taken longitudinally. Failure of any tension test specimen to comply with the yield strength or elongation requirements of the applicable drawing shall be cause for rejection of the lot. The test criteria for all four tensile specimens shall be as prescribed by ASTM Method E-8. The number of specimens and their location is to determine the acceptability of the mechanical property requirements. The Government shall not be restricted from testing additional specimens at any location to determine that the mechanical properties meet the drawing requirements for yield strength and elongation.

4.5.4.1 Microstructure examination. From each of the flat samples submitted for tension testing, one wafer approximately 1/2 inch square shall be prepared for metallographic examination from an undeformed portion of the specimen. When suitably prepared, the specimen shall be etched with Keller's reagent and examined by scanning under a metallurgical microscope at a minimum magnification of 500 diameters. Overheating shall be evidenced by the presence of rosettes in the microstructure or incipient melting at the grain boundaries (see 6.4). Evidence of the above shall cause rejection of the extrusion lot.

4.5.4.2 Quality inspection report. The contractor shall submit a quality inspection test, demonstration and evaluation report in accordance with Data Item Description DI-R-1724 giving detailed test results of data generated in accordance with paragraphs 4.5.4 and 4.5.5.

4.5.5 Hydrostatic Test. After final machining, but prior to drilling flash holes and prior to gaging, each fin shall be subjected to a hydrostatic test to determine compliance with the requirements of the drawing. Rupture, cracking, or bulging shall be evidence of fin failure and cause for rejection of the fin. The fin shall be hydrostatically tested using the equipment capable of performing the test accurately and consistently. In performing the test, the pressure will be applied until the required minimum pressure is reached and held for the required time. The equipment shall be calibrated prior to the start of each day's operation and at intervals of not over 4 hours of continuous operation. It shall also be calibrated prior to restarting the operation after a lay-off of three hours or more. If it has been found that the equipment is out of calibration in such a direction that the pressure was actually lower than required by the applicable drawing, the fins tested since the

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:32Z
Check the source to verify that this is the current version before use.

last satisfactory calibration shall be retested after the calibration error has been corrected. Each fin that successfully passes the test shall be stamped in accordance with the drawing. The contractor shall submit a monthly quality defect report in accordance with Data Item Description DI-R-1721 summarizing the number and type of defects found and pressure at rupture.

5. PACKAGING

5.1 Packaging requirements. Packaging shall be as specified on Dwg. 9287835.

5.2 Packing and marking. Packing and marking shall be as specified on Dwg. 9287835.

6. NOTES

6.1 Intended Use. The components covered by this specification are intended for use on the cartridge 60MM HE, M720. This is a pressure vessel application.

6.2 Ordering Data. See MIL-A-48078.

6.3 Submission of Inspection Equipment For Design Approval. See MIL-A-48078. Submit designs as required, to Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAT-I, Dover, New Jersey 07801.

6.4 Microstructure examination. Microstructure examination of solution heat treat specimens should be performed by a skilled metallographer familiar with aluminum alloys.

6.5 Alternative sample selection. An alternative method of defining an extrusion lot for the purposes of selection of samples for tension or microstructure examination will be considered. Proposed alternatives shall be submitted thru the PCO to the Cognizant Government Technical Agency for approval prior to implementation.

6.6 Visual examination qualifications. When compliance with the applicable requirements is in doubt as a result of visual examination, this characteristic may be measured or gaged to determine acceptability.

6.7 Surface roughness. The roughness comparison specimens prescribed by ANSI-B46.1 shall be used as a basis for surface roughness determination. Four power (4X) magnification may be used in performing visual examination.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:32Z
Check the source to verify that this is the current version before use.

6.8 Data requirements. Deliverable data required by this specification are cited in the following paragraphs:

Paragraph	Data Requirement	Applicable DID
3.5	Ammunition Data Card	DI-L-1410
4.5.4.2	Quality Inspection Test Demonstration and Evaluation Report	DI-R-1724
4.5.5	Quality Inspection Defect Report	DI-R-1721

(Copies of data item descriptions required by the contractors in connection with specific procurement functions should be obtained from the procuring activity, or as directed by the contracting officer). Direct submissions to Commander, US Army Research and Development Command, ATTN: DRDAR-QAT-A, Dover, NJ 07801.

6.9 Drawing. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

6.10 Changes from Previous Issue.- Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing Activity:
Army-AR

☆U.S. GOVERNMENT PRINTING OFFICE: 1981—703-023/5302

Project Number: 1310-A-262

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:32Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-F-48580B FIN M27

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 202640-22T19:32Z
Check the source to verify that this is the current version before use.