MIL-E-48622A(AR)
17 April 1980
Superseding
MIL-E-48622 (AR)
19 October 1979

MILITARY SPECIFICATION

EXTRACTOR FOR 155MM GUIDED PROJECTILE, M712 AND TRAINING PROJECTILE M823

This specification is approved for use by the US Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification contains requirements not covered by the drawings and provides quality assurance provisions for the fabrication of parts, assembly and packing of an extractor for the 155MM Guided Projectile, M712 and Training Projectile, M823.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078 -Ammunition, Standard Quality Assurance Provisions, General Specification for

DRAWINGS

U.S. Army Armament Research and Development Command

9305465 -Extractor Tool Assembly

9308015 -Aft Closure-Machining

FSC: 1320

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:35Z
Check the source to verify that this is the current version before use.

9331729 -Box, Packing, For Extractor Tool for Projectile 155MM, M712, & M823, P&M

9331769 -Base

3. REQUIREMENTS

3.1 Materials - Materials shall be in accordance with the applicable drawings and specifications.

3.2 Components and Assemblies - The components and assemblies shall comply with all requirements specified on drawing 9305465 and associated drawings and with all requirements specified in applicable specifications and standards.

3.2.1 Expansion Ring -The expansion ring (dwg. 9305470) shall close from the unrestrained to the restrained position (as shown on dwg. 9305465) when subjected to a tangential force of 10 pounds, maximum (max).

3.2.2 Assembly - All components and assemblies shall be capable of being assembled in both the operational and the stowed configuration as shown on dwg. 9305465 without binding, sticking, or jamming.

3.3 Strength - The assembled extractor (9305465) shall be capable of withstanding an applied axial force of 15000 pounds (lbs), minimum (min).

3.4 First Article Inspection This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.5 Workmanship The components and assemblies shall be free from chips, burrs, grease, dirt, gouges, rust, cracks, porosity or any other defects which would make the item unsuitable for the intended use. The cleaning method used shall not be injurious to any of the parts, nor shall the parts be contaminated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:35Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 *Responsibility for Inspection and Standard Quality Assurance Provisions* Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of Inspections The following types of inspection shall be conducted on this item:

a. First Article Inspection
b. Quality Conformance Inspection

4.3 First Article Inspection

4.3.1 Submission The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawing	Quantity
Strap Assembly	9305474	3
Ring, Support	9305473	3
Ring, Retaining	9305469	3
Ring, Expansion	9305470	3
Fitting Assembly	9305472	3
Extractor Tool Assembly	9305465	3
Support, Alignment	9340541	3

4.3.2 Inspections to be Performed Examination shall be in accordance with MIL-A-48078. The first article sample submitted in accordance with paragraph 4.3.1 shall be subjected to the following tests and inspections.

4.3.2.1 Extractor Tool Assembly (dwg. 9305465) The extractor tool assembly shall be subjected to the appropriate tests and then the following parts removed and inspected per Table I in lieu of submitting additional hardware.

Block Guide	9305429	3
Brace Extractor	9305431	3
Nut, Drive	9305467	3
Rod, Threaded	9305471	3
Ratchet Drive	9300464	3

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:35Z
Check the source to verify that this is the current version before use.

4.3.2.2 The parts submitted in accordance with 4.3.1 and 4.3.2.1 shall be subjected to all of the tests and inspections in Table I.

4.3.3 Rejection See MIL-A-48078

4.4 Quality Conformance Inspection

4.4.1 Inspection Lot Formation Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination See MIL-A-48078

a. Sampling Plans - Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 202640-22T19:35Z
Check the source to verify that this is the currentversion before use.

TABLE I FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-E-48622A (AR)

PARAGRAPH	TITLE		SHEET OF		DRAWING NUMBER
	Extractor				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Ratchet Drive (Dwg 9300464)	3		3.2	4.4.2.1
	Block, Guide (Dwg 9305429)	3		3.2	4.4.2.2
	Brace-Extractor (Dwg 9305431)	3		3.2	4.4.2.3
	Nut Drive (Dwg 9305467)	3		3.2	4.4.2.4
	Ring Assembly, Retaining (Dwg. 9305469)	3		3.2	4.4.2.5
	Ring Expansion (Dwg 9305470)	3		3.2	4.4.2.6
	Rod Threaded (Dwg 9305471)	3		3.2	4.4.2.7
	Fitting Assembly (Dwg 9305472)	3		3.2	4.4.2.8
	Ring Support (Dwg 9305473)	3		3.2	4.4.2.9
	Strap Assembly (Dwg 9305474)	3		3.2	4.4.2.10
	Extractor Tool Assembly (Dwg 9305465)	3		3.2	4.4.2.12
	Support Alignment (Dwg 9340541)	3		3.2	4.4.2.11

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:35Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-E-48622A (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.1	Ratchet, Drive		9300464
			NEXT HIGHER ASSEMBLY 9305465

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR	None defined				
MINOR					
201	Knurl missing or improper		0.65%	3.2	Visual
202	Protective finish incorrect		0.65%	3.2	Visual
203	Pin not removed		0.65%	3.2	Visual
204	Total Length		0.65%	3.2	Gage
205	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026/10-22T19:35Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-E-48622A (AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.2	Block, Guide	1	1	9305429
				NEXT HIGHER ASSEMBLY 9305465

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Location of screw hole		0.40%	3.2	Gage
102	Width from axial radius surface to flat surface (max)		0.40%	3.2	Gage
MINOR					
201	Counterbore missing or obviously incorrect		0.65%	3.2	Visual
202	Protective finish incorrect		0.65%	3.2	Visual
203	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:35Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-E-48622A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9305431
4.4.2.3	Brace, Extractor				NEXT HIGHER ASSEMBLY 9305465
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Total Length		0.40%	3.2	Gage
102	Location of large hole along length		0.40%	3.2	Gage
103	Pin clearance in hole		0.40%	3.2	Gage
104	Location of large hole along width		0.40%	3.2	Gage
MINOR					
201	Large hole diameter		0.65%	3.2	Gage
202	Protective finish incorrect		0.65%	3.2	Visual
203	Loose or missing pins		0.65%	3.2	Visual
204	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 20240-22T19:35Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-E-48622 A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9305467
4.4.2.4	Nut, Drive				NEXT HIGHER ASSEMBLY 9305465
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Pitch diameter of thread		0.40%	3.2	Gage
102	Minor diameter of thread, max.		0.40%	3.2	Gage
103	Length of thread		0.40%	3.2	Gage
104	Width of squared hole		0.40%	3.2	Gage
MINOR					
201	Length		0.65%	3.2	Gage
202	Outside diameter		0.65%	3.2	Gage
203	Diameter of cross hole		0.65%	3.2	Gage
204	True position of square hole		0.65%	3.2	Gage
205	Location of cross hole		0.65%	3.2	Gage
206	Protective finish incorrect		0.65%	3.2	Visual
207	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:35Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-E-48622A (AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.5	Ring Assembly, Retaining	1	1	9305469
				NEXT HIGHER ASSEMBLY 9305465

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Inside diameter		0.40%	3.2	Gage
102	Outside diameter (Unrestrained)		0.40%	3.2	Gage
103	Position of pads		0.40%	3.2	Gage
104	Pad welds incorrect		0.40%	3.2	Visual
MINOR					
201	Chamfer on inside diameter missing		0.65%	3.2	Visual
202	Protective finish incorrect		0.65%	3.2	Visual
203	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:35Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-E-48622A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9305470
4.4.2.6	Ring Expansion				NEXT HIGHER ASSEMBLY 9305465
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Unrestrained outside diameter		0.40%	3.2	Gage
102	Length of long side of ring tooth		0.40%	3.2	Gage
103	Thickness of short side of ring tooth		0.40%	3.2	Gage
104	Length of short side of ring tooth		0.40%	3.2	Gage
105	Distance from tab to short side of ring tooth		0.40%	3.2	Gage
106	Compressive spring force		0.40%	3.2.1	Test/4.5.2
107	Tab welds incorrect		0.40%	3.2	Visual
108	Hardness		0.40%	3.2	Gage
MINOR					
201	Tab length		0.65%	3.2	Gage
202	Tab width		0.65%	3.2	Gage
203	Tab thickness		0.65%	3.2	Gage
204	Ring web width		0.65%	3.2	Gage
205	Ring thickness		0.65%	3.2	Gage
206	Angle of Bevel on short side of ring tooth		0.65%	3.2	Gage
207	Protective finish incorrect		0.65%	3.2	Visual
208	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 20240-22T19:35Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-E-48622A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9305471
4.4.2.7	Rod, Threaded				NEXT HIGHER ASSEMBLY 9305465
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Length of thread		0.40%	3.2	Gage
102	Pitch diameter of thread		0.40%	3.2	Gage
103	Major diameter of thread, min.		0.40%	3.2	Gage
104	Outside diameter of rod		0.40%	3.2	Gage
105	Profile of groove		0.40%	3.2	Gage
106	Hardness		0.40%	3.2	Gage
MINOR					
201	Diameter of hole		0.65%	3.2	Gage
202	Location of hole		0.65%	3.2	Gage
203	Length of rod		0.65%	3.2	Gage
204	Length of groove		0.65%	3.2	Gage
205	V-notch profile		0.65%	3.2	Gage
206	Protective finish incorrect		0.65%	3.2	Visual
207	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:35Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-E-48622A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9305472
4.4.2.8	Fitting Assembly, Extractor				NEXT HIGHER ASSEMBLY 9305465
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Outside diameter of flange		0.40%	3.2	Gage
102	Outside diameter of expansion ring groove		0.40%	3.2	Gage
103	Inside diameter of fitting cap		0.40%	3.2	Gage
104	Pitch diameter of thread		0.40%	3.2	Gage
105	Major diameter of thread		0.40%	3.2	Gage
106	Length of thread		0.40%	3.2	Gage
107	Perpendicularity of tube to fitting		0.40%	3.2	Gage
108	Weld incorrect		0.40%	3.2	Gage
MINOR					
201	Diameter of small hole		0.65%	3.2	Gage
202	Location of small hole		0.65%	3.2	Gage
203	Diameter of large hole		0.65%	3.2	Gage
204	Location of large hole		0.65%	3.2	Gage
205	Pitch diameter of threaded hole		0.65%	3.2	Gage
206	Minor diameter of threaded hole		0.65%	3.2	Gage
207	Protective finish incorrect		0.65%	3.2	Visual
208	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:35Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-E-48622A (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.9	Ring, Support		9305473
			NEXT HIGHER ASSEMBLY 9305465

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Pitch diameter of threaded hole		0.40%	3.2	Gage
102	Minor diameter of threaded hole		0.40%	3.2	Gage
103	Pitch diameter of ring thread		0.40%	3.2	Gage
104	Minor diameter of ring thread		0.40%	3.2	Gage
105	Thickness of ring		0.40%	3.2	Gage
MINOR					
201	Location of threaded hole		0.65%	3.2	Gage
202	Location of slot		0.65%	3.2	Gage
203	Width of slot		0.65%	3.2	Gage
204	Outside diameter		0.65%	3.2	Gage
205	Protective finish incorrect		0.65%	3.2	Visual
206	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:35Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-E-48622A (AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.10	Strap Assembly, Retainer	1	1	9305474
				NEXT HIGHER ASSEMBLY 9305465

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR	None defined				
MINOR					
201	Hole inside diameter		0.65%	3.2	Gage
202	Length of short side of tape		0.65%	3.2	Gage
203	Length of long side of tape		0.65%	3.2	Gage
204	Stitching incorrect		0.65%	3.2	Visual
205	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:35Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-E-48622A (AR)

PARAGRAPH	TITLE		SHEET	DRAWING NUMBER
4.4.2.11	Support Alignment		1 OF 1	9340541
				NEXT HIGHER ASSEMBLY 9305465

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Outside diameter		0.40%	3.2	Gage
102	Slot or chamfers missing or obviously improper		0.40%	3.2	Gage
MINOR					
201	Inside diameter		0.65%	3.2	Gage
202	Thickness		0.65%	3.2	Gage
203	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:35Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-E-48622A (AR)

PARAGRAPH	TITLE		SHEET	OF	DRAWING NUMBER
4.4.2.12	Extractor Tool Assembly		1	1	9305465
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Tensile strength of assembly		100%	3.3	Test/4.5.1
102	Operational assembly incorrect		0.40%	3.2.2	Manual/Visual
MINOR					
201	Bonding incorrect		0.65%	3.2	Visual
202	Stowed assembly incorrect		0.65%	3.2.2	Visual
203	Sealant missing		0.65%	3.2	Visual
204	Marking incorrect		0.65%	3.2	Visual
205	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:35Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-E-48622A (AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.13	Box, Packing, For Extractor Tool Assembly	1	1	9331729
				NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR	None defined				
MINOR					
201	Fastner loose		0.65%	3.2	Visual
202	Board split		0.65%	3.2	Visual
203	Component missing		0.65%	3.2	Visual
204	Marking incorrect		0.65%	3.2	Visual
205	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:35Z
Check the source to verify that this is the current version before use.

4.4.3 Testing Testing is described in the First Article and Quality Conformance Inspection Tables.

4.4.4 Inspecton Equipment The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See section 6 of MIL-A-48078.

4.5 Test Methods and Procedures Assembled Extractor

4.5.1 Strength Test - The axial force specified in 3.3 shall be applied to the extractor by simulating its normal usage. The extractor shall be assembled to a test fixture designed to hold the front end by simulating an aft closure per dwgs 9308015 (M712) or 9331769 (M823) and supporting the other end on the brace outside of an eleven inch diameter circle. The axial load shall be applied by torqueing the system using the drive ratchet. The system shall be tested at each of its extended lengths. Failure to meet the specified requirements shall be cause to reject the unit.

4.5.2 Expansion Ring Operational Test The expansion ring (dwg. 9305470) shall be placed in a simulated assembly position and a force applied to the ring tabs to close the ring from the unrestrained to the restrained (closed) position. Failure to meet the specified requirements shall reject the ring lot.

5. PACKAGING

5.1 Packing, Packaging and Marking - Packing, packaging and marking of the extractor shall be in accordance with dwg. 9331729.

6. NOTES

6.1 Intended Use - The components covered by this specification are intended for use with the 155MM guided projectile, M712 and Training Projectile, M823.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:35Z
Check the source to verify that this is the current version before use.

6.2 Ordering Data - See MIL-A-48078.

6.3 Submission of Inspection Equipment for Design Approvals - See MIL-A-48078. Submit designs as required to: Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAR-I, Dover, N.J. 07801.

CUSTODIAN:
ARMY-AR

PREPARING ACTIVITY
ARMY-AR

Project Number: 1320-A527

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:35Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE MIL-E-48622A

Extractor for 155MM Guided Projectile, M712 and Training Projectile

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER M823

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:35Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

U.S. MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Armament R&D Command
ATTN: DRDAR-QAR
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:35Z
Check the source to verify that this is the current version before use.