MIL-I-60522(MU)
11 August 1969
SUPERSEDING
FA-PD-MI-2227,Rev.1
20 September 1957

MILITARY SPECIFICATION
INITIATOR, CARTRIDGE ACTUATED: M5A2
METAL PARTS ASSEMBLIES

1. SCOPE

1.1 This specification covers Initiator, Cartridge Actuated: M5A2, Metal Parts Assembly. The assembly will ultimately be loaded and used in conjunction with other propellant actuated devices in aircrew emergency escape systems.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-A-2550	- Ammunition and Special Weapons, General Specification for

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	- Quality Assurance Terms and Definitions
MIL-STD-413	- Visual Inspection Guide for Rubber O-Rings
MIL-STD-1167	- Ammunition Data Card

DRAWINGS

Munitions Command

F8596171	- Initiator, Cartridge Actuated, M5A2, Metal Parts Assembly
C8796541	- Container, Ammunition, Fiber, M376 for Initiator, Cartridge Actuated, M3A1, M3A1C or M5A2 with Cartridge, M73

FSC 1377

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

C8796542 - Box, Packing, Ammunition for Initiator, Cartridge Actuated, M3A1 or M5A2 with Cartridge M73 in Fiber Container, M376

IEL 8596171 - Inspection Equipment List for Initiator, Cartridge Actuated, M5A2, Metal Parts Assembly

(Copies of specifications, standards and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications.- The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bid or request for proposal shall apply:

ASA B46.1 - Surface Texture

(Application for copies should be addressed to the American Standards Association, 10 East 40th Street, New York, N.Y. 10016).

3. REQUIREMENTS

3.1 General.- Materials, parts and assemblies shall conform to the applicable drawings and referenced specifications.

3.2 Mechanical properties.- Mechanical properties required by the drawings shall be uniform throughout each part. Requirements for all alloy steel parts shall be achieved by quenching and tempering.

3.3 Hydrostatic pressure.- The initiator chamber and cap shall withstand an internal pressure of 5500 to 6500 pounds per square inch (PSI) for 15 seconds, minimum, without deformation or mechanical failure (See 6.2).

3.4 Shear pin strength.- After application of protective finish the shear pin shall sheer when a load of 41 $\pm$ 5 lbs is applied at the steady rate of 0.125 inches per minute.

3.5 Protective finish.- Protective finish shall be in accordance with the applicable specification and drawing and shall apply to all surfaces regardless of contour.

3.6 Residual magnetism.- The metal parts assembly shall not deflect the indicator of the compass more than 3 degrees in either direction when passed in front of the compass at a distance of 6 inches.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

3.7 Workmanship.- Workmanship shall be in accordance with the requirements of the applicable drawings and referenced specifications and the following:

3.7.1 Metal defects.- The component shall be free from cracks, splits, cold shuts, inclusions, porosity, or other metal defects.

3.7.2 Burr.- The part shall not have a burr which might interfere with the assembly or function of the item, or which might be injurious to personnel handling the item.

3.7.3 Foreign matter.- The part or assembly shall not contain chips, dirt, grease, rust, corrosion or other foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure aupplies and services conform to prescribed requirements.

4.1.1 Quality assurance terms and definitions.- Reference shall be made to MIL-STD-109 to define quality assurance terms used.

4.1.2 Inspection.- Inspection shall be in accordance with MIL-A-2550.

4.2 First article sample.

4.2.1 Initial production sample.- At the beginning of regular production, a sample shall be submitted in accordance with contract requirements and shall consist of 50 units of each heat-treated lot of components for hardness tests, 50 shear pins for shear pin test and the specified number of samples as indicated in the appropriate specification for protective finish tests to be tested in accordance with Table I, and 5 assemblies and 10 sets of unassembled components for visual and dimensional examination:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

TABLE I

Paragraphs Requirements	Test	Test	Sample Size	Type of Test Dest	Non-Destr
3.2	4.4.1	Hardness	50	X	-
3.3	4.4.2	Hydrostatic Pressure	Each	-	X
3.4	4.4.3	Shear Pin Strength	50	X	-
3.5	4.4.4	Protective Finish	(As specified in app. spec)	X	-
3.6	4.4.5	Residual Magnetism	Each	-	X

The sample shall be manufactured using the same materials, equipment, process and procedures as used in regular production. All parts and materials, including packaging and packing shall be the same as used for regular production and shall be obtained from the same source of supply.

4.2.1.1 Examination and tests.- After examination and provisional acceptance at source, the sample shall be inspected for all requirements of the drawings and specifications at a government laboratory or such other facility specified in the contract.

4.2.1.2 Initial production sample failure.- Failure of the sample to comply with the requirements of the drawings and specifications shall result in sample disapproval.

4.3 Inspection provisions.

4.3.1 Lot.

4.3.1.1 Submission of product.- The product shall be submitted in accordance with MIL-STD-105.

4.3.1.2 Size of lot.- A lot of metal parts assemblies shall consist of an identifiable group of metal parts produced by a homogeneous process.

4.3.2 Examination.- One hundred percent examination shall be performed on a defect basis in accordance with the classification of defects contained herein, using the sampling plan and associated criteria in tables II and III. For an individual defect (single characteristic) the criteria in table II shall be used. For total defects within a major or minor class, the criteria in table III shall be used. All non-conforming material shall be rejected. The roughness comparison specimens prescribed in ASA B46.1 shall be used as a basis of comparison for surface roughness determination. Four power (4X) magnification may be used in performing visual examination for such defects as burr and foreign matter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

Table II

Lot Size	Sample Size	Major Accept	Major Reject	Minor Accept	Minor Reject
1 - 300	100% Examination	-	-	-	-
301 - 1300	110	1	2	2	3
1301 - 3200	150	2	3	3	4
3201 - 8000	225	3	4	4	5
8001 - 22000	300	4	5	5	6

Table III

Sample Size for Major Defects Number of defects in class	Total Allowable Defects Per Sample Size 110	150	225	300
2 - 3	1	2	3	4
4 - 7	2	3	4	5
8 - 19	3	4	5	7
20 - 43	4	5	8	10
over 43	6	8	11	14

Sample Size for Minor Defects Number of defects in class	Total Allowable Defects Per Sample Size 110	150	225	300
2 - 3	2	3	4	5
4 - 7	3	4	5	7
8 - 16	4	5	8	10
17 - 48	6	8	11	14
over 48	8	11	17	20

4.3.2.1 Housing, Firing Pin, Drawing D8593012, covering a detail of Drawing D8596171.

Defect	Method of Inspection
CRITICAL	
1. Metal defect	Visual
MAJOR	
101. Pitch diameter of internal thread, max.	Gage
102. Minor diameter of internal thread, max.	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

4.3.2.1 (Cont'd)

Defect	Method of Inspection
MAJOR (Cont'd)	
103. Pitch diameter of external thread, min.	Gage
104. Major diameter of external thread, min.	Gage
105. Concentricity of pitch diameter of internal thread with cavity	Gage
106. Concentricity of groove with flange	Gage
107. Concentricity of boss cavity with cavity	Gage
108. Concentricity of pitch diameter of external thread with cavity	Gage
109. Concentricity of cavity with flange	Gage
110. Concentricity of striker hole with cavity	Gage
111. Concentricity of body, flange end, with cavity	Gage
112. Perpendicularity of flange face with cavity	
113. Perpendicularity of face of boss with pitch diameter of external thread	Gage
114. Symmetry of pin hole with cavity	Gage
115. Symmetry of width across flat with body, flange end	Gage
116. Diameter of cavity, max.	Gage
117. Diameter of datum location	Gage
118. Diameter of pin hole, max.	Gage
119. Diameter of groove	Gage
120. Diameter of flange, min.	Gage
121. Depth of counterbore internal thread	Gage
122. Depth of thread cavity	Gage
123. Length of effective internal thread, min.	Gage
124. Angle at datum diameter incorrect	Gage
125. Height of boss	Gage
126. Length of internal thread, max.	Gage
127. Angle at bottom of thread cavity, min.	Gage
128. Diameter of chamfer at internal thread cavity	Gage
129. Angle at mouth of internal thread cavity	Gage
130. Radius at root of boss	Gage
131. Profile of groove	Gage
132. Thread damaged of not full	Visual
133. Protective finish inadequate or defective	Visual
134. Surface finish of cavity and chamfer of thread cavity improper	Visual
135. Burr or sharp corner	Visual
136. Foreign matter	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

4.3.2.1 (Cont'd)

	Defect	Method of Inspection
MINOR		
201.	Pitch diameter of internal thread, min.	Gage
202.	Pitch diameter of external thread, max.	Gage
203.	Pitch diameter of pin hole thread	Gage
204.	Minor diameter of pin hole thread, max.	Gage
205.	Diameter of cavity, min.	Gage
206.	Diameter of boss cavity	Gage
207.	Diameter of body, flange end	Gage
208.	Diameter of pin hole, min.	Gage
209.	Diameter of counterbore, internal thread	Gage
210.	Diameter of undercut in cavity, if applicable	Gage
211.	Diameter of flange, max.	Gage
212.	Diameter of striker hole	Gage
213.	Depth of striker hole	Gage
214.	Depth of drill hole, pin thread, max.	Gage
215.	Total length	Gage
216.	Length of effective thread, pin hole	Gage
217.	Length across flanges	Gage
218.	Length from body of cavity to boss face	Gage
219.	Width of rear flange	Gage
220.	Location of pin hole	Gage
221.	Length of body, midsection	Gage
222.	Length from rear flange to boss face	Gage
223.	Length of flat, flange end	Gage
224	Width across flats	Gage
225.	Diameter of body intersection	Gage
226.	Width of groove	Gage
227.	Width of undercut in cavity, if applicable	Gage
228.	Marking missing, incorrect of illegible	Visual
229.	Radius or chamfer missing or incorrect, except as otherwise classified	Visual
230.	Surface finish improper, except as otherwise classified	Visual

4.3.2.2 Retainer, Cartridge, Drawing C8593013, covering a detail of Drawing D8596171.

CRITICAL		
1.	Metering slots in base missing	Visual
2.	Metal defective	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

4.3.2.2 (Cont'd)

	Defect	Method of Inspection
MAJOR		
101.	Pitch diameter of thread, max.	Gage
102.	Minor diameter of thread, max.	Gage
103.	Concentricity of cavity with pitch diameter of thread	Gage
104.	Perpendicularity of pitch diameter of thread with base	Gage
105.	Symmetry of metering slots in base with body	Gage
106.	Diameter of cavity, max.	Gage
107.	Depth of cavity	Gage
108.	Depth to bottom of counterbore	Gage
109.	Depth to metering slots in base	Gage
110.	Length of effective thread, min.	Gage
111.	Internal radius at mouth of cavity	Gage
112.	Total length	Gage
113.	Width of metering slots in base	Gage
114.	Drill point in base, max.	Gage
115.	Number of elongated slots incorrect	Visual
116.	Thread damaged or not full	Visual
117.	Protective finish inadequate or defective	Visual
118.	Burr	Visual
119.	Foreign matter	Visual
MINOR		
201.	Pitch diameter of thread, min.	Gage
202.	Diameter of body	Gage
203.	Diameter of cavity, min.	Gage
204.	Diameter of head	Gage
205.	Length of elongated slots	Gage
206.	Length of head	Gage
207.	Width of elongated slots	Gage
208.	Location of elongated slots	Gage
209.	Angle between head and body	Gage
210.	Location of metering slots	Visual
211.	Marking missing, incorrect of illegible	Visual
212.	Profile of elongated slots	Visual
213.	Radius missing or incorrect, except as otherwise classified	Visual
214.	Surface finish improper	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

4.3.2.3 Chamber, Initiator, Drawing C8593014, covering a detail of Drawing D8596171

	Defect	Method of Inspection
CRITICAL		
1.	Metal defective	Visual
MAJOR		
101.	Pitch diameter of large thread, min.	Gage
102.	Major diameter of large thread, min.	Gage
103.	Pitch diameter of small thread, min.	Gage
104.	Major diameter of small thread, min.	Gage
105.	Concentricity of counterbore with pitch diameter of large thread	Gage
106.	Concentricity of datum diameter with small thread	Gage
107.	Diameter of counterbore	Gage
108.	Depth of cavity	Gage
109.	Thickness of wall, min.	Gage
110.	Location of datum diameter	Gage
111.	Profile of gas port	Gage
112.	Thread damaged or not full	Visual
113.	Chamfer at base of cavity missing or incorrect	Visual
114.	Protective finish inadequate or defective	Visual
115.	Surface finish at end of gas port improper	Visual
116.	Burr	Visual
117.	Foreign matter	Visual
MINOR		
201.	Pitch diameter of large thread, max.	Gage
202.	Pitch diameter of small thread, max.	Gage
203.	Diameter of cavity	Gage
204.	Diameter of hole	Gage
205.	Diameter of small thread pilot	Gage
206.	Diameter of large thread pilot	Gage
207.	Length of large thread pilot	Gage
208.	Length of gas port	Gage
209.	Thickness of wall, max.	Gage
210.	Location of small thread	Gage
211.	Depth of counterbore	Gage
212.	Total length	Gage
213.	Length to end of large thread	Gage
214.	Marking missing, incorrect of illegible	Visual
215.	Radius or chamfer missing of incorrect, except as otherwise classified	Visual
216.	Surface finish improper, except as otherwise Classified	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

4.3.2.4 Pin, Shear, Drawing B8594745

Defect		Method of Inspection
CRITICAL		
	None Defined	
MAJOR		
101.	Diameter, max.	Gage
102.	Total length, min.	Gage
103.	Metal defective	Visual
104.	Protective finish inadequate or defective	Visual
105.	Surface finish improper	Visual
106.	Burr	Visual
107.	Foreign matter	Visual
MINOR		
201.	Total length, max.	Gage
202.	Profile of end	Gage

4.3.2.5 Cap, Drawing D8594856, covering a detail of drawing D8596171

CRITICAL		
1.	Metal defective	Visual
MAJOR		
101.	Pitch diameter of thread, max.	Gage
102.	Minor diameter of thread, max.	Gage
103.	Concentricity of pitch diameter of thread with center-hole, including perpendicularity with base of cavity	Gage
104.	Symmetry of flats with pitch diameter of thread	Gage
105.	Diameter of hole	Gage
106.	Depth of cavity	Gage
107.	Length of effective thread, min.	Gage
108.	Length to thread centerline	Gage
109.	Thickness of base	Gage
110.	Height, max.	Gage
111.	Profile of body	Gage
112.	Internal radius at base of large thread cavity, missing or incorrect	Visual
113.	Thread damaged or not full	Visual
114.	Protective finish inadequate or defective	Visual
115.	Burr	Visual
116.	Foreign matter	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

4.3.2.5 (Cont'd)

Defect	Method of Inspection
MINOR	
201. Pitch diameter of thread, min	Gage
202. Pitch diameter of set screw thread	Gage
203. Minor diameter of set screw thread, max.	Gage
204. Diameter of flange holes	Gage
205. Length between flange holes	Gage
206. Width across body flats	Gage
207. Location of flange holes	Gage
208. Length of flange	Gage
209. Width of flange	Gage
210. Thickness of flange	Gage
211. Location of set screw holes	Gage
212. Marking missing, incorrect or illegible	Visual
213. Radius or chamfer, missing or incorrect, except as otherwise classified	Visual
214. Surface finish improper	Visual

4.3.2.6 Pin, Firing, Drawing C8594859, covering a detail of Drawing D8596171

CRITICAL	
1. Metal defective	Visual
MAJOR	
101. Concentricity of groove with body	Gage
102. Concentricity of striker with body	Gage
103. Concentricity of striker shoulder with body	Gage
104. Symmetry of pin hole with body	Gage
105. Diameter of body, min.	Gage
106. Diameter of groove	Gage
107. Diameter of striker, max.	Gage
108. Diameter of pin hole, max.	Gage
109. Depth of pin hole, max.	Gage
110. Profile of striker	Gage
111. Profile of groove	Gage
112. Protective finish inadequate or defective	Visual
113. Surface finish of body and striker tip improper	Visual
114. Burr or sharp corner	Visual
115. Foreign matter	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

4.3.2.6 (Cont'd)

	Defect	Method of Inspection
MINOR		
201.	Diameter of body, max.	Gage
202.	Diameter of striker shoulder	Gage
203.	Diameter of pin hole, min.	Gage
204.	Depth of pin hole, min.	Gage
205.	Length from body to tip of striker	Gage
206.	Length of striker	Gage
207.	Location of pin hole	Gage
208.	Location of groove	Gage
209.	Depth of slot in base	Gage
210.	Total length	Gage
211.	Width of groove	Gage
212.	Width of slot in base	Gage
213.	Location of slot in base	Visual
214.	Marking missing, incorrect of illegible	Visual
215.	Radius missing or incorrect	Visual
216.	Surface finish improper, except as otherwise classified	Visual

4.3.2.7 *Assembly, Firing Pin Housing, D8596171 less all components except D8593012, C8594744, MS28775-009 and MS28775-12*

CRITICAL		
1.	Protrusion of firing pin	Gage
2.	"O" Ring missing	Visual
3.	Metal defective	Visual
MAJOR		
101.	"O" ring not lubricated	Visual
102.	Thread damaged or not full	Visual
103.	Protective finish inadequate or defective	Visual
104.	Foreign matter	Visual
MINOR		
	None defined	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

4.3.2.8 Assembly, Drawing D8596171

Defect	Method of Inspection
CRITICAL	
1. Any part missing	Visual
2. Improper assembly	Visual
3. Marking missing, incorrect or illegible	Visual
MAJOR	
101. Height of cap, max.	Gage
102. Set screw missing, loose, above flush or not covered with barium material	Visual and Manual
MINOR	
201. Total length, max.	Gage
202. Location of labels incorrect	Gage
203. Shipping cap or plug missing	Visual
204. Protective finish inadequate or defective	Visual

4.3.2.9 Packing in Fiber Container, Drawing F8796541

CRITICAL	
None defined	
MAJOR	
None defined	
MINOR	
201. Gap between body and cover, max.	Manual
202. Contents loose	Manual
203. Metal ends loose or distorted	Manual
204. Cut or damaged through all impregnated layers	Visual
205. Marking missing, incorrect or illegible	Visual
206. Tape incomplete or badly wrinkled	Visual
207. Length of tear tab, min.	Visual
208. Color of tape incorrect	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

4.3.2.10 Packing in Wooden Box, Drawing F8796542

Defect	Method of Inspection
CRITICAL	
None defined	
MAJOR	
None defined	
MINOR	
201. Contents loose	Manual
202. Hardware missing, loose, broken or improperly engaged	Visual & Manual
203. Strapping missing, loose, broken or improperly assembled	Visual & Manual
204. Contents of box exposed	Visual
205. Box damaged	Visual
206. Marking missing, incorrect or illegible	Visual
207. Number of units incorrect	Visual
208. Car seal missing, unsealed or improperly positioned	Visual

4.3.3 Inspection testing - The following tests shall be performed in accordance with the provisions of 4.4.

4.3.3.1 Hardness - Fifty units from each heat treated lot of components shall be tested for compliance with the values noted on the applicable drawing. Failure of any unit to comply with the drawing requirements shall be cause for rejection of the lot components.

4.3.3.2 Hydrostatic pressure - Each chamber and cap subassembly shall be subjected to the hydrostatic pressure test. Failure of any subassembly to comply with the requirements of 3.3 shall be casue for rejection of the sub-assembly.

4.3.3.3 Shear Pin strength - Fifty shear pins from each lot of shear pins tested by the contractor shall be tested for shear strength. Failure of any pin to comply with the requirements of 3.4 shall be cause for rejection of the lot.

4.3.3.4 Protective finish - The number of units for protective finish tests shall be in accordance with the applicable specification. Failure of any sample to comply with the requirements of 3.5 shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

4.3.3.5 Residual Magnetism - Each assembly shall be subjected to the test for excessive residual magnetism. Failure of any assembly to comply with the requirements of 3.6 shall be cause for rejection of the assembly.

4.3.4 Inspection equipment - The examination and tests shall be made using equipment listed on IEL8596171.

4.4 Test methods and procedures.

4.4.1 Hardness - Prior to the application of protective finish, a hardness testing machine shall be used to determine compliance with the hardness requirements specified on the applicable drawing.

4.4.2 Hydrostatic pressure - Prior to the application of protective finish the chamber and cap subassembly shall be mounted in the device, using the fixture for properly sealing all openings and subjected to the hydrostatic pressure.

4.4.3 Shear pin strength - After application of protective finish, the pin shall be subjected to the shear strength test. The test shall be performed in the fixture in conjunction with a tensile testing machine.

4.4.4 Protective finish - Test procedures for protective finish shall be in accordance with the specification referenced on the component drawing.

4.4.5 Residual magnetism - The initiator shall be tested for excessive residual magnetism in an area free of local magnetism effects by placing the initiator 6 inches from and at the same height as the compass in a north-south horizontal position (cap end at south) with the compass set in an east-west heading. The initiator shall be moved slowly past the compass in a longitudinal direction for its wntire length, rotated 90 degrees in the horizontal position about its longitudinal axis and moved slowly back past the compass. This procedure shall be repeated for each 90 degree rotation of the initiator.

5. PREPARATION FOR DELIVERY

5.1 Packing and marking - Packing and marking shall be in accordance with drawing C8796541 and C8796542.

5.2 Data card - Data card information shall be as specified in MIL-STD-1167.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data - Procurement documents should specify the title, number, and date of this specification.

6.2 A mechanical failure is defined as any deformation or breakage of a part, the occurrence of which is other than a design function.

6.3 Supersession data - This specification includes the requirements of purchase description FA-PD-MI-2227 dated 20 September 1957.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1377-A028

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

[ ] DIRECT GOVERNMENT CONTRACT [ ] SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

[ ] YES [ ] NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

FOLD

Department of the Army

Frankford Arsenal
Philadelphia, Pa. 19137

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
Department of the Army

Commanding Officer
Frankford Arsenal
ATTN: SMUFA-N1100
Philadelphia, Pa. 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.