MIL-P-60608A
25 February 1972
SUPERSEDING
MIL-P-60608
1 October 1968

MILITARY SPECIFICATION

PROJECTILE, 20MM, TARGET PRACTICE-TRACER, M221; METAL PARTS

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers metal parts for Projectile, 20mm, TP-T, M221.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

TT-C-490 - Cleaning Methods and Pretreatment of Ferrous Surfaces for Organic Coatings

MILITARY

MIL-S-46070 - Steel Bar for Projectile Stock

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-651 - Visual Inspection Standards for 20mm Ammunition and Components
MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

FSC 1305

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:49Z
Check the source to verify that this is the current version before use.

2.1 (Cont)

DRAWINGS

U.S. ARMY MUNITIONS COMMAND

C7258814	- Nose
B7258816	- Blank, Rotating Band, for Projectiles, 20mm
F7258861	- Carton for Interplant Shipment of Projectiles, 20mm, Assemblies and Metal Parts Assemblies (200)
D7259136	- Shipping Container for Inert Projectiles, 20mm, Assemblies and Metal Parts Assemblies (10,000)
D7259146	- Cartridge, 20mm, Target Practice-Tracer, M220
IEL 7259148	- Index of Inspection Equipment Lists for: Projectile, 20mm, TP-T, M221, Metal Parts
D7259148	- Projectile, 20mm, TP-T, M221, Metal Parts
D7259149	- Body, Nose and Rotating Band Assembly, Unpainted
D7259150	- Body and Rotating Band Assembly
D7259152	- Body

PUBLICATIONS

U.S. ARMY MATERIEL COMMAND

AMCR 715-505 - Ammunition Ballistic Acceptance Test Methods, Volume 8, Test Procedures for 20mm Cartridges

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions shall be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications.-The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

American Society for Testing and Materials (ASTM)
ASTM B117-64 -- Method of Test for Salt Spray (Fog) Testing

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pa. 19103)

(Technical Society and Technical Association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using federal agencies.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:49Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 General.-The projectile shall comply with Drawing (Dwg.) D7259148, referenced specifications and other requirements specified herein.

3.2 Materials.-Materials shall be in accordance with applicable drawings and specifications. Prior to producing projectile bodies from a heat of steel, the contractor shall have bar stock verification tests conducted, in a manner acceptable to the Government, to establish that the bar stock meets the requirement of MIL-S-46070.

3.3 Manufacturing process.-All parts and assemblies shall be manufactured by a process approved by the contracting officer and no deviation from that process shall be made without his prior approval. (see 6.2)

3.4 Banding.-The rotating band blank and the rotating band seat shall be clean at the time of banding. Shot or sandblasting shall not be used to clean the serrated band seat after knurling. The rotating band blank shall fill the band seat.

3.5 Soundness.-Metal discontinuity in the projectile body, as determined by eddy current inspection, shall be less than that represented by Production Check Standard (PCS) No. 1.

3.6 Protective coating.

3.6.1 Phosphate coating.-The pretreatment process used shall comply with the applicable requirements of Dwg. D7259148. The phosphate coating shall comply with the requirements of TT-C-490 for appearance and minimum weight, as applicable to the type of phosphate coating used.

3.6.2 Paint adhesion.-The painted exterior of the body shall meet the requirements of TT-C-490 for adhesion.

3.6.3 Corrosion resistance.-The painted exterior of the body assembly shall show no evidence of corrosion (red rust) after exposure to a 5 percent solution of atomized salt spray for 24 hours.

3.7 Metal parts security.-The sample projectile, metal parts, when assembled into cartridges having a mean instrumental velocity at 78 feet of 3540 ± 25 feet per second (fps), shall not separate or break up in the metal parts security test.

3.8 Workmanship.-The requirements for workmanship are as specified by applicable drawings, referenced specifications and the following:

3.8.1 Processing defects.-The projectile shall be free of defects, such as dents, deep scratches, cuts, sharp edges, burrs, metal flaws and other forms of substandard workmanship.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:49Z
Check the source to verify that this is the current version before use.

3.8.2 Cleanliness.-The projectile shall be free of all foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality assurance terms and definitions.-Reference shall be made to MIL-STD-109 for definition of quality assurance terms.

4.2 Bar stock verification.-Independent of tests and inspections performed by the steel bar supplier, an examination shall be made on each lot of bars. The inspections and tests used to verify the bar stock quality shall be as specified by MIL-S-46070, Table IV, using the requirements, acceptance criteria and test methods referenced therein, with the following modifications:

Chemical composition: Sulphur only is required.
Mechanical properties: Unmodified.
Grain size: Unmodified.
Soundness:
    Macro-etch:
        Billet: See Note 1
        Bar: See Note 1
    Magnetic: See Note 1
Surface decarburization: Not required.
Dimensions: Diameter only.
Workmanship: See Note 1

NOTE 1. The supplier's macro-etch, magnetic and visual inspection shall be monitored to the extent necessary to assure compliance with MIL-S-46070.

4.3 First article sample. (see 6.3)

4.3.1 Initial production sample.-At the beginning of regular production a sample applicable to the approved process shall be submitted in accordance with contract requirements and shall consist of:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:49Z
Check the source to verify that this is the current version before use.

4.3.1 (Cont)

a. Inspection and nonfiring tests:

125 Rotating band blanks
125 Noses
125 Bodies, without rotating band
125 Body and rotating band assemblies
125 Body, nose and rotating band assemblies, unpainted
125 Projectile metal parts, assemblies
3 Standard test panels

b. Firing test:

4,000 projectile metal parts, assemblies

The sample shall be manufactured using the same materials, equipment, processes and procedures as will be used in regular production. Identification shall be in accordance with MIL-STD-1168.

4.3.1.1 Examination and test.-After inspection and provisional acceptance at source, the sample will be inspected for all requirements of the drawings and specifications at a Government laboratory or such other facility specified by the contract. (see 6.3)

4.3.1.2 Initial production sample failure.-Failure of the sample to comply with requirements of the drawings and specifications will result in sample disapproval.

4.4. Inspection provisions.

4.4.1 Submission of product.-The product shall be submitted in accordance with MIL-STD-105 or MIL-STD-1235, as applicable.

4.4.1.1 Lot.-A lot shall consist of projectile metal parts assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawings and drawing revisions, and same specification and specification revision.

4.4.1.2 Lot identification.-Each projectile metal parts assembly and each packed lot shall be identified in accordance with applicable drawings and MIL-STD-1168.

4.4.2 Examination.-One hundred percent examination shall be performed by the contractor for all critical defects. Examination for major and minor defects shall be performed as specified herein. Each part and each assembly found to be defective shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:49Z
Check the source to verify that this is the currentversion before use.

4.4.2.1 Sampling and acceptance criteria.-The sampling plans and procedures shall be in accordance with MIL-STD-105 or MIL-STD-1235. To determine product acceptability, major and minor defects as listed herein may be considered collectively on a class basis or they may be considered individually. However, where major defects are considered collectively on a class basis, the acceptance number for any individual defect of the class shall be limited by the assigned Acceptable Quality Level (AQL) for individual defect associated with the class. (see 4.4.2.2.c) In addition, where three or less defects appear in a classification, or, where MIL-STD-1235 is used, sampling plans applicable to a class shall not be used. (see 6.4)

4.4.2.2 AQL's.-The following AQL's are assigned to major and minor defects:

a. Individual:

Major	0.25%
Minor	0.40%

b. Class basis:

Major	1.50%
Minor	2.50%

c. Individual defects associated with the class basis:

Major	0.40%

4.4.3 Classification of defects.-1/ The classification of defects shall be as specified herein (see 6.5):

4.4.3.1 Rotating band blank (see Dwg. B7258816).

Categories and Defects	Method of Inspection
Critical: None defined.	
Major:	
101. Foreign matter	Visual (see 3.8.2)
102. Defective metal, including lamination	Visual
103. Incomplete or deformed	Visual 2/
Minor:	
201. Width, max.	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:49Z
Check the source to verify that this is the current version before use.

4.4.3.2 Nose (see Dwg. C7258814).

Categories and Defects	Method of Inspection
Critical: None defined.	
Major:	
101. Diameter, ogive at shoulder, min.	Gage
102. Length, spherical surface to shoulder, max.	Gage
Minor:	
201. Diameter, ogive at shoulder, max.	Gage
202. Length, spherical surface to shoulder, min.	Gage
203. Diameter, cylindrical surface	Gage
204. Over-all length, min.	Gage
205. Profile, ogive, except length, spherical surface to shoulder	Gage
206. Finish	Visual/Feel
207. Foreign matter	Visual
208. Mutilated	Visual

4.4.3.3 Body (see Dwg. D7259152).

Categories and Defects	Method of Inspection
Critical: None defined.	
Major:	
101. Diameter, bourrelet, min.	Gage
102. Depth, knurling, min.	Visual/Gage 3/
103. Knurling missing, incomplete or deformed	Visual
104. Foreign matter in rotating band seat (at time of banding)	Visual
105. Thread score missing	Visual
106. Length, to rear edge of rotating band seat	Gage
107. Depth, body cavity, max.	Gage
108. Perforation or fracture in tracer cavity	Visual
109. Angle of crimp lip	Gage
Minor:	
201. Diameter, rotating band seat (knurled)	Gage
202. Width, knurling, min.	Visual/Gage 3/
203. Width, rotating band seat	Gage
204. Mouth chamfer missing	Visual
205. Over-all length	Gage
206. Depth, mouth cavity, min.	Gage
207. Foreign matter in mouth or body cavity (at time of nosing)	Visual
208. Diameter, mouth cavity	Gage
209. Diameter, body cavity, max.	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:49Z
Check the source to verify that this is the current version before use.

4.4.3.4 Body, nose and rotating band assembly, unpainted (see Dwgs. D7259152, D7259150 and D7259149).

Categories and Defects	Method of Inspection
Critical:	
1. Ferrous metal discontinuity	"Soundness" Test
Major:	
101. Diameter, bourrelet, max.	Gage
102. Diameter, tracer cavity	Gage
103. Depth, tracer cavity	Gage
104. Run out, tracer cavity with bourrelet	Gage
105. Diameter, metering disc seat	Gage
106. Depth, metering disc seat	Gage
107. Width, crimping lip	Gage
108. True position, metering disc seat with tracer cavity	Gage
109. Diameter, body, rear of rotating band, min.	Gage
110. Run out, body diameter, rear of rotating band, with bourrelet	Gage
111. Diameter, rotating band	Gage
112. Run out, rotating band, with bourrelet	Gage
113. Profile, crimping groove	Gage
114. Radius, rear edge of crimping groove, max.	Gage
115. Location, crimping groove	Gage
116. Length, nose, to rear edge of rotating band	Gage
117. Run out, nose, with bourrelet	Gage
118. Gap, between nose and body, max.	Gage
119. Body ogive above flush with nose ogive	Visual
120. Void, junction rotating band and body	Visual
Minor:	
201. Width, rotating band	Gage
202. Depth and width of undercut, front and rear of rotating band	Gage
203. Finish	Visual/Feel 4/
204. Mutilated	Visual
205. Loose nose	Manual 5/

4.4.3.5 Projectile, metal parts, 20mm, TP-T, M221 (see Dwg. D7259148).

Categories and Defects	Method of Inspection
Critical: None defined.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:49Z
Check the source to verify that this is the current version before use.

4.4.3.5 (Cont)

Categories and Defects	Method of Inspection
Major:	
101. Diameter, bourrelet, max.	Gage
102. Diameter, body, rear of rotating band, max.	Gage
103. Diameter, metering disc seat, min.	Gage
104. Diameter, tracer cavity, min.	Gage
105. Depth, tracer cavity, min.	Gage
106. Foreign matter	Visual 6/
107. Weight	Balance
108. Drill point below max. depth of tracer cavity	Visual
Minor:	
201. Paint inadequate	Visual
202. Paint on rotating band	Visual
203. Exterior paint not dry	Touch
204. Marking incorrect, incomplete, illegible or missing	Visual
205. Rotating band damaged	Visual

1/ MIL-STD-651 shall apply in defining and evaluating visual defects.

2/ A rotating band blank which is deformed or judged to lack sufficient metal in any part of its width or thickness to provide for complete band seat fill and minimum rotating band profile dimensions shall be classed defective.

3/ Measurement of knurling for compliance with the minimum depth and width requirements shall apply where visual inspection indicates that either dimension is borderline.

4/ Measurement of surface roughness shall apply where visual inspection indicates that the specified finish is exceeded.

5/ If the nose moves with respect to the projectile body under thumb and finger pressure applied in the lateral or axial direction, the projectile shall be classified defective.

6/ An assembly that has foreign matter on the exterior or contained in the tracer cavity shall be classed defective.

4.4.4 Tests.-The tests listed in Table I shall be conducted in compliance with the test methods and procedures prescribed by 4.5. The samples shall be selected in such a manner as to be representative of the entire lot. The sample size and acceptance criteria for each test shall be as specified.

Source: https://assist.dla.mil -- Downloaded: 202640-23T00:49Z
Check the source to verify that this is the current version before use.

Table I

Test	Sample Size		Item	Rqmt Para
Band tightness	1/	315	Projectile, metal parts, painted	3.4
Automatic inspection effectiveness	2/		PCS No. 1 (see 4.5.3)	--
Soundness verification	3/	315	Body, nose, and rotating band assembly, uncoated	3.5
Phosphate coating (appearance & weight)	4/	3	Standard panels (see TT-C-490)	3.6.1
Paint adhesion	5/	13	Projectile, metal parts, painted	3.6.2
Corrosion resistance	6/	32	Projectile, metal parts, painted	3.6.3
Metal parts security	7/	250	Projectile, metal parts, painted	3.7

1/ If two or more units of the sample have an average radial void, between the seated band and the band seat, greater than 0.004 inch, the lot shall be rejected. If one unit of the sample has an average radial void, greater than 0.004 inch, a second sample consisting of the same number of units as specified for the first sample shall be tested. If in the accumulated samples, two or more units have an average radial void greater than 0.004 inch, the lot shall be rejected.

2/ Failure of the flaw detector to reject PCS No. 1 shall be cause for rejection of all assemblies inspected for "soundness" since the preceding test and shall require requalification of the equipment for automatic inspection. (see 4.5.3)

3/ Rejection of one or more units of the sample by the flaw detector in the test for body metal soundness shall be cause for rejection of the lot.

4/ Failure of the phosphate coating on the standard panels to comply with the applicable requirements shall be cause for rejection of all projectiles phosphated since the preceding test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:49Z
Check the source to verify that this is the current version before use.

5/ If two or more units of the sample fail to comply with the requirement for paint adhesion, the lot shall be rejected. If one unit of the sample fails to comply with the requirement, a second sample consisting of the same number of units as specified for the first sample shall be tested. If in the accumulated samples, two or more units fail to comply with the requirement for paint adhesion, the lot shall be rejected.

6/ If two or more units of the sample fail to comply with the corrosion resistance requirement, the lot shall be rejected. If one unit fails to comply with the requirement, a second sample consisting of the same number of units as specified for in the first sample shall be tested. If in the accumulated samples, two or more units fail to comply with the corrosion resistance requirement, the lot shall be rejected.

7/ The occurrence of one or more of the following casualties, as witnessed by hole(s) in the fragmentation screens, or recovery of the part(s) or fragment(s), shall be cause for rejection of the lot, except as otherwise provided:

a. Body breakup.

b. Breakup or separation of the nose from the body.

c. Complete rotating band separation. This is defined as detachment of all of the band having band seat knurling imprint.

d. Partial rotating band separation. This is defined as detachment of part of the band having band seat knurling imprint.

e. The following acceptance criteria shall apply to thrown band fragments having no evidence of band seat knurling imprint:

(1) The lot shall be accepted if two or less projectiles throw band fragments having length not greater than 0.500 inch.

(2) The lot shall be rejected if three or more projectiles throw band fragments having length not greater than 0.500 inch.

(3) The lot shall be rejected if any projectile throws a band fragment having length greater than 0.500 inch (indicative of deep seated band lamination).

(4) The lot will not be penalized for band particles thrown as a result of normal band fringing or slivering.

4.4.5 Packaging, packing and marking inspection.-Inspection for packaging, packing and marking shall comply with applicable requirements of MIL-STD-1169.

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:49Z
Check the source to verify that this is the current version before use.

4.4.6 Inspection equipment.-Index of Inspection Equipment Lists IEL 7259148 identifies inspection equipment list required to perform examination and tests prescribed herein. Equipment design shall be in accordance with code designation on the applicable IEL (reference is made to Inspection Equipment List for definition of coding format).

4.5 Test methods and procedures.

4.5.1 Band tightness.-The method of test shall comply with all requirements of the operating instructions for the band tightness tester (see Dwg. B7259545, a detail of IEL 7259148). The inspection sample shall be cycled through the tester to determine compliance with the rotating band tightness requirement. The total measurement of radial void registered on the tester indicator at final ram pressure shall be divided by four (number of indentors) to determine the average radial void.

4.5.2 Soundness.-The method of inspection shall comply with all requirements of Operating Instruction Manual, prepared for operation of the Eddy Current Flaw Detector (see Dwg. D11075203, a detail of IEL 7259148), for detecting metal discontinuity in projectile bodies for 20mm ammunition, except for those inspection requirements which are reserved for Government application, as specified herein.

4.5.2.1 Application of defect standards.-Master defect standards, referenced in the Operating Instruction Manual, shall apply to resolve inspection discrepancies occurring between the results of defect standards supplied for contractor "soundness" inspection and those supplied for Government "soundness" verification. (see 6.6)

4.5.3 Automatic eddy current inspection effectiveness.-Equipment checkout shall be performed as stated in the operation instruction manual at the start of each shift and after any adjustment or shutdown. Upon completion of checkout, cycle the PCS No. 1, front slot and rear slot standards through the inspection system during automatic operation. All three standards must be rejected to assure correct adjustment for reject level and scan limits. During remainder of shift the PCS No. 1 shall be cycled through the equipment at intervals of 20 ± 5 minutes during automatic operation.

4.5.3.1 Equipment verification.-The government inspector will maintain, independent of the contractor, a set of standards and may cycle these standards through the equipment at any time. Failure of equipment to reject standards will be evidence that the equipment is not properly adjusted and the contractor will so be notified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:49Z
Check the source to verify that this is the current version before use.

4.5.4 Soundness verification.-After equipment checkout and verification as specified in 4.5.3 and 4.5.3.1 the entire lot sample will be inspected with the equipment operating automatically. Any rejected unit of the sample will be automatically cycled through the equipment with the CAL. button pressed (to lower the sensitivity one step below that used for production inspection). Any unit which is rejected at the lower sensitivity shall be classed as a defective.

4.5.5 Phosphate coating.-The method of test shall be as prescribed by TT-C-490 for the type of coating used. The prescribed panels shall be processed, with the projectiles to be represented, at the start of daily production and at 4-hour intervals, maximum, thereafter. Appearance and weight of the coating shall be recorded.

4.5.6 Paint adhesion.-The method of test shall be as prescribed by TT-C-490. The test shall be made on the painted bourrelet of each unit of the sample. Visible exposure of underlying phosphate coating or ferrous metal, of any unit of the sample as a result of the test, shall be classed as a defect.

4.5.7 Corrosion resistance.-The method of test shall be as prescribed in American Society for Testing and Materials (ASTM), ASTM B117. The paint shall not be disturbed, however, the rotating band and unpainted surfaces of the sample projectiles may be masked out by a wax coating or other suitable material. The salt spray solution and exposure time shall be as specified in 3.6.3.

4.5.8 Metal parts security.-The method of test will be as prescribed by AMCR 715-505, Volume 8, Section 3, modified as necessary to load the lot sample at the specified mean velocity in lieu of excess pressure. The sample assemblies with metering discs will be loaded and assembled into cartridges as specified by Dwg. D7259146 with the following exceptions:

(1) Inert material will be used to simulate the weight of trace composition.

(2) The seal over the simulated tracer composition may be omitted.

(3) A propellant shall be used which will produce the specified mean velocity of 3540 ± 25 fps.

The test cartridges, at ambient temperature, will be fired in bursts of 50 shots in an M39 gun. The gun barrel will be at ambient temperature for the firing of each burst. The cyclic rate of fire will be recorded for informational purposes.

5. PREPARATION FOR DELIVERY

5.1 Packing, Level C.-Each lot of projectile assemblies shall be packed as specified by Dwgs. F7258861 or D7259136.

Source: https://assist.dla.mil -- Downloaded: 202640-23T00:49Z
Check the source to verify that this is the currentversion before use.

5.2 Marking and labeling.-Marking or labeling of shipping containers shall comply with applicable requirements of MIL-STD-1169.

6. NOTES

6.1 Ordering data.-Invitations for bids and contracts or orders will specify the following:

6.1.1 Title, number and date of this specification.

6.1.2 Place of inspection, if not at place of manufacture.

6.1.3 Packing and marking instructions. (see 5.1 and 5.2)

6.1.4 Provision for shipment and testing of production lot samples for the metal parts security test.

6.1.5 Provision for the supply, maintenance and disposition of mandatory ballistic test equipment for acceptance inspection purposes.

6.1.6 Provision for the submission and approval of the manufacturing process. (see 3.3)

6.2 Process deviation.-A process deviation is defined as a change in the approved basic method of manufacture, or an operational change which alters the metallurgical or physical properties of the item.

6.3 First article sample.-Where an initial production sample is required by the contract, the contracting officer will notify the test facility when to proceed with the metal parts security test. (see 4.3) Additional projectiles may be required by the test facility.

6.4 AQL's.-The optional use of AQL values for either individual defects or classes of defects, with individual major defect limitation, is intended to minimize inspection agency administrative burden which might result from an exclusive assignment of individual defect AQL's. The option also permits flexibility where sampling inspection for acceptance is integrated into the manufacturing process.

6.5 Intermediate point inspection.-The classification of defects identifies the defect characteristics (among other things) for acceptance inspection. It may be necessary to modify the sequence of inspection stations to best suit the manufacturing process. Inspection for defect characteristics which will be hidden or altered by subsequent processing operations (including unrelated operations), should be scheduled to prevent premature acceptance which could be detrimental to the attainment of optimum product quality in the end item.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:49Z
Check the source to verify that this is the current version before use.

6.6 Defect standards.-The initial supply of defect standards and instructions for contractor and Government application to the eddy current method of inspection will be furnished with the eddy current inspection equipment. Replacement standards should be requisitioned through normal channels by the Government agency having contract administration responsibility.

Custodians:

Army - MU
Air Force - 70

Preparing Activity:

Army - MU

Review Activities:

Army - MU
Air Force - 70

Project No. 1305-0690

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:49Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

[ ] YES [ ] NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:49Z
Check the source to verify that this is the current version before use.