SUPERSEDING
MIL-S-83791 (USAF)
19 November 1973

MILITARY SPECIFICATION

# SUITCASE, FLYER'S CLOTHING, B-4B

This specification is approved for use by
HQ AFLC CASO/LODS, Federal Center, Battle Creek MI 49016,
Department of the Air Force, and is available for use by all
Departments and Agencies of the Department of Defense.

## 1. SCOPE

1.1 This specification covers one type and size of clothing bag.

## 2. APPLICABLE DOCUMENTS

*2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

Federal

| | |
|---|---|
| C-B-191 | Beeswax, Technical; Crude Grade |
| L-P-375 | Plastic Film, Flexible Vinyl Chloride |
| V-F-106 | Fasteners, Slide, Interlocking |
| V-T-295 | Thread, Nylon |
| KK-L-169 | Leather, Horsehide Chrome Tanned for Gloves, Garments and Equipage |
| KK-L-271 | Leather, Cattlehide, Strap, Vegetable Tanned |
| QQ-P-416 | Plating, Cadmium (Electrodeposited) |
| QQ-S-698 | Steel, Sheet and Strip, Low-Carbon |
| QQ-W-428 | Wire, Steel, Carbon (High Carbon, Round, for Mechanical Springs, General Purpose) |
| QQ-W-461 | Wire, Steel, Carbon (Round, Bare, and Coated) |

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Hq AFLC CASO/LODS, Federal Center, Battle Creek MI 49016 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:41Z
Check the source to verify that this is the current version before use.

| | |
|---|---|
| TT-V-109 | Varnish, Spar, Alkyd-Resin |
| VV-W-95 | Wax, Paraffin, Technical |
| DDD-L-20 | Label: for Clothing, Equipage and Tentage, (General Use) |
| MMM-A-139 | Adhesive Natural or Synthetic-Natural Rubber |
| PPP-B-636 | Box, Shipping, Fiberboard |

Military

| | |
|---|---|
| MIL-C-496 | Clip, End, Strap |
| MIL-W-530 | Webbing, Textile, Cotton, General Purpose, Natural or in Colors |
| MIL-B-543 | Buckles, Tongueless and Web Strap |
| MIL-C-7219 | Cloth, Duck, Nylon |
| MIL-F-10336 | Fiber Sheet, Vulcanized |
| MIL-L-11075 | Loops, Strap Fastener |
| MIL-E-20652/1 | Eyelets, Metallic, Rolled Flange Type; and Eyelet Washer |
| MIL-C-20696 | Cloth, Coated, Nylon, Waterproof |

STANDARDS

Federal

| | |
|---|---|
| FED-STD-191 | Textile Test Methods |
| FED-STD-751 | Stitches, Seams and Stitchings |

Military

| | |
|---|---|
| MIL-STD-105 | Sampling Procedures and Tables for Inspection by Attributes |
| MIL-STD-129 | Marking for Shipment and Storage |
| MIL-STD-1186 | Cushioning, Anchoring, Bracing, Blocking, and Waterproofing; with Appropriate Test Methods |
| MS16535 | Rivet-Tubular, Oval Head |
| MS21043 | Nut- Self-Locking, Hexagon |
| MS27980 | Fasteners, Snap, Style 2 (Regular Wire Spring Clamp Type) |
| MS35214 | Screw, Machine-Pan Head, Cross-Recessed, Brass, Black Oxide, UNC-2A |
| AN960 | Washer, Flat |

DRAWINGS

Air Force

| | |
|---|---|
| 52K6757 | Suitcase, Flyer's Clothing, Sage Green, Type B-4B |
| 36D5887 | Handle-Flyer's Clothing Bag |

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

*2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated the issue in effect on date of invitation for bids or request for proposal shall apply.



Source: https://assist.dla.mil -- Downloaded: 202610-23T09:41Z
Check the source to verify that this is the current version before use.

DEPARTMENT OF COMMERCE

| | |
|---|---|
| CS35 | Hardwood Plywood |

(Application for copies should be addressed to the Superintendent of Documents, US Government Printing Office, Washington DC 20402.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

| | |
|---|---|
| ASTM-A-108 | Steel Bars, Carbon, Cold Finished, Standard Quality |
| ASTM-A-575 | Merchant Quality Hot Rolled Carbon Steel Bars |
| ASTM-A-663 | Merchant Quality Hot Rolled Carbon Steel Bars Subject to Mechanical Property Requirements |

(Application for copies should be addressed to the American Society for Testing and Materials (ASTM), 1916 Race Street Philadelphia PA 19103.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to American Trucking Associations, Attn: Tariff Order Section 1616 P Street, N.W., Washington DC 20036.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago IL 60606.)

## 3. REQUIREMENTS

3.1 First article. When specified (see 6.2), before production is commenced, a sample of the finished item shall be submitted or made ready for the contracting officer or his authorized representative for inspection as specified in 4.2.1. The approval of the preproduction sample authorizes the commencement of production but does not relieve the supplier of responsibility for compliance with all applicable provisions of this specification. The preproduction sample shall be manufactured by the supplier in the same facilities to be used for the manufacture of the production items.

3.2 Materials.

*3.2.1 Coated cloth. The coated cloth shall be nylon conforming to MIL-C-20696, type III, Class II except it shall be coated on one side only with the compound specified in 3.2.1.1 and shall conform to the requirements of Table I when tested as specified in 4.2.2. The coating shall be pebble grain in appearance conforming to Uniroyal Plastic Products Patt Roll No. PF6134, Roehlen Engraving Work Patt Roll Nos 67RE02 or 51 RE19, Consolidated Engravers Corp. Patt Roll No. 7569 or equal (see 6.3). If substitute pattern is used, prior to use, a sample shall be submitted to the contracting officer who will secure approval from the responsible activity. The coated side shall be placed on the outside of the bag.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:41Z
Check the source to verify that this is the current version before use.

TABLE I. Physical requirements of coated fabric.

| Characteristics | Minimum | Maximum |
|---|---|---|
| Weight-ounces per square yard | 11.0 | 12.25 |
| Breaking strength-pounds | | |
| Warp | 325 | |
| Filling | 275 | |
| Tearing strength-pounds | | |
| Warp | 20 | |
| Filling | 20 | |
| Adhesion of coating-pounds per 2 inch width min. | | |
| Average (5 specimens) | | |
| Dry or wet | 40 lb | |
| Single determinations (no more than 2 of 5 determination) | 30 lb | |
| Resistance to accelerated weathering | | |
| No blooming, chalking, bleeding, cracking or flaking | | |
| Cold crack resistance at minus 10°F | No cracking | |
| Flame resistance- | | |
| Warp | 42 sec | |
| Heat after 2 hour exposure at 160°F ± 2°F | No melting or stickiness | |

3.2.1.1 Coating compounds. The coating compound shall be suitably compounded virgin vinyle chloride or vinyl chloride-acetate copolymer plasticized with phthalate or phosphate ester plasticizers to at least 60 percent of the total plasticizer level. The total plasticizer level shall not exceed 85 parts per 100 parts resin. The compound shall be adequately protected with fire and mold inhibitors and anti-bacterial agents.

3.2.1.2 Color. The coated cloth shall be sage green in color to match Air Force shade 1509.

3.2.2 Plywood. The plywood for the coat hanger shall be 5 ply, technical type, waterproof bond, high density, good grade I, 0.250 inch thick conforming to commercial standard CS-35-61.

3.2.3 Fiber sheet. The fiber sheet for the frame, stiffener and retainer shall be vulcanized fiber sheet, .1875 inch thick, and shall conform to MIL-F-10336.

3.2.4 Cattlehide leather. The leather for the handle strap shall be cattlehide conforming to KK-L-271, type I, II or III, class 1, 6 ounce thick. The color shall be black Air Force shade 1513.

3.2.5 Horsehide leather. The leather covering for the handle shall be horsehide conforming to KK-L-169 type I, class 2, Section 1.75 to 3.25 ounce thick. Vegetable tanned horsehide may be substituted at contractor's option.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:41Z
Check the source to verify that this is the current version before use.

3.2.6 Adhesive. The adhesive used in the fabrication of the handle shall conform to MMM-A-139, class 2.

3.2.7 Vinyl. The vinyl shall conform to L-P-375, type II. The thickness shall be 20 gage. The color shall be black. The vinyl shall show no cracking at -10° Fahrenheit (F) when tested as specified in 4.2.2.

3.2.8 Webbing. The webbing shall conform to MIL-W-530, type II or III, class 4. The color shall approximate the color of the coated cloth (see 3.2.1.2).

3.2.9 Wax. The wax for dipping the ends of the webbing shall be a mixture of equal parts by volume of beeswax conforming to C-B-191 and paraffin conforming to VV-W-95.

3.2.10 Steel.

3.2.10.1 Steel Bar. The steel bar for the hook attachment ring shall conform to ASTM-A-575, ASTM-A-663 or ASTM-A-108.

3.2.10.2 Steel wire. The steel wire for the clothing hanger retainer shall conform to QQ-W-461 composition FS1006 to FS1020 finish No. 1. The steel wire for the clothing bag hook shall conform to QQ-W-461 composition FS1020 finish No. 1. The steel wire for the clothing hanger hook shall conform to QQ-W-428 type II.

3.2.10.3 Steel sheet. The steel sheet for the frame retainer clamp shall conform to QQ-S-698 commercial quality, cold rolled, half hard, temper finish No. 1.

3.2.11 Varnish. The varnish for the hanger shall conform to TT-V-109.

3.2.12 Duck cloth. The duck cloth for the dust curtain and the shoe bag shall conform to MIL-C-7219, type III. The color shall be sage green Air Force shade 1509.

3.2.13 Thread. The nylon thread for all stitching shall be black conforming to V-T-295, type I, class I. The thread for the handle shall be size E. The thread for the binding on the dust cover and the shoe bag shall be size F. The thread for all other sewing operations shall be size 3.

3.3 Components.

3.3.1 Loop. The loops for the handle shall conform to MIL-L-11075, type III, style P.

3.3.2 Buckle. The buckle shall conform to MIL-B-543, type III, style 3, class 3 (construction A) size 5/8 inch.

3.3.3 Clip, end. The webbing end clip shall conform to MIL-C-496, type I, class 2, size 5/8 inch.

3.3.4 Fastener, slide. The slide fasteners shall be brass conforming to V-F-106, type I, style 18, size MH. The fastener tape shall be sage green Air Force shade No. 1509.

3.3.5 Snap, spring. The spring snap for the clothing hanger shall be nickel plated cast brass conforming to North and Judd part number 334 or equal.

3.3.6 Rivet. The rivet for attaching the clothing hanger hook to the clothing hanger shall be MS16535-310.

3.3.7 Glides. The rivets for the glides shall be J.L. Thomson part number 5-6688 or equal.

3.3.8 Labels. The labels shall conform to DDD-L-20.

3.3.8.1 Identification label. The identification label shall be type I, class 5.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:41Z
Check the source to verify that this is the current version before use.

3.3.8.2 Blank label. The blank label shall be type I, class 10.

3.3.9 Washers.

3.3.9.1 Washers, steel. The steel washers shall conform to AN960D8.

3.3.9.2 Washers, brass. The brass washers shall conform to MIL-E-20652-1-BBW-101.

3.3.10 Eyelets. The eyelets shall conform to MIL-E-20652-1-BBB-117.

3.3.11 Screws. The screws shall conform to MS35214-42 or -43 as shown on Drawing 52K6757.

3.3.12 Nuts. The nuts shall conform to MS21043.

3.3.13 Fasteners, snap. The snap fasteners shall be black finish brass conforming to MS27980.

3.3.14 Metal handle clip. The clip shall be a commercial product fabricated from steel.

3.4 Assembly. The bag shall be fabricated and assembled in accordance with the drawings listed in Section 2 and the provisions of this specification. In the event of a conflict between the drawings and this specification, the specification shall govern.

3.5 Stitching. All stitching shall conform to FED-STD-751, type 301. Gusset stitching shall be 3 to 6 stitches per inch. The stitching on the handle shall be 5 to 6 stitches per inch. All other stitching shall be 6 to 8 stitches per inch.

3.5.1 Stitching ends. Stitching ends shall be overstitched not less than one inch except where ends are turned under in a hem, are held down by other stitching or where stitching is performed automatically. When stitch patterns such as box, box with cross-stitch, or straight line tacking are performed automatically, at least 3 or more tying, overlapping or backstitches shall be used to secure the ends of stitching.

3.5.2 Thread breaks. Thread breaks, skipped stitches and bobbin runouts shall be repaired by overstitching the break beginning at least one inch before the break and ending not less than one inch beyond the break.

3.5.3 Tension. Thread tension shall be properly maintained so there will be no loose or excessively tight stitching. All thread ends shall be trimmed 0.250 inch or less.

3.6 Plating. The clothing bag hanger hook, clothing bag hook ring and clothing hanger hook shall be cadmium plated in accordance with QQ-P-416, type I, class 3.

3.7 Surface treatment. The clothing hanger shall be sanded smooth and shall be varnished with the varnish specified in 3.2.12. The varnish shall be smooth, even and uniform. There shall be no evidence of flaking, cracking, peeling or blistering, and there shall be no tackiness.

3.8 Metal parts. All metal parts shall be free from burrs or sharp edges that may cut or tear clothing placed in the bag.

3.9 Shade or size tickets. The use of shade or size tickets with metal attachments that might damage the cloth or those that leave an adhesive mass attached to the cloth upon removal of the tickets, is prohibited.

3.10 Setting of snap fasteners. The snap fasteners shall be securely set without cutting the surrounding cloth.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:41Z
Check the source to verify that this is the current version before use.

3.11 Setting of webbing end clip. The webbing shall be inserted fully in the end clip. The clip shall be securely clinched without cutting the webbing. The webbing shall be flat at the point of entrance.

3.12 Replacing defective components. At the time of cutting or manufacturing, components found to contain defects which are classified as defects in Table II shall be removed from production and replaced with nondefective components.

3.13 Workmanship. The finished bag shall be clean and shall conform to the quality and grade of product established by this specification. The occurrence of defects shall not exceed the acceptable quality levels specified herein.

TABLE II. General Defects.

| Defects | Classification | |
|---|---|---|
| | Major | Minor |
| Material defects and damages | | |
| a. Basic material | | |
| 1. Hole, cut, tear or needle chew | X | |
| 2. Mend or patch | X | |
| 3. Exposed drill holes | | X |
| 4. Fabric defects - seriously affecting serviceability or appearance | X | |
| - affecting serviceability or appearance but not seriously | | X |
| b. Coating | | |
| 1. Damaged, cracked, blistered, abraded, or punctured | X | |
| 2. Any area of coating omitted, coating tacky or flaking | X | |
| c. Vinyl | | |
| 1. Not specified thickness | X | |
| 2. Hole, cut or break | X | |
| d. Webbing | | |
| 1. Not firmly and tightly woven | X | |
| 2. Frayed or scalloped edges | X | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:41Z
Check the source to verify that this is the current version before use.

TABLE II. General Defects. - Continued

| Defects | Classification | |
|---|---|---|
| | Major | Minor |
| e. Hardware: Any component missing, damaged, broken or malformed; protective finish omitted or not as specified | X | |
| f. Leather: Holes, cuts or tears; loose, spongy, flaky weak or thin spots | X | |
| g. Seams and stitching: open seams | | |
| 1. Up to 0.500 inch | | X |
| 2. More than 0.500 inch | X | |
| NOTE: A seam shall be classified as open when 1 or more stitches joining a seam are broken or when 2 or more continuous skipped stitches or run offs occur. On double stitched seams a seam shall be classified as open when either one or both sides of the seam are open | | |
| h. Raw edges (except on binding) | | |
| More than 0.250 inch when securely caught in stitching | | X |
| NOTE: Raw edges not securely caught in stitching shall be classified as open seams. | | |
| i. Seam and stitch types - wrong seam or stitch type | | |
| - Seriously affecting serviceability or appearance | X | |
| - Affecting serviceability or appearance but not seriously | | X |
| j. Stitch tension - loose, resulting in a loosely exposed top or bobbin thread; tight, resulting in puckering of fabric on seams | | X |
| k. Stitches per inch | | |
| 1. More than one stitch less than the minimum specified | X | |
| 2. One stitch less than the minimum specified or one or more stitches in excess of the maximum specified | | X |
| l. Stitching | | |
| 1. Ends overstitched less than one inch | | X |
| 2. Margin: Gage on double needle stitching not as specified | | X |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:41Z
Check the source to verify that this is the current version before use.

TABLE II. General Defects. - Continued

| Defects | Classification | |
|---|---|---|
| | Major | Minor |
| m. Box stitching | | |
| 1. Any required row of stitching omitted | | X |
| 2. Length of box stitching less than specified by more than 1/8 inch | | X |
| 3. Needle or feed dog chews | X | |
| n. Components and assembly | | |
| 1. Any component part or required operation omitted or not as specified | X | |
| 2. Any required row of stitching omitted except on box stitching | X | |
| 3. Seams or hems badly twisted, puckered or pleated | | X |
| 4. Any part of case caught in an unrelated operation or stitching | X | |
| 5. Suitcase gusset not of one piece or gusset joining seam not finishing underneath top protector | X | |
| o. Binding - improperly or loosely applied | | X |
| End of binding not finished as specified | | X |
| Edge of binding not finished as specified | | X |
| p. Corners - radius not uniform on all corners of pockets or case, corners irregularly shaped | | X |
| q. Slide fasteners not as specified | X | |
| Slide jams or fails to interlock chain; tape improperly applied, causing malfunction | X | |
| r. Handle - not fabricated as indicated on Drawing 36D5887 | | |
| - Seriously affecting serviceability or appearance | X | |
| - Affecting serviceability or appearance but not seriously | | X |
| - Ends of stitching not knotted or backstitched | | X |
| - Metal handle clip omitted | X | |



Source: https://assist.dla.mil -- Downloaded: 202610-23T09:41Z
Check the source to verify that this is the current version before use.

TABLE II. General Defects. - Continued

| Defects | Classification | |
|---|---|---|
| | Major | Minor |
| - Finished ends of handle not securely attached to case | X | |
| - Backing material on handle assembly omitted or damaged | X | |
| s. Reinforcements - omitted, misplaced, or improperly applied failing to serve intended purpose | X | |
| - Finished dimensions of reinforcements less than specified by more than 0.125 inch, unless otherwise specified | | X |
| - Slide fastener tape extension on pockets not caught in stitching attaching reinforcement to pocket gusset | | X |
| - Cut edges of snap fastener reinforcements, along edge of bag, interfere with operation of slide fastener | | X |
| t. Snap fasteners - not specified type, size or finish | | X |
| - Studs or sockets on dust curtains or shoe pockets misplaced, failing to effect a smooth and secure closure or causing noticeable distortion after closure | | X |
| - Any fastener not functioning properly, failing to snap closed or open freely; any fastener omitted | X | |
| - Female fasteners on body gusset do not correspond with male fasteners on frame failing to effect a secure attachment | | X |
| - Improperly set, not securely clinched, i.e., components of stud or socket separate when fasteners are snapped and unsnapped; clinched excessively, cutting surrounding fabric | X | |
| u. Frame; stiffener and coat retainer | | |
| - Cracked, warped, delaminated, or construction not as specified: | | |
| - Seriously affecting serviceability | X | |
| - Affecting serviceability but not seriously | | X |
| - Burrs or sharp edges not removed | | X |
| - Eyelets not set through coat retainer webbing | | X |
| - Ends of retainer clamp not securely crimped over edges of upper frame assembly | | X |
| - Coat retainer webbing not assembled as specified | | X |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:41Z
Check the source to verify that this is the current version before use.

TABLE II. General Defects. - Continued

| Defects | Classification | |
|---|---|---|
| | Major | Minor |
| v. Luggage gliders - omitted, damaged, insecurely clinched, or clinched excessively affecting serviceability | X | |
| w. Hanger assembly - any hanger or component assembly omitted | X | |
| - Plywood cracked, warped, or delaminated | X | |
| - Edges of plywood not broken as specified | | X |
| - Hanger snap hook fails to function or engage retainer | | X |
| - End of screw on hook attachment not staked to prevent disassembly | | X |
| - Rivet attaching snap hook to hanger not securely clinched | | X |
| - Hanger hook not detachable from ring on outside of case | | X |
| - Varnish - not as specified | | X |

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Certificate of compliance. When certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification.

4.2 Inspections. Sampling for inspections shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

4.2.1 First article inspection. When required, the preproduction sample submitted in accordance with 3.1 shall be inspected as specified in Table II and Table III for compliance with design construction, workmanship and dimensional requirements.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:41Z
Check the source to verify that this is the current version before use.

TABLE III. Examination of suitcase for dimensional characteristics.

| Defects | Classification | |
|---|---|---|
| | Major | Minor |
| Overall dimension - smaller than nominal dimensions less applicable minus tolerances indicated on the drawing, but not smaller than nominal dimensions less twice the applicable minus tolerance | | X |
| Smaller than nominal dimensions less twice the applicable minus tolerance indicated on the drawing | X | |
| Larger than nominal dimensions and applicable plus tolerance indicated on the drawing | | X |
| Component and location dimension not within specified tolerances | | |
| - Seriously affecting serviceability | X | |
| - Affecting appearance or serviceability, but not seriously | | X |

4.2.2 Component and material inspection. In accordance with 4.1, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase order. In addition, testing shall be performed on components listed in Table IV for characteristics noted. The methods of testing specified in FED-STD-191, wherever applicable and as listed in Table IV shall be followed. Where the determinations per sample unit and results reported are not specified, they shall be as indicated in the applicable test method. All requirements are applicable to the sample unit. The sample unit for testing the coated cloth shall be 3.5 yards full width.

4.2.2.1 Adhesion of coating after water immersion. The test specimens used in dry adhesion of coating that have been separated 3 inches shall be immersed in distilled water at room temperature for 2 hours. After immersion, the specimens shall be blotted dry and the wet adhesion shall be determined on the remainder of the specimen.

4.2.2.2 Resistance to accelerated weathering. The specimens, with the coated side facing the light source shall be exposed as specified in Method 5804 except that the time of exposure shall be 100 hours. At the end of the exposure period, the specimens shall be visually examined to determine if the coating shows signs of blooming, chalking or bleeding. After examination, the specimen shall be folded by hand, face out, sharply upon itself and visually examined for cracking or flaking.

4.2.2.3 Resistance to low temperature. A 1 by 4 inch specimen of the coated cloth with the long dimension warpwise and a 1 by 4 inch specimen of the coated cloth with the long dimension filling wise shall be exposed for 30 minutes at a temperature of minus 10°F ± 5°F. The sample shall then be bent sharply, coated side out, 180 degrees over a 0.125 inch steel rod that has been exposed in the test chamber with the test specimen. The specimen shall then be visually examined for cracking, flaking or separation of the coating from the fabric.

4.2.2.4 Resistance to high temperature. A 2 by 6 inch specimen of the coated cloth shall be exposed for a period of 2 hours in a circulating air oven at a temperature of 160°F ± 2°F. At the end of this period, the coated cloth shall be visually examined for any tackiness, blistering, melting, or softening.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:41Z
Check the source to verify that this is the current version before use.

4.2.2.5 Cold crack resistance. A 1 by 4 inch specimen of the vinyl shall be exposed for 30 minutes at a temperature of minus 10°F ± 5°F. The specimen shall then be bent sharply 180 degrees over a 0.125 inch steel rod that has been exposed in the test chamber with the test specimen. The specimen shall then be visually examined for cracking.

4.2.3 End item examination. Bags shall be examined for conformance to dimensional requirements of the drawing and for satisfactory construction detail. The sample unit shall be one complete bag assembly.

4.2.3.1 In-process inspection. Inspection shall be made at any point or during any phase of the manufacturing process to determine whether operations or subassemblies are accomplished as specified on AF Drawing 52K6757. The Government reserves the right to exclude from consideration for acceptance any material or service for which in-process inspection has indicated nonconformance.

TABLE IV - Test methods.

| Component | Characteristic | Rqmts Para | Test Method | No. of Dets per Sample | Results Reported As |
|---|---|---|---|---|---|
| Coated Cloth | Weight | Table I | 5041 | 5 | To nearest 0.1 oz |
| | Breaking strength | Table I | 5100 | 5 | To nearest 0.1 lb |
| | Tearing strength | Table I | 5134 | 5 | To nearest 0.1 lb |
| | Adhesion of coating | Table I | 5970/ 4.2.2.1 1/ | 5 | To nearest 0.1 lb |
| | Rate of burning | Table I | 5903 2/ | 5 | Pass or fail |
| | Resistance to: | | | | |
| | Accelerated weathering | Table I | 4.2.2.2 | 1 | Pass or fail |
| | Low temperature | Table I | 4.2.2.3 | 1 | Pass or fail |
| | High temperature | Table I | 4.2.2.4 | 1 | Pass or fail |
| Coating Compound Vinyl | Composition | 3.2.1.1 | 3/ | | |
| | Cold crack res | 3.2.8 | 4.2.2.5 | 1 | Pass or fail |

1/ Except 5.1 and 5.3.

5.1 - The coated side shall be the side of the cloth to be tested. The surface shall be wiped clean using a damp cloth dipped in Methyl Ethyl Ketone (MEK) and air dried for 15 minutes. One coating of Bostik 7130* shall be applied to the surface of each specimen and air dried for 15 minutes. A second coat shall be applied to the same coated side and the same coated side of each specimen shall be placed together.

5.3 - The specimens shall be left between the 2 plates for 4 hours. The plates shall then be removed and the specimens air dried for 72 hours. The specimens shall be cut to a 2 X 6 inch test piece.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:41Z
Check the source to verify that this is the current version before use.

* Bostik 7130 may be purchased from:
USM Corporation
Bostik Division
Boston Street
Middleton MA 01949

2/ Except that the test specimen shall be 9 inches in length and the 42 second time for observation of the burning shall include the 12 second burner flame time. During the 42 second period, the specimen shall be observed. Propagation of the flame the length of the test specimen at any time during the 42 second period shall be recorded as a failure. Five specimens shall be tested in the warp direction and the results reported individually as pass or fail.

3/ A certificate of compliance shall be submitted for the stated requirement.

4.2.3.2 Classification of defects. Defects shall be classified in accordance with lists shown in Table II and Table III.

4.2.4 Examination of preparation for delivery requirements. Examination shall be made to determine that packaging, packing and marking are in compliance with the requirements of Section 5. Defects shall be scored as shown in Table V. The sample unit shall be one suitcase completely wrapped or bagged or one shipping container fully prepared for delivery. The lot shall be the number of completely wrapped or bagged suitcases or shipping containers offered for inspection at one time.

TABLE V. Examination of preparation for delivery.

| Examine | Defect |
|---|---|
| Marking | Omitted, incorrect, illegible, of improper size, location, sequence or method of application |
| Materials | Any component missing<br>Any component damaged |
| Workmanship | Inadequate application of components, such as incomplete closure or seal<br>Containers bulging or distorted |

4.3 AQL's and inspection levels. The inspection levels and acceptable quality levels (AQL's) expressed in defects per hundred units shall be as follows:

| Examination | Inspection Level | AQL's |
|---|---|---|
| For defects applicable to material defects (Table II) | II | 2.5 Major defects per hundred units<br>10.0 Total defects per hundred units |
| For defects applicable to dimensional characteristics (Table IV) | S-3 | 4.0 Major defects per hundred units<br>10.0 Total defects per hundred units |
| For defects applicable to preparation of delivery defects in Table V | S-2 | 2.5 defects per hundred units |



Source: https://assist.dla.mil -- Downloaded: 202610-23T09:41Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation and packaging. Preservation and packaging shall be Level A or C as specified (see 6.2).

5.1.1 Level A. Each bag shall be completely wrapped with a sheet or bag of polyethylene film. The wrap or bag closure shall be secured with pressure sensitive tape.

5.1.2 Level C. Each bag shall be preserved and packaged in a manner that will afford adequate protection against corrosion, deterioration and damage from the supply source to the first receiving activity. This may conform to the supplier's commercial practice if it meets the requirements of this level.

5.2 Packing. Packing shall be Level A, B or C as specified (see 6.2).

5.2.1 Level A. Each bag preserved and packaged as specified in 5.1.1 shall be packed in a weather-resistant container conforming to PPP-B-636, Grade W5c. Waterproofing and cushioning shall be in accordance with MIL-STD-1186. Closure and strapping shall be in accordance with the Appendix of PPP-B-636. Containers shall be of minimum tare and cube and of uniform size and shape.

5.2.2 Level B. Level B packing shall be the same as level A except that containers shall be domestic type, Grade 175, CF, SW and waterproofing is not required.

5.2.3 Level C. Bags preserved and packaged as specified in 5.1.2 shall be packed in a manner that will afford adequate protection against damage during shipment from the supply source to the first receiving activity. Containers shall conform to Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

5.3 Marking. In addition to any special marking required by the contract or order, interior packages and exterior containers shall conform to MIL-STD-129.

6. NOTES

6.1 Intended use. The clothing suitcase is to be used by flight crews and other personnel to carry items of personal property while traveling.

6.2 Ordering data.

a. Title, number and date of this specification.

b. When a first article is required (see 3.1).

c. Selection of applicable levels of packaging and packing (see 5.1 and 5.2)

6.3 Sources of pebble grain design (see 3.3.1). Satisfactory pebble grain design of the exterior fabric may be obtained from Uniroyal Plastics Products, Division of Uniroyal Inc., P.O. Box 488, Port Clinton OH 43452, Roehlen Engraving Work, 701 Jefferson Road, Rochester NY 14623, or Consolidated Engravers Corporation, 311 E. 12th Street, Charlotte NC 28206.

*6.4 Reclaimed materiels. The use of reclaimed materiels shall be encouraged to the maximum extent possible.

6.5 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:41Z
Check the source to verify that this is the current version before use.

requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Air Force - 99

Review activity:
Air Force - 99

Preparing activity:
Air Force - 99

(Project 8460-F057)



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:41Z
Check the source to verify that this is the current version before use.

FOLD

HQ AFLC CASO/LODS
Federal Center
Battle Creek MI 49016

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID
DEPARTMENT OF AIR FORCE
DOD-318




HQ AFLC CASO/LODS
Federal Center
Battle Creek MI 49016

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:41Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 PREVIOUS EDITION WILL BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:41Z
Check the source to verify that this is the current version before use.