INCH-POUND

MIL-P-60608A
AMENDMENT 4
31 July 1998
SUPERSEDING
AMENDMENT 3
31 July 1987

MILITARY SPECIFICATION

PROJECTILE, 20MM, TARGET PRACTICE - TRACER
M221; METAL PARTS

MIL-P-60608 was inactivated after 1 November 1995 for new design.

This amendment forms a part of MIL-P-60608A, dated 25 February 1972, and is approved for use by all Departments and Agencies of the Department of Defense.

Throughout the specification, delete "M221" and substitute "M221" and M221B1".

PAGE 2

2.1, Drawings: Delete "D7259149 - Body, Nose and Rotating Band Assembly, Unpainted" and substitute "D7259149 - Projectile, 20mm, TP-T, M221 and M221B1, Unpainted."

Delete: "D7259150 - Body and Rotating Band Assembly" and substitute "D7259150 - Body and Rotating Band, Projectile, 20mm, TP-T, M221 and M221B1."

Delete: "D7259152 - Body" and substitute "D7259152 - Body, Projectile, 20mm, TP-T, M221 and M221B1."

PAGE 7

4.4.3.3, under Major: Delete 105 and substitute the following:

"105. Score missing Visual"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:48Z
Check the source to verify that this is the current version before use.

Under Minor: Delete 209 and substitute the following:

"209. Diameter, body cavity, max. (Machined Body) Gage"

PAGE 8

4.4.3.4, under Major: Delete 108 and substitute the following:

"108. Runout, metering disc seat with bourrelet Gage"

PAGE 13

4.5.8, Delete "The sample assemblies….. mean velocity of 3540 ± 25 fps" and substitute the following:

"The sample metal part projectiles may be either inert or live tracer charged. The sample projectiles shall be loaded and assembled into cartridges as specified by Dwgs. 7259147 and 7259146 with the following exceptions:

a. Inert tracer charged projectiles/cartridges:

(1) Inert material shall be used to simulate the weight of the igniter/tracer compositions.

(2) Metering disc, part no. 10542428, shall be assembled over the tracer cavity.

(3) The seal, part no. 10542429, placed over the simulated igniter/tracer compositions may be omitted.

(4) A propellant shall be used which will produce a mean instrumental velocity of 3540 ± 25 fps at a distance of 78 feet.

b. Live tracer charged projectile/cartridges:

(1) There shall be no exception to Dwg. 7259147.

(2) A propellant shall be used which will produce a mean instrumental velocity of 3540 ± 25 fps at a distance of 78 feet."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:48Z
Check the source to verify that this is the current version before use.

* 4.5.8, Add the following:

"Customers, through the procuring activity, may modify this requirement and base acceptance on firing bursts of 50 shots in a M61 gun."

The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army-AR
Air Force-99

Review activities:
Air Force-99

Preparing activity:
Army-AR

(Project 1305-0202)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:48Z
Check the source to verify that this is the current version before use.