NOTE: The document identifier and heading have been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

INCH-POUND
MIL-PRF-123/2C
AMENDMENT 1
28 February 1997

PERFORMANCE SPECIFICATION SHEET
CAPACITORS, FIXED, CERAMIC DIELECTRIC,
(TEMPERATURE STABLE AND GENERAL PURPOSE),
HIGH RELIABILITY, LEADED
STYLE CKS06

This amendment forms a part of MIL-C-123/2C, dated 28 September 1994 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

FIGURE 1, case height, delete ".290 MAX" and substitute ".290 ± 0.010 "

PAGE 3

TABLE I, add the following additional entries:

"

PIN	Capacitance	Capacitance tolerance	Voltage-temperature limits	Rated voltage
	pF			volts
M123A02BXB564KC	560,000	K	BX	50
M123A02BXB684KC	680,000	K	BX	50
M123A02BXB824KC	820,000	K	BX	50
M123A02BXB105KC	1,000,000	K	BX	50

"

Requirements, following marking, add:

"Extension of qualification option: For MIL-C-123/2 manufacturers that are currently qualified to a subset of the full capacitance range for a given voltage rating and voltage-temperature characteristic; qualification to additional capacitance values may be granted based upon successfully meeting MIL-STD-790 requirements, in-process inspection, and group A and group B inspections for those values. This qualification option is restricted to a given voltage rating and voltage-temperature characteristic. The highest capacitance value qualified can be the basis for qualifying lower capacitance values of the same voltage rating and voltage temperature characteristic."

Custodians:
Air Force - 19
NASA - NA
Navy - EC

Review activities:
Army - CR
Air Force - 85

Preparing activity:
DLA - CC

(Project 5910 - 1941)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T05:09Z
Check the source to verify that this is the current version before use.