MIL-I-6839B
AMENDMENT 3
12 September 1986
SUPERSEDING
AMENDMENT 2
26 JUNE 1979

MILITARY SPECIFICATION

INDICATOR, SYMBOL INDICATING, LANDING GEAR POSITION

This amendment forms a part of Military Specification MIL-I-6839B, dated 29 December 1965, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Delete title and substitute the above title.

* 2.1 Under SPECIFICATIONS Federal delete "QQ-P-416" and add "PPP-B-601--Boxes, Wood, Cleated Plywood" and "PPP-B-636--Box, Shipping Fiberboard".

* Under SPECIFICATIONS Military delete "MIL-E-5272" and "MIL-P-7936". Add "DOD-D-1000--Drawings, Engineering and Associated Lists".

Add boxed paragraph to bottom center of page.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Oklahoma City Air Logistics Center/MMEDO, Tinker AFB OK 73145-5990 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

PAGE 2

* Under SPECIFICATIONS Military delete "MIL-D-70327" and add "MIL-C-83488--Coating, Aluminum, Ion Vapor Deposited".

* Under STANDARDS Military delete "MS33586". Add "MIL-STD-810C--Environmental Test Methods and Engineering Guidelines" and " MIL-STD-889--Dissimilar Metals".

* Add:
"2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

ASTM-D-3951 Packaging, Commercial

(Application for copies should be addressed to: ASTM, 1916 Race St, Philadelphia PA 19103.)

AMSC N/A FSC 6610
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T07:31Z
Check the source to verify that this is the current version before use.

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

PAGE 3

* Add:
"3.3.1.1 Reclaimed material. The use of reclaimed materials shall be encouraged to the maximum extent possible."

3.3.2.1 Line 1: Delete "MS33586" and add "MIL-STD-889".

PAGE 5

3.6 Line 3: Delete "MIL-D-70327" and add "DOD-D-1000".

PAGE 6

* 3.10.2 Delete and add:
"3.10.2 Steel parts. Steel parts shall be coated with ion vapor deposited aluminum, where practicable, in accordance with MIL-C-83488, type I or II as applicable and of a class that is adequate to achieve the degree of protection required. Other protective coating, in lieu of MIL-C-83488, may be used if demonstrated to be satisfactory and approved by the preparing activity. Cadmium plating must be avoided when satisfactory alternative processes can be used."

PAGE 10

4.6.9 Line 3: Delete "300 to 3000 cycles per minute" and add "5 to 50 cycles per second".

PAGE 11

* 4.6.10 Line 1: Delete "Procedure IV of MIl-E-5272: and add "Method 516.2, Procedure I of MIL-STD-810C".

PAGE 12

* 4.6.15 Delete and add:
"4.6.15 Vibration failure. The indicator shall be subjected to a vibration test in accordance with Method 514.2, Procedure I, Part I, utilizing Table 514.2-II and Figure 514/2-2, Curve C , Category b.1 of MIL-STD-810C. The test shall last for a period of three hours. After vibration, the indicator shall be subjected to and shall meet the requirements of the tests specified in 4.6.2 and 4.6.3."

* 4.6.16 Line 2: Delete "MIL-E-5272, Procedure I" and add "MIL-STD-810C, Method 509.1".

* 4.6.17 Delete and add:
"4.6.17 Sealing. The indicator shall be subjected to Immersion Tests, Method 512.1, Procedures III of MIL-STD-810C. The absolute pressure of the air above liquid shall be reduced one inch of mercury for one minute, then increased 2.5 inches for one hour."

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T07:31Z
Check the source to verify that this is the current version before use.

Add the following new paragraphs 4.7, 4.7.1, and 4.7.2:

"4.7 Packaging inspection.

4.7.1 Quality conformance. The inspection of the preservation-packaging and interior package marking shall be in accordance with group A and B quality conformance inspection requirements, section 4 of MIL-P-116. The sampling and inspection of the packing and marking for shipment and storage shall be in accordance with the quality assurance provisions of applicable container specification and the marking requirements of MIL-STD-129.

4.7.2 First article. When the unit container is capable of serving as the shipping container, First Article inspection and rough handling tests, as outlined in section 4 of MIL-P-116, shall be accomplished followed by a functional test of the unit to insure freedom from operational malfunction."

Delete section 5 in its entirety and substitute the following new section:

"5 PACKAGING

5.1 Preservation-packaging. Preservation-packaging shall be level A or C as specified.

5.1.1 Level A.

5.1.1.1 Cleaning. Unit shall be cleaned in accordance with process C-1 of MIL-P-116.

5.1.1.2 Drying. Immediately after cleaning, the unit shall be dried following any one or combination of the drying procedures of MIL-P-116. The drying procedures employed shall not be injurious to the unit.

5.1.1.3 Preservation application. Not required.

5.1.1.4 Unit packaging. Unless otherwise specified by the contracting activity, each unit shall be packaged in quantity unit packs of one each in accordance with method 1C-1 of MIL-P-116. Overbox each completed pack in a PPP-B-636 fiberboard, weather-resistant class box. Cushioning material between bag and container shall be of a type, density and thickness that will protect the unit from impact shock damage when tested as specified in paragraph 4.7 of this specification.

5.1.2 Level C. Units shall be cleaned, dried, and individually packaged in a manner that will afford adequate protection against corrosion, deterioration and physical damage during shipment from supply source to the first receiving activity.

* 5.1.3 Industrial. The industrial preservation of indicators shall be in accordance with ASTM-D-3951-82.

5.2 Packing. Packing shall be level A, B, C, or Industrial as specified (see 6.2).

5.2.1 Level A. Units packed as specified in 5.1 shall be packed in shipping containers conforming to specification PPP-B-636, weather-resistant. Closure and

Source: https://assist.dla.mil Downloaded: 2026-10-17T07:31Z
Check the source to verify that this is the current version before use.

reinforcing requirements shall be in accordance with the appendix of PPP-B-636. For the Army, specification PPP-B-601 plywood box shall be used for the shipping container.

5.2.2 Level B. Units packaged as specified in 5.1 shall be packed in shipping containers conforming to specification PPP-B-636, class domestic. closure and reinforcing requirements shall be in accordance with the appendix of PPP-B-636. For the Army, the shipping containers shall conform to specification PPP-B-636, class weather-resistant.

5.2.3 Level C. Packaged units shall be packed in shipping containers in a manner that will afford adequate protection against damage during direct domestic shipment from the supply source to the first receiving activity. These packs shall conform to applicable carrier rules and regulations.

* 5.2.4 Industrial. The packaged indicators shall be packed in accordance with ASTM-D-3951-82.

5.3 Marking. In addition to any special marking required by the contract or order, each unit package and shipping container shall be marked in accordance with MIL-STD-129. The nomenclature shall be: "Indicator, Position, Leanding Gear."

PAGE 13

* 6.3 Delete last sentence and add: "The activity responsible for the Qualified Products List is OC-ALC/MMEDO, Tinker AFB, OK 73145-5990 and information pertaining to qualification or products may be obtained from that activity".

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modification, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Air Force - 99
Army - AV
Navy - AS

Preparing Activity:
Air Force - 71

Project Number:
6610 - 0114

Reviewer:
Air Force - 11
Army - MI

User:
Marine Corps - MC

☆U.S. GOVERNMENT PRINTING OFFICE: 1986 — 605-036/44808

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T07:31Z
Check the source to verify that this is the current version before use.