INCH-POUND
MIL-PRF-6855/2A
15 June 2009
SUPERSEDING
MIL-R-6855/2
16 February 1987

# PERFORMANCE SPECIFICATION SHEET

# RUBBER, SYNTHETIC, STRIP (OR TAPE)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirement for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-6855.

REQUIREMENTS:

Part numbers:

Part numbers shall consist of the prefix M, specification number, specification sheet number, and a six-digit dash number assigned using tables I, II, III and IV herein, as shown in the following example:

| **M** | **6855** | **/** | **2** | **-** | **XX** | **X** | **X** | **XX** |
|---|---|---|---|---|---|---|---|---|
| Prefix for Military Specification | Specification Number | | Specification Sheet Number | | Two-Digit Classification Number (table I). | One-Digit Thickness Letter (table II). | One-Digit Length Number (table III). | Two-Digit Width Number (table IV). |

Example: M6855/2-XXXXXX

Dimensional tolerances:

Tolerances of MIL-PRF-6855, tables I and II, shall apply to strip width and thickness respectively. Tolerance for strip length shall be -0 percent, +3 percent of the specified length.

Surface finish:

All synthetic rubber strip surfaces shall be smooth and free from cloth imprint.

VERIFICATION:

Inspection and test of synthetic rubber strips shall be in accordance with MIL-PRF-6855, Section 4, VERIFICATION.



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T07:34Z
Check the source to verify that this is the current version before use.

TABLE I. Type, class, grade.

| Classification Number | Classification of Requirements | | |
|---|---|---|---|
| 01 | | Class 1 | Grade 30 |
| 02 | | Class 1 | Grade 40 |
| 03 | | Class 1 | Grade 50 |
| 04 | | Class 1 | Grade 60 |
| 05 | | Class 1 | Grade 70 |
| 06 | | Class 1 | Grade 80 |
| 07 | Type A | Class 2 | Grade 30 |
| 08 | Type A | Class 2 | Grade 40 |
| 09 | Type A | Class 2 | Grade 50 |
| 10 | Type A | Class 2 | Grade 60 |
| 11 | Type A | Class 2 | Grade 70 |
| 12 | Type A | Class 2 | Grade 80 |
| 13 | Type B | Class 2 | Grade 30 |
| 14 | Type B | Class 2 | Grade 40 |
| 15 | Type B | Class 2 | Grade 50 |
| 16 | Type B | Class 2 | Grade 60 |
| 17 | Type B | Class 2 | Grade 70 |
| 18 | Type B | Class 2 | Grade 80 |
| 19 | | Class 3 | Grade 30 |
| 20 | | Class 3 | Grade 40 |
| 21 | | Class 3 | Grade 50 |
| 22 | | Class 3 | Grade 60 |
| 23 | | Class 3 | Grade 70 |
| 24 | | Class 3 | Grade 80 |
| 25 | Type A | Class 4 | Grade 30 |
| 26 | Type A | Class 4 | Grade 40 |
| 27 | Type A | Class 4 | Grade 50 |
| 28 | Type A | Class 4 | Grade 60 |
| 29 | Type A | Class 4 | Grade 70 |
| 30 | Type A | Class 4 | Grade 80 |
| 31 | Type B | Class 4 | Grade 30 |
| 32 | Type B | Class 4 | Grade 40 |
| 33 | Type B | Class 4 | Grade 50 |
| 34 | Type B | Class 4 | Grade 60 |
| 35 | Type B | Class 4 | Grade 70 |
| 36 | Type B | Class 4 | Grade 80 |
| 37 | | Class 5 | Grade 30 |
| 38 | | Class 5 | Grade 40 |
| 39 | | Class 5 | Grade 50 |
| 40 | | Class 5 | Grade 60 |
| 41 | | Class 5 | Grade 70 |
| 42 | | Class 5 | Grade 80 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T07:34Z
Check the source to verify that this is the current version before use.

TABLE II. Strip thickness – T.

| Strip Thickness Letter | T (Inches) |
|---|---|
| A | 0.015 |
| E | 0.031 |
| H | 0.062 |
| J | 0.093 |
| L | 0.125 |
| N | 0.187 |
| P | 0.250 |
| R | 0.375 |
| T | 0.500 |
| W | 0.625 |
| Y | 1.000 |

TABLE III. Strip length – L.

| Strip Length Number | L (Inches) |
|---|---|
| 1 | 12.000 |
| 2 | 24.000 |
| 3 | 36.000 |
| 4 | 60.000 |
| 5 | 144.000 |
| 6 | 300.000 |
| 7 | 900.000 |

TABLE IV. Strip width – W.

| Strip Width Number | W (Inches) |
|---|---|
| 02 | 0.250 |
| 04 | 0.500 |
| 06 | 0.750 |
| 08 | 1.000 |
| 10 | 1.250 |
| 12 | 1.500 |
| 14 | 1.750 |
| 16 | 2.000 |
| 18 | 3.000 |
| 20 | 4.000 |
| 22 | 5.000 |
| 24 | 6.000 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T07:34Z
Check the source to verify that this is the current version before use.

| Metric Conversion Chart[1/] | | | | |
|---|---|---|---|---|
| **Inch** | **mm** | | **Inch** | **mm** |
| 0.015 | 0.38 | | 1.750 | 44.45 |
| 0.031 | 0.79 | | 2.000 | 50.80 |
| 0.062 | 1.57 | | 3.000 | 76.20 |
| 0.093 | 2.36 | | 4.000 | 101.60 |
| 0.125 | 3.18 | | 5.000 | 127.00 |
| 0.187 | 4.75 | | 6.000 | 152.40 |
| 0.250 | 6.35 | | 12.000 | 304.80 |
| 0.375 | 9.53 | | 24.000 | 609.60 |
| 0.500 | 12.70 | | 36.000 | 914.40 |
| 0.625 | 15.88 | | 60.000 | 1524.00 |
| 0.750 | 19.05 | | 144.000 | 3657.60 |
| 1.000 | 25.40 | | 300.000 | 7620.00 |
| 1.250 | 31.75 | | 900.000 | 22860.00 |
| 1.500 | 38.10 | | | |
| NOTE:<br>[1/] See general note 2. | | | | |

GENERAL NOTES TO TABLES:

1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Use of this specification sheet for US Army Communications-Electronics Command is restricted to Class 4 and Class 5.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army – MR
Navy – SH
Air Force – 11
DLA – CC

Preparing Activity:
Navy – SH
(Project 4720-2008-019)

Review Activities:
Army – AR, AT, AV, CE, CR, MI
Navy – AS, OS, YD
Air Force – 71, 99
DLA –GS, IS

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T07:34Z
Check the source to verify that this is the current version before use.