INCH-POUND
MIL-PRF-6855/4A
w/AMENDMENT 1
29 June 2022
SUPERSEDING
MIL-PRF-6855/4A
15 June 2009

PERFORMANCE SPECIFICATION SHEET

RUBBER, SYNTHETIC, TUBING

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-6855.

REQUIREMENTS:

Part numbers:

Part numbers shall consist of the prefix M, specification number, specification sheet number, and a six-digit dash number assigned using tables I, IIA, IIB, IIC, and III herein, as show in the following example:

M	**6855**	**/**	**4**	**-**	**XX**	**XXX**	**X**
Prefix for Military Specification	Specification Number		Specification Sheet Number		Two-Digit Classification Number (table I).	Three-Digit Size Number (table IIA, IIB, or IIC).	One-Digit Length Number (table III).

Example: M6855/4-XXXXXX

Dimensional tolerances:

Tolerances for tubing inside diameter and wall thickness shall be in accordance with tables IIA, IIB, and IIC herein, as applicable. Tolerance for tubing length shall be -0 percent, +3 percent of the specified length.

Surface finish:

All synthetic rubber tubing surfaces shall be smooth and free from pin holes, flash, or any other imperfections which may impair serviceability.

VERIFICATION:

Inspection and test of synthetic rubber tubing shall be in accordance with MIL-PRF-6855, Section 4, VERIFICATION.

AMSC N/A FSC 4720

DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T07:34Z
Check the source to verify that this is the current version before use.

TABLE I. Type, class, grade.

Classification Number	Classification of Requirements		
01		Class 1	Grade 30
02		Class 1	Grade 40
03		Class 1	Grade 50
04		Class 1	Grade 60
05		Class 1	Grade 70
06		Class 1	Grade 80
07	Type A	Class 2	Grade 30
08	Type A	Class 2	Grade 40
09	Type A	Class 2	Grade 50
10	Type A	Class 2	Grade 60
11	Type A	Class 2	Grade 70
12	Type A	Class 2	Grade 80
13	Type B	Class 2	Grade 30
14	Type B	Class 2	Grade 40
15	Type B	Class 2	Grade 50
16	Type B	Class 2	Grade 60
17	Type B	Class 2	Grade 70
18	Type B	Class 2	Grade 80
19		Class 3	Grade 30
20		Class 3	Grade 40
21		Class 3	Grade 50
22		Class 3	Grade 60
23		Class 3	Grade 70
24		Class 3	Grade 80
25	Type A	Class 4	Grade 30
26	Type A	Class 4	Grade 40
27	Type A	Class 4	Grade 50
28	Type A	Class 4	Grade 60
29	Type A	Class 4	Grade 70
30	Type A	Class 4	Grade 80
31	Type B	Class 4	Grade 30
32	Type B	Class 4	Grade 40
33	Type B	Class 4	Grade 50
34	Type B	Class 4	Grade 60
35	Type B	Class 4	Grade 70
36	Type B	Class 4	Grade 80
37		Class 5	Grade 30
38		Class 5	Grade 40
39		Class 5	Grade 50
40		Class 5	Grade 60
41		Class 5	Grade 70
42		Class 5	Grade 80

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T07:34Z
Check the source to verify that this is the current version before use.

TABLE IIA. Light wall tubing sizes.

Tubing Size Number	Minimum Inside Diameter (Inches)	Maximum Inside Diameter (Inches)	Nominal Inside Diameter (Inches)	Minimum Wall Thickness (Inches)	Maximum Wall Thickness (Inches)	Nominal Wall Thickness (Inches)
L02	0.109	0.141	0.125	0.031	0.047	0.039
L04	0.109	0.141	0.125	0.047	0.063	0.055
L06	0.141	0.172	0.156	0.047	0.063	0.055
L08	0.172	0.203	0.188	0.047	0.063	0.055
L10	0.234	0.266	0.250	0.047	0.079	0.063
L12	0.297	0.328	0.312	0.047	0.079	0.063
L14	0.359	0.391	0.375	0.047	0.079	0.063
L16	0.422	0.453	0.438	0.047	0.079	0.063
L18	0.484	0.516	0.500	0.047	0.079	0.063
L20	0.547	0.578	0.562	0.047	0.079	0.063
L22	0.609	0.641	0.625	0.047	0.079	0.063
L24	0.734	0.766	0.750	0.047	0.079	0.063
L26	0.859	0.891	0.875	0.047	0.079	0.063
L28	0.984	1.016	1.000	0.047	0.079	0.063

TABLE IIB. Heavy wall tubing sizes.

Tubing Size Number	Minimum Inside Diameter (Inches)	Maximum Inside Diameter (Inches)	Nominal Inside Diameter (Inches)	Minimum Wall Thickness (Inches)	Maximum Wall Thickness (Inches)	Nominal Wall Thickness (Inches)
H02	0.109	0.141	0.125	0.094	0.110	0.102
H04	0.141	0.172	0.156	0.094	0.110	0.102
H06	0.172	0.203	0.188	0.094	0.110	0.102
H08	0.234	0.266	0.250	0.109	0.141	0.125
H10	0.297	0.328	0.312	0.109	0.141	0.125
H12	0.359	0.391	0.375	0.078	0.109	0.094
H14	0.359	0.391	0.375	0.109	0.141	0.125
H16	0.422	0.453	0.438	0.109	0.141	0.125
H18	0.484	0.516	0.500	0.109	0.141	0.125
H20	0.547	0.578	0.562	0.109	0.141	0.125
H22	0.609	0.641	0.625	0.109	0.141	0.125
H24	0.734	0.766	0.750	0.109	0.141	0.125
H26	0.859	0.891	0.875	0.109	0.141	0.125
H28	0.984	1.016	1.000	0.109	0.141	0.125
H30	1.234	1.266	1.250	0.109	0.141	0.125
H32	1.484	1.516	1.500	0.133	0.179	0.156
H34	1.734	1.766	1.750	0.133	0.179	0.156

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T07:34Z
Check the source to verify that this is the current version before use.

TABLE IIC. Extra heavy wall tubing sizes.

Tubing Size Number	Minimum Inside Diameter (Inches)	Maximum Inside Diameter (Inches)	Nominal Inside Diameter (Inches)	Minimum Wall Thickness (Inches)	Maximum Wall Thickness (Inches)	Nominal Wall Thickness (Inches)
E02	0.109	0.141	0.125	0.156	0.219	0.188
E04	0.141	0.172	0.156	0.156	0.219	0.188
E06	0.172	0.203	0.188	0.156	0.219	0.188
E08	0.234	0.266	0.250	0.156	0.219	0.188
E10	0.297	0.328	0.312	0.156	0.219	0.188
E12	0.359	0.391	0.375	0.219	0.281	0.250
E14	0.422	0.453	0.438	0.219	0.281	0.250
E16	0.484	0.516	0.500	0.156	0.219	0.188
E18	0.484	0.516	0.500	0.219	0.281	0.250

TABLE III. Tubing length – L.

Tubing Length Number	L (Inches) (Feet)
3	72.000 (6)
5	144.000 (12)
7	300.000 (25)
9	1800.000 (150)
B	3600.000 (300)
K	7200.000 (600)

Metric Conversion Chart 1/

Inch	mm	Inch	mm	Inch	mm	Inch	mm
0.031	0.79	0.179	4.55	0.484	12.29	1.000	25.40
0.039	0.99	0.188	4.78	0.500	12.70	1.016	25.81
0.047	1.19	0.203	5.16	0.516	13.11	1.234	31.34
0.055	1.40	0.219	5.56	0.547	13.89	1.250	31.75
0.063	1.60	0.234	5.94	0.562	14.27	1.266	32.16
0.078	1.98	0.250	6.35	0.578	14.68	1.484	37.69
0.079	2.01	0.281	7.14	0.609	15.47	1.500	38.10
0.094	2.39	0.297	7.54	0.625	15.88	1.516	38.51
0.102	2.59	0.312	7.92	0.641	16.28	1.734	44.04
0.109	2.77	0.328	8.33	0.734	18.64	1.750	44.45
0.110	2.79	0.359	9.12	0.750	19.05	1.766	44.86
0.125	3.18	0.375	9.53	0.766	19.46	72.000	1828.80
0.133	3.38	0.391	9.93	0.859	21.82	144.000	3657.60
0.141	3.58	0.422	10.72	0.875	22.23	300.000	7620.00
0.156	3.96	0.438	11.13	0.891	22.63	1800.000	45720.00
0.172	4.37	0.453	11.51	0.984	24.99		

NOTE:
1/ See general note 2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T07:34Z
Check the source to verify that this is the current version before use.

GENERAL NOTES TO TABLES:

1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. DELETED.

AMENDMENT NOTATIONS: The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

CONCLUDING MATERIAL

Custodians:
Army – MR
Navy – SH
Air Force – 20
DLA – CC

Review activities:
Army – AR, AT, AV, CE, CR, MI
Navy – AS, OS, YD
Air Force – 71
DLA – GS

Preparing activity:
Navy – SH
(Project 4720-2022-007)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T07:34Z
Check the source to verify that this is the current version before use.