MILITARY SPECIFICATION

ENGINES, AIRCRAFT, RECIPROCATING, PREPARATION
FOR SHIPMENT AND STORAGE OF

This amendment forms a part of Military Specification MIL-E-6058B, dated 24 November 1971, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1 Under SPECIFICATIONS, Federal, after "P-D-680", insert: "BB-N-411 Nitrogen, Technical". Change the title of "PPP-T-60" to read: "Tape, Packaging, Waterproof".

PAGE 2

2.1 Under SPECIFICATIONS, Military, change the title of "MIL-C-5584" to read "Containers, Shipping, and Storage, Metal Reusable".

PAGE 15

3.4.3(g) Delete in its entirety and substitute:

"(g) Two lid bolts, spaced 180 degrees apart, shall be replaced with two MS bolts, each with a cotterpin hole drilled in it, for the eventual installation of two tamperproof lead seals."

Add the following new paragraphs:

"3.4.4 Pressurization of shipping container with dry nitrogen. The gasket and lid shall be installed and all fastenings shall be tightened to an even tension. Containers that are hermetically sealed or designed to be pressurized in service shall be purged and filled as follows:

(a) Pressurize to 7.5 ± .5 psi using high purity nitrogen gas BB-N-411 (Type I, Grade A or B, Class 1).
(b) Allow the container to stand 30 minutes (minimum), then bleed the container to atmospheric pressure.
(c) Repeat steps (a) and (b).
(d) Pressurize to 5 ± 1 psi using high purity nitrogen, BB-N-411.
(e) Check for leaks by brushing a soap solution over all seams and closure joints while observing for bubbles which are blown away or increase in size and break. No leaks permitted.
(f) Attach two tamperproof lead seals conforming to MS 51938 to the cotterpin holes drilled in the lid attaching bolts."

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:07Z
Check the source to verify that this is the current version before use.

4.5 Delete in its entirety and substitute:

"4.5 Leak test.

4.5.1 Pressurized containers. Pressurized containers (see 3.4.4) shall be tested for leaks by applying a soap solution to all joints and weld seams and observing for bubbles which are blown away or increase in size and break.

4.5.2 Nonpressurized containers. Nonpressurized containers shall be checked for leaks by pressurizing to 5 ± 1 psi and following the procedure in 4.5.1. If necessary, the pressure relief valve shall be removed and the aperture blocked off. At the conclusion of the test, the internal pressure shall be vented off to equalize internal and external pressures."

Custodians:
Army - AV
Navy - AS
Air Force - 99

Review Activities:
Army - CR, SM, ME
Air Force - 11

Preparing Activity:
Navy - AS
(Project No. PACK-0567)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:07Z
Check the source to verify that this is the current version before use.