SEE SECTION	I	I	I	I	I	I	I	I	I	I	I
NO. BLADES	4	6	2	2	3	6	4	6	3	6	6
BLADE SIZE	1	1	1-1/2	2	2	1	1-1/2	1-1/2	2	2	3
SHAFT SIZE	4[illegible]	4[illegible]	4[illegible]	4[illegible]	4[illegible]	5[illegible]	5[illegible]	5[illegible]	5	6	6[illegible]
A DIA. +.003 -.000	3.878	3.878	4.190	4.503	4.503	3.878	4.19[illegible]	4.19[illegible]	4.503	4.503	5.[illegible]03
B DIA. +.002 -.000	4.247	4.247	4.622	4.997	4.997	4.247	4.622	4.6[illegible]2	4.997	4.997	5.622
C DIA +.010 -.000	3.437	3.437	3.750	3.937	3.937	3.437	3.75[illegible]	3.75[illegible]	3.937	3.937	4.39[illegible]
D +.002 -.000	.875	.875	1.062	1.250	1.250	.875	1.[illegible]62	1.[illegible]62	1.250	1.250	1.375
E	13/16	13/16	15/16	1-1/16	1-1/16	13/16	15/16	15/16	1-1/16	1-1/16	1-3/16
F ±.010	3.125	4.6875	2.937	3.187	3.187	4.6875	3.375	5.250	3.500	5.750	6.375
G ±.005	7.750	9.312	8.1875	9.062	9.062	9.312	8.625	10.500	9.375	11.625	12.875
H DIA. +.000 -.005	3.875	3.875	3.875	3.875	3.875	4.562	4.562	4.562	4.562	5.562	5.562
J DIA. +.000 -.005	3.875	3.875	3.875	3.875	3.875	4.625	4.625	4.625	4.625	5.500	5.500
K	6-19/32	6-19/32	6-19/32	6-19/32	6-19/32	6-25/32	6-25/32	6-25/32	6-25/32	8-1/16	8-1/16
L	6	6	6	6	6	6-1/8	6-1/8	6-1/8	6-1/8	7-1/4	7-1/4
M DIA.	5	5	5-1/2	5-7/8	5-7/8	5	5-1/2	5-1/2	5-7/8	6-1/16	6-7/8
N	4-9/32	4-9/32	4-5/32	4-11/32	4-11/32	4-3/32	3-31/32	3-31/32	3-31/32	5-1/16	5-1/16
P DIA.	4-1/4	4-1/4	4-5/8	5	5	4-1/4	4-5/8	4-5/8	5	5	5-5/8
Q	1-3/4	1-1/2	1-5/8	1-5/8	1-5/8	1-3/4	1-5/8	1-5/8	1-5/8	1-5/8	1-13/16
R DIA. +.005 -.002	3.133	3.133	3.133	3.133	3.133	3.812	3.812	3.812	3.812	SAME AS CONTROLLABLE PITCH HUBS SEE AND10529	
S DIA. +.005 -.002	2.881	2.881	2.881	2.881	2.881	3.562	3.562	3.562	3.562		
T ±.001	.306	.306	.306	.306	..306	.377	.377	.377	.377		
U DIA.	—	—	—	—	—	—	—	—	—	—	—
X	2-17/32	2-17/32	2-17/32	2-17/32	2-17/32	2-15/16	2- 5/16	2- 5/16	2- 5/16	3-5/32	3-5/32
Y DIA.	3-5/32	3-5/32	3-5/32	3-5/32	3-5/32	3-27/32	3-27/32	3-27/32	3-27/32	4-27/32	4-27/32
R1 RAD +.005	—	—	—	—	—	—	—	—	—	—	—
R2 RAD	—	—	—	—	—	—	—	—	—	—	TEST
R3 RAD ±1/4	—	—	—	—	—	—	—	—	—	—	
R4 RAD	—	—	—	—	—	—	—	—	—	—	CLUB
Z	7-1/2	7-1/2	7-1/2	7-1/2	7-1/2	7-11/16	7-11/16	7-3/4	7-11/16	9-1/32	9-3/32
AA	9/16	9/16	9/16	9/16	9/16	9/16	9/16	9/16	9/16	9/16	9/16
BB DIA.	4-1/8	4-1/8	4-1/8	4-1/8	4-1/8	4-3/4	4-3/4	4-3/4	4-3/4	5-3/4	5-3/4
CC DIA.	3-15/16	3-15/16	3-15/16	3-15/16	3-15/16	4-5/8	4-5/8	4-5/8	4-5/8	5-5/8	5-5/8

DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES FRACTIONS ±1/64.

① INACTIVE FOR NEW DESIGN AFTER 17 MARCH 1953. NO SUPERSEDING AN STANDARD.

① FOR DEFINITION AND APPLICATION OF DRAWING STATUS NOTES, SEE ANA BULLETIN NO. 337.

APPROVED 26 Dec 42 REVISED ① 17 Mar 53

NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

NOTE: This drawing was approved by joint action of the Air Force and Navy Departments as the Air Force-Navy standard for this product. This drawing supersedes all antecedent standard drawings for the same product and shall become effective for the procurement of aeronautical supplies, or for use in new designs, not later than 6 months after the latest date of approval shown.

AIR FORCE-NAVY AERONAUTICAL DESIGN STANDARD

PROPELLER HUBS – STANDARD DIMENSIONS FOR GROUND – ADJUSTABLE

AND10527

SHEET 3

NOT A PART NUMBER

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:29Z
Check the source to verify that this is the current version before use.