MILITARY SPECIFICATION

ZIRCONIUM CARBIDE, POWDERED, TECHNICAL

This Interim Amendment is approved for use within the US Army Armament, Munitions and Chemical Command, with DOD-Z-82674(OS), dated 23 November 1977

PAGE 1

* 1.1. Scope. Change "one type" to "two types".

Add the following paragraph:

"1.2 Classification. The zirconium carbide shall be of the following types:

Type I - For general use.

Type II - For use in propellant for the M864 system.

Both types shall conform to the same requirements and properties as given in this specification."

* 2.1 Issues of documents. Add the following:

"SPECIFICATIONS

FEDERAL

PPP-D-723 - Drums, Fiber

MILITARY

MIL-B-117 - Bag, Sleeve and tubing - Interior packaging
MIL-B-46506 - Box, Ammunition Packing, Wood, Wirebound
MIL-F-50449 - Filler, Sheet Form (for use in Ammunition Containers)."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:21Z
Check the source to verify that this is the current version before use.

2.2 Other publications. Under "National Motor Freight Classification, delete "Traffic Order Section" and substitute "Traffic Department". Under ASTM E146 "add the following: "ASTM D3951 - Standard practice for Commercial Packing."

PAGE 6

4.7.9 Average particle diameter Delete "6.73 sample" and substitute "a 6.73 g sample accurate to ± 0.01 g".

* 5. Packing. Delete this title and substitute "PREPARATION FOR DELIVERY."

* 5.1 Packaging and packing. Delete this paragraph in its entirety and substitute the following:

"5.1 Packaging and Packing.

5.1.1 Level A. - Unless otherwise specified in the contract or purchase order, the zirconium carbide shall be packed in non-returnable fiber drums in accordance with Specification PPP-D-723, (Type III, Grade A.) The drums shall be finished with a normal 0.0004 inch thick polyethylene liner, properly heat sealed or otherwise closed to afford protection to the contents equivalent to that given by a heat seal closure. The drum shall now be placed in a barrier bag constructed from material conforming to Style 1, Type I, Class E, MIL-B-117. The bag shall be heat sealed. The bagged drum shall be placed in a tight fitting wirebound box conforming to Type I, Class 1, Grade A, MIL-B-46506. The box shall be lined with mandatory fillers conforming to MIL-F-50449. Use additional fillers as required for tight pack.

5.1.2 Level B. - Level B packaging shall be the same as Level A, except, the barrier bag and mandatory fillers shall be eliminated. However, continue to use fillers as required for tight pack.

5.1.3 Level C. - Unless otherwise specified in the contract or order, packaging and packing shall be in accordance with ASTM D-3951.

* 6.1 Intended use. Add "and for M864 propellant component".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:21Z
Check the source to verify that this is the current version before use.

"The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the revious amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment."

Custodian:
Navy-OS

Preparing activity:
Army-AR

(Project 6810-A012)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:21Z
Check the source to verify that this is the current version before use.