MIL-A-82667/2(OS)
AMENDMENT 2
27 June 1985
SUPERSEDING
AMENDMENT 1
18 September 1978

MILITARY SPECIFICATION SHEET

AMMONIUM PERCHLORATE, CONDITIONED

This amendment forms a part of Military Specification Sheet MIL-A-82667/2, dated 31 January 1977.

PAGE 1

* 1.1, line 2: Delete "two" and substitute "three".

1.2, Type I: Add "Class 3 - Ground crystals (5 - 6 µm)".

* 1.2: Add "Type III Class 1 - whole crystals (200 µm)
Class 2 - whole crystals (45 µm)"
Class 3 - ground crystals (8 - 13 µm)".

2.1, under "SPECIFICATIONS": Delete "MIL-D-3464" and its title.

PAGE 2

2.1: Delete "MIL-STD-129" and its title.

2.2: Delete "CODE OF FEDERAL REGULATIONS....and supplements thereto.)".

PAGE 3

3.1, line 7: Following "13 µm." insert "Type I Class 3 shall be Type I crystals ground to a particle size of 5 to 6 µm."

* 3.1: Add the following to end of paragraph, "Type III Class 1 and Class 2 shall be solid white crystalline ammonium perchlorate consisting of essentially whole crystals with rounded corners and edges. Type III Class 3 shall be Type III Class 1 crystals ground to a particle size of 8 to 13 µm."

* 4.5, line 3: After "4.7." add new sentence: "Type III tests shall be as specified in Table I".

FSC 6810

DISTRIBUTION STATEMENT A

APPROVED FOR PUBLIC RELEASE, DISTRIBUTION IS UNLIMITED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:20Z
Check the source to verify that this is the current version before use.

PAGE 4

* Add the following to Table I:

"Type III

	Minimum	Maximum	Test Method
Purity	99.0		4.6.1
Chloride, as NH_4Cl	--	0.03	4.6.2
Chlorate, as NH_4ClO_3		0.02	4.6.3
Bromate, as NH_4BrO_3		0.003	4.6.4
Sulfate Ash, as H_2SO_4	--	--	--
Sulfated Ash, Calculated as $NaClO_4$	--	0.8	4.6.5
Iron, as Fe_2O_3	--	0.001	4.6.6
Sodium and Potassium	--	0.08	4.7.6
Tricalcium Phosphate, as $Ca_3(PO_4)_2$	0.20	0.35	4.6.7
Moisture, total	--	0.05	4.6.8
Moisture, surface	--	0.025	4.6.9
Water Insolubles	--	0.35	4.7.10
Acid Insolubles	--	0.04	4.6.10
pH	5.5	6.5	4.6.11
Granulation, Classes 1, 2, Class 3	Table II or IV		4.6.12 4.6.13"

PAGE 5

* Table II: Change Table heading to: "Type I Class 1 and Type III Class 1 Particle Size."

* Add Table IV as follows:

"TABLE IV - Type III Class 2 Particle Size.

U.S. Standard Sieve No.	Percent passed by the size sieve shown	
	Minimum	Maximum
150	98	--
230	90	98
270	75	90
325	55	75"

PAGE 6

4.6.1, at end of paragraph: Add "N = normality of standard silver nitrate solution".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:20Z
Check the source to verify that this is the current version before use.

PAGE 13

* 4.6.12: Change paragraph heading to: "Type I Class 1 and Type III Class 1 particle size."

* 4.6.13: Delete and substitute:

"4.6.13 Type I, Class 2 and 3, Type III, Class 3 particle size.

The Particle size for Type I Class 2, Type I Class 3 and Type III Class 3 shall be determined in accordance with ASTM B 330-65."

PAGE 14

4.7.1, at end of paragraph: Add "W = weight of specimen, g."

PAGES 18 and 19

5.1, 5.1.1 and 5.2: Delete and substitute:

"5.1 Preservation. Preservation shall be level A in accordance with MIL-A-82667.

* 5.2 Packaging. Type I, Class 2 and Class 3 and Type III, Class 3 ammonium perchlorate shall be packaged in accordance with level A of MIL-A-82667. Type I Class 1, Type II, and Type III, Class 1 and Class 2, ammonium perchlorate shall be packaged in accordance with level C of MIL-A-82667."

* 5.3 Marking. Type I, Class 2 and Class 3 and Type III, Class 3 ammonium perchlorate shall be marked in accordance with level A marking of MIL-A-82667. Type I Class 1, Type II, and Type III, Class 1 and Class 2, ammonium perchlorate shall be marked in accordance with level C marking of MIL-A-82667."

PAGE 19

* 6.1, line 1: Delete "aoxidizer" and substitute "an oxidizer".
line 2: Delete "Type I" and substitute "Type III, Class 1 and Class 3".
line 2: Add "Type I, Class 3 is intended to be used in propellant in accordance with MIL-P-82680 for the CKU-7/a rocket catapult."

* 6.1: Add new sentence at end of paragraph, "The Type III material is to be used in the Mk 23 Mod 2 Rocket Motors."

6.2.1: Delete "(b) Quantity required" and substitute "(b) Quantity, type and class required."

Delete "(f) Packaging...(see 5.1.1)" and substitute "(f) Safety precautions (see 6.7 and 6.9)".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:20Z
Check the source to verify that this is the current version before use.

6.2.2, below "Applicable DID*": Insert "DI-T-3721".

PAGE 21

* Add new paragraphs:

"6.9 Explosive hazard classification. Type I Class 2 and Class 3 and Type III Class 3 ammonium perchlorate in accordance with this specification are Class A explosives. The contracting officer is directed to section 5 of MIL-A-82667 and NAVSEAINST 8023.1 for additional information.

6.9.1 Hazard notice. The ammonium perchlorate described herein is an oxidizing material and/or high explosive and consequently presents a hazard in manufacture, handling, storage and shipment. The contractor should recognize this hazard and take appropriate measures to guard and protect against fire, explosion, adverse environment, corrosive atmosphere, rough handling and electrically induced incidents."

NOTE: The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing Activity:
NAVY - OS

Project No. 6810-NB44

☆U.S. GOVERNMENT PRINTING OFFICE: 1985 — 505-038/23263

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:20Z
Check the source to verify that this is the current version before use.