MILITARY SPECIFICATION

CARTRIDGE, IMPULSE, CCU-22/A ASSEMBLY

* This amendment forms a part of Military Specification MIL-C-82651, dated 31 January 1977, and is approved for use by all Departments and Agencies of the Department of Defense.

Page 2

* 2.1 After "MIL-STD-810 Environmental Test Methods", insert:

"MIL-STD-1168 Ammunition Lot Numbering"

2.1, under "DRAWINGS": Insert the following:

"Naval Air Systems Command (Code Ident 30003)
736AS159 Shear Pin"

delete "11740613 Shear Pin"

Page 3

* 3.4.1 Delete and substitute:

"3.4.1 Explosive components. All explosive components, including but not limited to ignition powders and igniters, shall be manufactured within the 12 months prior to the contract scheduled delivery date for the assembly lot. Primers shall be manufactured or requalified within the 12 months prior to the contract schedule delivery date for the assembly lot."

* 3.4.2 Change "... cartridge assemblies lot." to "... assembly lot."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:19Z
Check the source to verify that this is the current version before use.

Page 4

3.8: Delete and substitute:

"3.8 Shear pin strength. Each lot of shear pins in accordance with drawing 736AS159-2 shall be tested in accordance with 4.5.7. Shear pins shall shear (double shear) when subjected to a load of 58 - 63 lbs applied at a rate of .125 inches per minuts."

* 3.11.1: Delete and substitute:

"3.11.1 Production lot designation. The production lot number shall follow MIL-STD-1168. The construction of the lot number shall be as follows:

IHM75D002-007
a b c d e

where:

a = Manufacturer's Identification Code
b = The year of manufacture of the oldest batch of propellant in the lot.
c = The month of manufacture of the oldest batch of propellant in the lot expressed as an alpha code in accordance with 4.1.3 of MIL-STD-1168.
d = Lot interfix number (controlled by Naval Ordnance Station, Code 5152, Indian Head, MD 20640 or procuring activity).
e = Lot sequence number - lot number (manufacturer is responsible for the assignment of lot numbers)."

Page 6

4.4.1.2: Delete and substitute:

"4.4.1.2 Vibration. The cartridge assembly shall be subjected to random vibration in accordance with procedure IA of Method 514.2 of MIL-STD-810 for 6 hours with 2 hours on each axis. Before vibration, units shall be temperature conditioned in accordance with TABLE II. The input vibratory acceleration shall be in accordance with curve A of Figure 514.2 - 2A with a Wo factor of $0.1G^2/Hz$. If the cartridge assembly must be removed from the environmental conditioning chamber or if the temperature falls outside the specified temperature limits for a period of more than 5 minutes, the testing shall be stopped and the unit shall be reconditioned. A reconditioning time of 2 minutes for every minute the

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:19Z
Check the source to verify that this is the current version before use.

unit is outside the specified temperature envelope shall be required. A continuous temperature history of the unit shall be kept for all conditioning and testing time. Unless otherwise noted, the cartridge assembly shall be mounted on a test fixture in a manner that will simulate actual catapult/seat/aircraft installation and excited through the attachment fittings.

In addition to compliance with paragraph 4.5.2 of Method 514.2, the cartridge shall comply with the gun fire vibration test of Method 519.2 for those applications whereby guns are installed on the aircraft. However, if the maximum test spectrum level of the gunfire configuration is equal to or less than the above specified test levels, the gunfire vibration test is not required."

Page 10

4.5.7, line 3: Delete "41 ± 5 lbs" and substitute "58 - 63 lbs (double shear)".

Page 13

6.4.2, line 4: Delete "from 6 inches before to 6 inches after separation" and substitute "from separation to 12 inches after separation."

Page 15

6.11, line 1: Delete "rocket catapult" and substitute "cartridge assembly".

Marginal notation. The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of the document based on the entire content irrespective of the marginal notation and relationship to the last previous issue.

Custodian:
NAVY - OS
AIR FORCE - 99

Preparing Activity:
NAVY - OS

Project Number:
1377-0712

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:19Z
Check the source to verify that this is the current version before use.