MILITARY SPECIFICATION

VALVE, CONTROL

This amendment forms a part of Military Specification MIL-V-23254C(AS), dated 10 May 1984, and is approved for use within the Naval Air Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.1 under STANDARDS, MILITARY, delete title of MIL-STD-810 in its entirety and substitute: "Engineering Test Methods and Engineering Guidelines".

2.1.2 Naval Air Systems Command, under DL 58A164D810, add: "58A164D859 Valve, Seal".

PAGE 5

3.3 Design and construction, second line, delete "with DL 58A164D810" and substitute: "with the drawings listed in DL 58A164D810".

3.3.6 Identification of parts, last line, delete "in DL 58A164D810." and substitute: "on the drawings listed in DL 58A164D810."

PAGE 6

3.4 Construction, first and second lines, delete "with DL 58A164D810" and substitute: "with the drawings listed in DL 58A164D810".

3.8.1 High temperature, second line, delete "501" and substitute: "501.2".

3.8.2 Low temperature, second line, delete "502" and substitute: "502.2".

3.8.3 Temperature shock, second line, delete "Method 3" and substitute: "Method 503.2".

PAGE 7

3.8.4 Dust, last line, delete "510" and substitute: "510.2".

3.8.5 Salt fog, second line, delete "509" and substitute: "509.2".

3.8.6 Humidity, second line, delete "507" and substitute: "507.2".

3.8.8 Shock, second line, delete "516, Figure 516-2" and substitute: "516.3".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:03Z
Check the source to verify that this is the current version before use.

PAGE 10

Revise table I as follows:

a. For test N, in column for sample D, add: "10".

b. For test P, in column for sample D, delete "10" and substitute: "11".

c. For test Q, in column for sample D, delete "11" and substitute: "12".

d. For test T, in column for sample D, delete "12" and substitute: "13".

PAGE 15

4.6.8.1 High temperature, second line, delete "501" and substitute: "501.2".

4.6.8.2 Low temperature, revise as follows:

a. On second line, delete "502" and substitute: "502.2".

b. On third line, delete "-45°C" and substitute: "-54°C".

4.6.8.3 Thermal shock, second line, delete "503" and substitute: "503.2".

4.6.8.4 Dust, revise as follows:

a. On second line, delete "510" and substitute: "510.2".

b. On last line, delete "4.6.3.2 and 4.6.3.3" and substitute: "4.6.3 and 4.6.5."

4.6.8.5 Salt fog, revise as follows:

a. On second line, delete "509" and substitute: "509.2".

b. On last line, delete "4.6.3" and substitute: "4.6.3 and 4.6.5."

4.6.8.6 Humidity, revise as follows:

a. On second line, delete "507" and substitute: "507.2".

b. On last line, delete "4.6.3.2 and 4.6.3.3" and substitute: "4.6.3 and 4.6.5."

PAGE 16

4.6.8.7.2 Control valve operation, last line, "delete "4.6.3 and 4.6.3.3" and substitute: "4.6.3 and 4.6.5."

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:03Z
Check the source to verify that this is the current version before use.

PAGE 18

4.6.11 Shock, second line, delete "516", Procedure I, Figure 516-2" and substitute: "516.3, Procedure I".

PAGE 19

6.2.2 Data requirements, eighteenth line, delete "DoD-5000.19L., Vol II, AMSL" and substitute: "DoD 5010.12-L, AMSDL".

Preparing activity:
Navy -AS
(Project No. 1055-N077)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:03Z
Check the source to verify that this is the current version before use.