INCH-POUND

A-A-58045
May 26, 1995

COMMERICAL ITEM DESCRIPTION

TRACTOR,WKEELED,AIRCRAFT TOWING

The General Services Administration has authorized the use of this commercial item description by all federal agencies.

1. SCOPE. The new commercial aircraft towing tractor, herein after called tow tractor must be capable of towing military aircraft up to 500,000 pounds, under all weather conditions on level pavement. The tow tractor will have a maximum weight of 40,000 pounds with a minimum drawbar pull of 27,000 pounds. The primary intended use of this tow tractor is to tow military aircraft on U.S. Air Force installations.

2. SALIENT CHARACTERISITICS. Failure of the tow tractor to meet the above and the following salient characteristics will require rejection of the offer. The tow tractors shall be free from faulty construction or any defect which affects appearance, serviceability, and durability. The loaders shall be representative of the quality and workmanship found in tow tractors offered for new commercial sale.

2.1 Gross Weight: Tow tractors shall have a maximum gross vehicle weight (GVW) of 40.000 pounds.

2.2 Drawbar Pull: Tow tractors shall have a minimum drawbar pull (DBP) of 27.000 pounds on dry level concrete.

2.3 Air Ttansportability: The tow tractor shall be capable of being transported in a C-141 military transport aircraft. The requirements for this are contained in MIL-STD-1791.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be addressed to WR-ALC/TILC, with copy to WR-ALC/LVKB Robins AFB, GA 31098-5609, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1740

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:59Z
Check the source to verify that this is the current version before use.

2.4 Engine Type: Tow tractor shall have a diesel engine and powetrain sufficient to develop the required drawbar pull. Diesel engine shall be suitable for operation on JP-8 or Jet A-1 fuel.

2.5 Running Gear Design: Tow tractor shall have four wheel drive and four wheel steerng. Four wheel steering shall feature both crab and coordinated steering. Tow tractors which feature electronic four wheel steering shall comply with EMI requirements of SAE J511. Wheelwells shall be designed so that tire chains may be used without interference.

2.6 Mobility: Tow tractor shall be capable of traveling a minimum of 15 MPH forward and 2.5 MPH in reverse.

2.7 Brake System: Tow tractor shall feature hydraulic operated brakes.

2.8 Perking Brake: Tow tractor shall be equipped with a mechanically actuated disc type parking brake.

2.9 Electrical System: Tow tractor shal 1 feature a 12v electrical system

2.10 Cab design: Tow tractor shall be equipped with an enclosed two man cab. Interior cab sound level shall not exceed 84 dB(A) with doors and windows closed. Cab instrumentation shall be standard commercial installation. Cab shall be equipped with wipers, mirrors, visors, heater/defroster, ventilating fan, interior dome light and other equipment as found in standard commercial offering.

2.11 Lighting: Tow tractor lighting shall be equivalent to the standard commercial offering. A flashing beacon light shall be mounted on the cab roof.

2.12 Pintles: Tow tractor shall be equipped with front and rear pin and clevis type coupler or jaw type(MS511 18-2) pintle hook located 24 inches above the ground.

2.13 Winterization: When requested, vehicle shall be equipped with winterization equipment making the vehicle suitable for storage at -60 degrees F and operation at -40 degrees F.

2.14 Fire Extinguisher: Tow tractor shall be equipped with a dry chemical type fire extinguisher.

2.15 Finish: Tow tractor shall be painted Dark Green (Color 24052, FED-STD-595) using offeror's standard commercial paint system.

2.16 Visibility: Tow tractor shall be so constructed as to provide maximum visibility in all directions. Rearward visibility shall be provided within an envelope defined by a point fifteen feet from the rear of the tractor and 30 inches from the ground to a point one foot behind the tractor and 54 inches above the ground.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:59Z
Check the source to verify that this is the current version before use.

2.17 Safety: Tow tractors offered under this specification shall comply with applicable safety requirements imposed on vehicles of this type in the commercial market.

3. QUALITY ASSURANCE PROVISIONS.

3.1 Contractor Certfication: The contractor shall certify that the product offered meets the salient characteristics of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and qaulity assurance practices, and is the same product offered for sale in the commercial marketplace. The government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

MILITARY INTEREST:

CUSTODIAN:
AIR FORCE--99

PREPARING ACTIVITY:
AIR FORCE--84

AGENT
AIR FORCE 99

Project Number 1740F174

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:59Z
Check the source to verify that this is the current version before use.