[INCH-POUND]

A-A-58048
29 SEP 1995

COMMERCIAL ITEM DESCRIPTION

GUARD, SAFETY, TIRE INFLATION

The General Services Administration has authorized
the use of this Commercial Item Description.

1. SCOPE. This Commercial Item Description is for a tire safety guard used for inflating truck tires and for limited use on smaller aircraft tires. The unit features a computerized inflator, pressure tank, sliding doors-left and right, a jet bead seater and expanded metal frame.

2. SALIENT CHARACTERISTICS. The tire inflation cage shall be constructed of high tensile steel and welded throughout. Construction of the inflation cage shall be durable enough to sustain the blast from the exploding tire. It shall be deflected to a minimum of 5 to 15% of the original pressure at a distance of 2ft from the chamber. The self-closing side doors shall have completely covered frames to prevent parts with bolt-together-rims from flying out during a rim separation The front must have roll-out capability of the tire after inflation.

2.1 Pressure Regulator. A pressure regulator that can handle an inlet of 300 bar of pressure and outlet of 20 bar shall be provided with the unit. The unit requires 145 psi air outlet.

2.2 Inflator. The maximum pressure shall be 20 bar. A maximum pressure range of 40 psi with manual over-ride features of 60 psi is also required. The inflator shall be capable of overinflating and deflating automatically with a calculated amount of air over a specific period of time. The unit shall be capable of changing the desired inflation pressure. The inflator shall not be capable of being set below 1 bar/5 psi overinflation. A battery shall be installed to keep the programmable features in memory in case of power outage. A truck tire shall be inflated in order to ensure that the unit complies with paragraphs 2, 2.1, and 2.2.

Beneficial comments, recommendations, additions, deletions, clarifications, etc and any data which may improve this document should be sent to The Resources and Logistics Services Division, SA-ALC/TILDD, Kelly AFB, TX 78241-5000

AMSC N/A FSC 4910

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:59Z
Check the source to verify that this is the current version before use.

2.3 Life. The overall operational life of the unit shall be designed for a minimum of twenty years.

2.4 Corrosion Resistance. Measures will be taken such that the selection of materials, coatings and design features will be corrosion resistant The industry's proven record of the company's inflation systems in the field will serve as adequate proof of a tested finish.

2.5 Maintainability. A minimum number of parts and tools shall be required for maintenance by design practices such as reducing the variety of bolthead sizes to the practical minimum

2.6 Electrical power requirements The power requirements for this unit shall be 110 volt and 1 phase

2.7 Metric Product. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within specified tolerances using conversion tables contained in the latest revision of Federal Standard No 376 and all other requirements of this Commercial Item Description are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable The contracting officer has the option of accepting or rejecting the product.

2.8 Noise and Noise Test. The unit under any operating condition shall be no noisier than 84dBA slow scale measured not more than four feet from the perimeter of the unit and shall be tested to demonstrate that the noise level meets the noise limit specified herein.

3. REGULATORY REQUIREMENTS

3.1 Classification of tests. The inspection and testing of the unit shall be conducted in accordance with paragraphs 2, 2.1, and 2.2 Classification of the types of failures is described in Appendix A, "Bid Sample Evaluation Criteria".

3.2 Safety. The units shall comply with the Federal OSHA requirements in effect on the date that the proposal is issued. In the event that state and local OSHA regulations are also in effect, the Federal OSHA regulation shall take precedence.

4 QUALITY ASSURANCE PROVISIONS

4.1 Contractor Certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this Commercial Item Description and that the product conforms to the producer's own drawing, specifications, standards and quality assurance practices. The government reserves the rights to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

4.2 Bid Samples. The government will request a bid sample from the contractor that wishes to be considered for contract award A 14 to 30 day evaluation on each bid sample will be made at

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:59Z
Check the source to verify that this is the current version before use.

SA/ALC, LDEE, Building 1562, Kelly Air Force Base, San Antonio, Texas, 78241 Bid samples should be shipped to this address Contractor shall furnish continuous maintenance support (parts and labor) during the evaluation

5. PACKAGING.

5.1 Preservation, Packaging, Packing, Labeling and Marking. Preservation, packaging, labeling, and marking shall be specified in the contract or order.

MILITARY INTERESTS

Custodian
Air Force - 99

Review Activity
Navy - YD
DLA - CS

Preparing Activity
Air Force - 82

Agent
Air Force - 99

Project Number
(4910-0788)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:59Z
Check the source to verify that this is the current version before use.