INCH-POUND

A-A-58048C
25 March 2004
SUPERSEDING
A-A-58048B
10 April 2002

COMMERCIAL ITEM DESCRIPTION

GUARD, SAFETY, TIRE INFLATION

The General Services Administration has authorized the use of this Commercial Item Description.

1. SCOPE

1.1 Scope. This Commercial Item Description (CID) is for a tire safety cage used for inflating large truck and aircraft tires. The cage is limited in use to tires with a pressure rating of 232 psi. The cage features is in compliance with AFOSH 91-20.

2. SALIENT CHARACTERISTICS

2.1 Inflation Cage. The tire inflation cage shall be constructed of high tensile steel or equivalent material and shall be welded throughout. Construction of the inflation cage shall be such that it will be able to retain the blast and debris generated by tires during a tire explosion. The tire cage must have roll-out and roll-in capability of the tire. The tire cage shall be provided with a jet bead seater.

2.2 Pressure Regulator. A pressure regulator that can handle an inlet of 300 psi of pressure and outlet of 20 psi shall be provided with the unit.

2.3 Inflator. The inflator shall be capable of inflating, deflating and inflating to a preset pressure. The inflation pressure setting that is being applied to the tire shall be capable of being changed.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: The Resources and Logistics Services Division, WR-ALC/LEEE, Warner Robins AFB, GA. 31098

AMSC N/A FSC 4910

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:59Z
Check the source to verify that this is the current version before use.

2.4 Performance. The tire cage shall be a minimum of 32 inches wide, 64 inches long, and 64 inches high. The tire inflation cage shall have the capacity to withstand the maximum force that would be transferred to it during a tire wheel separation occurring 150% of the maximum tire specification pressure for the type of wheel being serviced in accordance with AFOSH-STD 91-20, Chapter 8. The cage shall be constructed so as to contain the debris emanated from a wheel tire failure with a maximum force of 348 psi.

2.5 Life. The overall operational life of the unit shall be designed for a minimum of twenty years.

2.6 Finishing. Measures shall be taken such that the selection of materials, coatings and design features shall be corrosion resistant. The tire cage shall be painted dark green.

2.7 Maintainability. A minimum number of parts and tools shall be required for maintenance by design practices such as reducing the variety of bolt-head sizes to the practical minimum.

2.8 Power requirements. The power requirements for the tire inflator system shall be 110 volt AC, single phase. The tire cage shall be capable of servicing tires from a compressed nitrogen supply source, 300 PSIG, 20 CFM.

2.9 Metric Product. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within specified tolerances using conversion tables contained in the latest revision of FED-STD-376 and all other requirements of this Commercial Item Description are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable the contracting officer has the option of accepting or rejecting the product.

2.10 Noise and Noise Test. The unit under any operating condition shall be no noisier than 84dBA slow scale measured at four feet from the perimeter of the unit and shall be tested to demonstrate that the noise level meets the noise limit specified herein.

2.11 Classification of tests. The inspection and testing of the unit shall be conducted in accordance with paragraphs 2.1 through 2.10. Failure of the unit to meet the inspection and testing requirements as stated in this specification will be considered as a failure of the unit. The unit and manufacturer will be removed as a considered source for solicitation**.**

2.12 Safety and health requirements. The manufacturer shall ensure that the units shall be in compliance with Occupational Safety and Health Administration (OSHA) 3086 and AFOSH-STD 91-20 that apply and that are in effect on the date that the proposal is issued.

3. REGULATORY REQUIREMENTS

3.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:59Z
Check the source to verify that this is the current version before use.

4. PRODUCT CONFORMANCE PROVISIONS

4.1 Product Conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices and be the same product offered for sale in the commercial market. The Government reserves the right to require proof of such conformance.

4.2 Market Acceptability.

4.2.1 Documentation. Literature describing the safety guard, performance characteristics and testing data or calculations showing that it meets the safety pressure requirements of this CID.

a. Literature describing the safety guard and performance characteristics (catalogs, brochures, specification sheets).

b. Set of drawings for the unit. This shall include drawings for major components. Documentation showing that the same unit has been sold to the government. If substantially identical production units have been sold to the government, evidence to allow the government to substantiate the safe, reliable performance and satisfactory quality of the production units must be submitted with the offeror's request for waiver of bid samples. This evidence shall include contract numbers, quantities sold, location of the procuring activity and names and telephone numbers of the contracting officer. The government reserves the right to make a determination as to whether this condition has been met, by making use of any evidence submitted by the offeror as well as evidence available within official government records. The units must have a proven record of performance showing that they are safe, reliable and satisfactory in performance, materials and quality of construction.

c. Documentation showing that the same unit has been sold commercially. Substantially identical production units have been sold to commercial customers in sufficient quantities so as to demonstrate the reliability of the units in their application, performance, safety and acceptance of the units by the commercial market through continued procurement and usage.

d. Failure to submit adequate documentation to substantiate items subparagraphs (a) through (d) above will be cause for bid sample submittal.

4.3 Production units. All production units delivered under this contract shall have the same parts, part numbers, configuration, materials, and process as those of the approved bid sample. In addition, production units shall be fabricated from the same parts and part numbers (original manufacturer's part numbers) being that those components and part numbers were utilized on the approved bid sample. No substitute part numbers will be allowed.

5. PACKAGING.

5.1 Preservation, Packaging, Packing, Labeling and Markings. Preservation, packaging, labeling, and marking shall be specified in the contract or order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:59Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Sources of referenced documents.

6.1.1 Government documents. Copies of federal documents may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402

FEDERAL STANDARD

FED-STD-376	Preferred Metric Units for General use by the Federal Government

6.1.2 Other government documents. Copies of Air Force occupational safety and health standards referenced in this CID may be obtained electronically at: http://afpubs.hq.af.mil

AIR FORCE OCCUPATIONAL SAFETY AND HEALTH STANDARD (AFOSH)

AFOSH 91-20	Vehicle Maintenance Shops - Chapter 8, Tire and Wheel Maintenance Tire Servicing Equipment

6.1.3 Industry standards. Copies of industry standards referenced in this CID may be obtained from the following addresses:

OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)

Occupational Safety and Health Administration (OSHA) 3086.

Applications for copies should be sent to the U.S. Department of Labor, 200 Constitution Avenue NW, Room 423, Washington, DC 20210.

6.2 Changes from previous issue: The margins of this specification are marked with asterisks to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:59Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodian:
Air Force – 99

Reviewer:
DLA – CC

CIVIL AGENCY COORDINATING ACTIVITY:

GSA – FSS

Preparing Activity:
Air Force – 84

Agent:
Air Force – 99

Project Number (4910-0002)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at www.dodssp.daps.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:59Z
Check the source to verify that this is the current version before use.