[INCH-POUND]
A-A-58053
08 DEC 95
SUPERSEDING
MIL-B-87986

COMMERCIAL ITEM DESCRIPTION

BEAD BREAKER, PNEUMATIC TIRE

The General Services Administration has authorized the use of this commercial item description as a replacement for MIL-B-87986 for all federal agencies.

1. SCOPE

1.1 Scope This commercial item description covers a pneumatic tire bead breaker rated at ten tons It is hydraulic in operation and is powered by an explosion proof electric motor. It is intended to be used to break the beads of divided wheel aircraft tires ranging in size horn 15-58 inches diameter and 4-22 inches wide

2. SALIENT CHARACTERSTICS

2.1 Functional requirements. The bead breaker shall provide a means of breaking the beads of tires from divided wheel aircraft rims using ring adapters. It shall be capable of being operated by one person Changing adapter ring sizes shall be the only changes to the bead breaker required when changing tire sizes. The machine shall break both beads of the tire with one actuation without damage to either tire or wheel. An instructional panel shall be affixed to the bead breaker. Instructions shall be clear, concise, and sufficient to enable operation of the machine without damage or injury to the operator. The panel shall be readily visible from the operators position. The bead breaker shall be finished to protect against corrosion normally found in a shop/hanger environment. The shipping weight shall not exceed 2,000 pounds.

2.2 Hydraulic system. The hydraulic system shall consist of an electrically powered pump and all components and fittings necessary for safe, reliable operation and shall be compatible with fluid conforming to MIL-H-5606. All controls shall be permanently marked as to operation and shall be capable of being operated by a person wearing heavy gloves. Controls shall be smooth and non erratic.

2.3 Electrical requirements. Electrical equipment and wiring provided shall conform to the National Electrical Code, NFPA 70. The explosion proof electric motor shall conform to Undenvriters Laboratories Class I, Group D, designed for connection to 220/440 volts, 3 phase, 60 hertz electrical power unless otherwise specified in the contract or purchase order.

Beneficial comments, recommendations, additions, deletions, clarifications, etc and any other data which may improve this document should be sent to San Antonio ALC/TILDD, 485 Quentin Roosevelt Rd Kelly AFB, Tx 78241-6425

AMSC N/A FSC 4910

DISTRIBUTION STATEMENT A. Approved for public release, disribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:59Z
Check the source to verify that this is the currentversion before use.

2.4 Ring adapters The bead breaker shall be capable of adapting to the specified ring adapters identified in Table 1. Ring adapters shall be easily changed and shall have permanent rubber pads wherever the adapter rings contact the wheels.

3. QUALITY ASSURANCE PROVISIONS

3.1 Contractor Certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this commercial item description, and that the product conforms to the producers own drawings, specifications, standards, and quality assurance practices. The government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

3.2 Bid Sample. When specified in the contract or purchase order, a bid sample shall be provided for government verification of compliance with the following inspection(s).

3.2.1 Static Proof Load. The bead breaker shall be capable of exerting a 15 ton force between the cylinder and the stationary ram.

4. PACKAGING

4.1 Preservation, Packing, and Marking. Preservation, packing, and marking shall be as specified in the contract or purchase order.

5. NOTES

5.1 National Stock Numbers. The following NSN corresponds to this CID. The NSN may not be indicative of all possible NSNs associated with this CID.
4910-01-245-2865

5.2 Subject term (key word) listing.
Bead breaker, pneumatic tire
Divided wheel, pneumatic aircraft tire
Tire, pneumatic, bead breaker

MILITARY INTERESTS
Custodians
Navy -
Air Force -99
Army -

Review Activity
DLA - CS

Preparing Activity
Air Force -82

Agent Activity
Air Force -99

(Project 4910-0800)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:59Z
Check the source to verify that this is the current version before use.

Table I
Ring Adapter Sizes

Part Number	NSN
120D153/34"	4910-01-332-5546
120112500/27″	4910-01-332-5547
120D167/22"	4910-01-332-554$
120D151/19"	4910-01-121-8523
120D126-2/17.5"	4910-01-332-8735
120D188/15.5"	4910-01-332-5549
120D187/14"	4910-01-332-8736
120D147/13"	4910-01-332-5550
120D180/12"	4910-01-332-5551
120D162/10"	4910-01-332-8737
120D186/8"	4910-01-332-5552

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:59Z
Check the source to verify that this is the current version before use.