INCH-POUND

A-A-58056
1 April 1996

COMMERCIAL ITEM DESCRIPTION

Mechanical Street Sweeper, Minimum 3 Cubic Yard Capacity

This commercial description covers a self propelled riding type, diesel engine driven, high dust control, street sweeper.

Salient Characteristics. The street sweeper shall possess, but shall not be limited to, the following characteristics. All necessary systems and components not specified herein shall be the manufacturer's standard.

Physical dimensions.

a. Overall width: 70 inches maximum.
b. Overall length: 169 inches maximum.
c. Overall Height: 100 inches maximum.
d. Weight: 12,500 pounds maximum.

Drive system. The system shall be the manufacturer's standard, water cooled, diesel engine. Minimum 90 hp engine is required. The engine shall operate satisfactorily on grade JP-4 and grade JP-5 fuel conforming to MIL-T-5624 under emergency, short duration conditions and on grade JP-8 fuel conforming to MIL-T-83133 under normal conditions. The unit shall be equipped with a hydrostatic transmission. The unit shall be equipped with a hydraulic bypass tow valve and towing hooks.

Steering System. The turning radius shall be no greater than 13 feet. The unit shall be equipped with full time four wheel steering. The tires shall be steel belted radial.

Suspension. The unit shall be equipped with the manufacturer's standard commercial suspension system.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: WR-ALC/LVRE, 225 Ocmulgee Ct, Robins AFB, GA 31098-1647.

AMSC N/A FSC 3825

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:59Z
Check the source to verify that this is the current version before use.

Cab. The unit shall be equipped with a sealed pressurized cab equipped with the following features: heater, defroster, blower, windshield wiper and washer, tinted safety glass, second person seating, power steering, and a filtered cab air intake.

Sweeping Path. The unit shall be equipped with both a minimum 51-inch long cylindrical main brush for loading debris and at least one rotary side brush.

Lighting. The sweeper shall include headlights, taillights, and backup lights. It shall also include, as a minimum, two front floodlights and one rear floodlight.

Dust Control. The sweeper shall be equipped with the manufacture's standard dust control system.

Debris Pickup. The sweeper shall be able to efficiently pick up sand, dirt, rocks, broken glass, and bulky light debris.

Hopper. The unit shall be equipped with a minimum 3 cubic yard stainless steel hopper. The hopper shall be capable of being mechanically dumped.

Auxiliary Side Brush. The unit shall be equipped with an additional rotary brush that the operator can control with a single joy stick from inside the cab. The operator shall be able to adjust both the position of the brush, as well as its tilt hydraulically. The brush shall permit sweeping around obstacles and on top of curb areas inaccessible to the sweeper's conventional side brush.

Auxiliary equipment. The following-shall be provided:
a. The unit shall be equipped with a high capacity vacuum hose attachment suitable for pick up of wet or dry debris. The hose inlet shall have a minimum 6-inch OD and 12-foot length.

b. The unit shall be equipped with an audio backup alarm.

Painting. Unless otherwise specified (see Note 1), painting shall be in accordance with manufacturer's standard commercial practice.

Identification marking. A permanently marked identification plate shall be securely attached to the vehicle in a readily accessible location. The identification plate shall contain the following information:

nomenclature
manufacturer's model number

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:59Z
Check the source to verify that this is the current version before use.

manufacturer's serial number
manufacturer's name
manufacturer's address
manufacturer's service phone number
date of manufacture
contract number
national stock number
registration number

QUALITY ASSURANCE

Safety. The sweeper shall conform to all Federal Laws and Regulations governing noise, air pollution and other health and safety requirements which are in effect for this type of equipment at the time of contract award.

The mechanical street sweeper furnished must be the latest model as of the date of award (with minor modifications, as that term is defined in DOD FAR Supplement 252.211-7012, Paragraph K-85 of the solicitation) of an established product previously produced and sold in substantial commercial quantities (exceeding the criteria at FAR 15.804-3(f)(2)(ii)(A)) for at least three years immediately preceding the issuance date of the solicitation. The broom/blower/engine skid furnished, or earlier models of it, absent minor modifications, shall have routinely been supported with spare/repair parts which were produced or sold in the normal course of business. At the time of delivery, the contractor shall furnish the Administrative Contracting Officer with verification of compliance with these requirements.

NOTE TO OFFERORS: Offerors shall provide, as part of their proposals, the following information on the sweeper (or its earlier models) being offered as a commercial item:

(1) Total sales to the U.S. Government or to contractors for U.S. Government use during the three years immediately preceding the issuance date of the solicitation.

(2) Total sales of the item to the general public during the three years immediately preceding the issuance date of the solicitation.

(3) Length of time the item has been sold in the commercial market place.

(4) Points of contact and phone numbers of customers to which the item has been sold in the commercial market place.

(5) Other pertinent information necessary to determine that the item is an established commercial item.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:59Z
Check the source to verify that this is the current version before use.

Contractor certification. The contractor shall certify that the product offered meets the salient characteristics of this description and conforms to the producers' own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Notes.

Note 1. If painting other than manufacturer's standard commercial practice is required, the type of painting and the finish color shall be specified in the contract and/or order.

Note 2. When a turbo charged diesel engine (100 hp, minimum) is required, this requirement shall be specified in the contract and/or order.

Note 3. When a high dump (minimum 72 inches) is required, this requirement shall be specified in the contract and/or order.

Note 4. When factory air conditioning is required in the cab, this requirement shall be specified in the contract and /or order.

Note 5. The required warranty, service and training shall be as specified in the contract and /or order.

Custodian:
AIR FORCE-99

Preparing Activity:
AIR FORCE-84

Project number 3825-0234

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:59Z
Check the source to verify that this is the current version before use.