[INCH-POUND]
A-A-58059
22 March 1996

COMMERCIAL ITEM DESCRIPTION

LATHE, BRAKE DRUM/ROTOR

The General Services Administration has authorized the use of this commercial item description by all federal agencies.

1. SCOPE. This Commercial item description is for a multi-speed combination brake drum/disc lathe. which will be used to service and maintain U.S. Ar Force transporation vehicles and related equipment

2. SALIENT CHARACTERISTICS

2.1 General. The lathe shall be capable of truing and be equipped with accessories for commercial and military passenger vehicle brake drums and disc brake rotors within the sizes specified in this document. The lathe shall be capable of turning brake drums and disc brake rotors weighting up to and including 200 pounds, with wheel removed, within the sizes and accuracy's specified herein. Performance accuracy shall apply after turning/truing the brake drum or disc brake rotor in the lathe and shall be unaffected by the mounting position of the brake drum or disc on the arbor. Unit shall have lathe industry standard paint color and type.

2.2 Performance specifications. The lathe specifications shall not be less than those shown. Where a range is indicated the required performance shall be from and including the smaller figure or less to and including the larger figure or more.

Parameter	Range
a. Drum diameter range	6 inches -28 inches (ID)
b. Drum friction surface depth of cut range	1 to 8 recks
c Drum cutting feed rate range (feeds/rev)	0.0015 to 0.015 inches (infinitely variable)
d Drum cutting feed rate range (feeds/mm)	0.3750 to 15 inches (infinitely variable)
e Rotor diameter range	4 to 24 inches
f. rotor width range	0.125 to 4.5 inches
g rotor cutting feed rate range (feeds/rev)	0.001 to 0.010 inches (infinitely variable)
h Rotor cutting feed rate range (feeds/min)	0.25 to 1.0 inches (infinitely variable)
i Spindle speeds (rev/mm)	100-150-200 (3 Positions)
j. Electric power requirements	115 VAC, 1 phase, NEMA 5-20

2.3 Features Units shall have a removable arbor to accept various adapter and arbors and the lathe spindle shall be powered by a minimum of one (1) horsepower drive motor. Feed travel shall not be

Beneficial comments, recommendations, additions, deletions, clarifications, etc and any data which may improve this document should be sent to Technology & Industrial Services Division, SA-ALC/TILDD 485 Quentin Roosevelt Rd , Kelly AFB TX 78241-6524

AMSC N/A FSC 4910

DISTRIBUTION STATEMENT A. Approved for public release distribution is unliminted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

engageable on the drum and rotor feeds at the same time. Cross-slides shall be designed with dovetails ways with adjustments for machine wear. The unit shall be equipped with worklight and integral safety shield and a spindle to run on tapered roller bearings with adjust ments for wear. The boring bar or the twin cutter shall be interchanged by removing one nut, either may be used at any point on either dovetail cross-slide. The unit shall include a workbench with provisions for hanging accessories and a took kit consisting of one (1) disc brake rotor micrometer and one (1) drum wear limit gauge for 8 to 14 inches. The unit shall also Include adapters such as short radius cones, taper cones, sleeves, bushings and spacers.

2.4 Machine accuracy. The lathe and accessories shall not exceed the following tolerances:

a Spindle taper run-out (concentricity) 0.0005 inch total indicator reading (TIR)

b Arbor inn-out (concentricity O 0005 inch TIR at all positions along its length up to 7 inches from the spindle nose and 0.001 TIR inch from 7 to 16 inches and 0.0015 TIR past 16 inches. if applicable.

3. REGULATORY REQUIREMENTS.

3.1 Safety. The unit shall comply with the Federal OSHA and NFPA standards in effect at the time the proposal is issued. The units shall conform to BAR 90 accuracy standards 1 in the event that state and/or local OSHA regulations are also in effect, the Federal regulations shall take precedence.

4. QUALITY ASSURANCE PROVISIONS.

4.1 Contractor Certification. The contractor shall certify and maintain evidence that the product offered meets the salient characteristics of the CID and the product conforms to the producers own drawings, specifications, standards and quality assurance practices. The government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract or purchase order.

4.2 Bid sample. The government reserves the right to request a bid sample if the literature submitted is not adequate. Bid samples shall be subjected to a 15 to 30 business day evaluation. Evaluation criteria is maintained by the procuring activity.

5 . PACKAGING. The preservation. packaging, labeling and marking shall be specified in the contract or purchase order. In general, the units shall conform to all applicable federal and commercial regulations consistent with the lathe industry pracatice.

Custodians
Air Force-99
Army - AL
Navy-YD1
DLA - CS

Preparing activity
Air Force-82

Agent Activity
Air Force-99

(Project No 4910-0489)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.